



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: TLM606

### 6 outlet, 6-ft cord, 900 joule All-metal Protect It! Surge Suppressor



#### Highlights

- 6 outlets / 6 ft. cord
- 900 joule rating
- \$5,000 [Ultimate Lifetime Insurance](#) (USA & Canada only)

#### Description

Tripp Lite's TLM606 surge suppressor offers complete AC surge suppression for comprehensive protection of personal computers, home stereos, televisions, VCRs, DVD players, power tools and other electrical and electronic equipment. Heavy grade AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLM606 offers 6 total outlets, a 6 foot power cord and diagnostic LED to warn of suppressor damage. AC surge suppression rated at 900 joules shields equipment from surges and line noise. Rugged metal housing offers convenient protection of desktop computer equipment and accessories. \$5,000 [Ultimate Lifetime Insurance](#) (USA and Canada Only). PLUG/OUTLETS: Input - 6 ft. AC line cord with NEMA 5-15P plug/Output - 6 NEMA 5-15R outlets ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA 5-15R wall receptacle) FORMAT: Metal strip SUPPRESSION: AC: 150V RMS Clamping/900 joules/330V UL1449 3rd Edition

#### Applications

- Ideal for personal computers, TV/VCR/DVD, stereos, power tools and lamps/lighting

#### Package Includes

- TLM606 surge suppressor
- Instruction manual and warranty information

#### Features

- 6 outlets
- 6 ft. cord
- Surge suppression rating: 900 joules
- EMI/RFI noise filtering
- Diagnostic LED confirms suppressor "protection present" (green)
- Convenient keyhole slots allow secure mounting on wall or desk
- Can accommodate up to 1 transformers without blocking adjacent outlets
- Rugged metal case provides extra safety and durability
- Illuminated on/off switch with integrated 15 amp circuit breaker
- \$5,000 [Ultimate Lifetime Insurance](#) (USA and Canada Only) covers connected equipment

#### Specifications

OVERVIEW	
Intended Application	Home/Office
OUTPUT	

Frequency compatibility	50 / 60 Hz
Output watts	1800
Circuit Breaker (amps)	15
Outlet quantity / type	6 NEMA 5-15R
Transformer accommodation	Supports 1 large transformer without covering adjacent outlets
Outlet orientation	Single row of outlets
<b>INPUT</b>	
Recommended Electrical Service	120V (110-125V)
Input connection type	NEMA 5-15P
Input cord length (ft.)	6
Input cord length (m)	1.8
Input cord gauge, type	14 gauge, SJT
Voltage compatibility (VAC)	120
Maximum Surge Amps	45000
<b>LEDS ALARMS &amp; SWITCHES</b>	
Switches	Illuminated on/off switch with integrated 15 amp circuit breaker
Diagnostic LEDs	Built-in LED confirms suppressor "protection present" (green) status
<b>SURGE / NOISE SUPPRESSION</b>	
AC suppression joule rating	900
AC suppression response time	< 1 ns
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
Clamping voltage (RMS)	150V
UL1449 let through rating	330V - UL Verified
EMI / RFI filtering	Up to 20dB
<b>DATALINE SURGE SUPPRESSION</b>	
Telephone/DSL Protection	No
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
<b>PHYSICAL</b>	
Shipping weight (lbs)	1.6
Shipping weight (kg)	.7
Unit Dimensions (HWD/in)	1.5 x 12.5 x 2.5
Unit Dimensions (HWD/cm)	3.8 x 31.8 x 6.3
Shipping Dimensions (HWD/in)	1.75 x 15.5 x 4.5

<b>Shipping Dimensions (HWD/cm)</b>	4.4 x 39.4 x 11.4
<b>Unit weight (lbs)</b>	1.4
<b>Unit weight (kg)</b>	.6
<b>Material of construction</b>	Metal
<b>Integrated keyhole mounting tabs</b>	Keyhole slots enable mounting to a variety of surfaces
<b>Receptacle Color</b>	Light Gray
<b>AC line cord color</b>	Light Gray
<b>Style</b>	Strip
<b>Form factors supported</b>	Supports floor / wall / desktop placement
<b>Outlets center to center measurement</b>	38.89mm
<b>Keyhole slot center to center measurement</b>	165mm
<b>CERTIFICATIONS</b>	
<b>Additional International Approvals</b>	Complies with RoHS (Restriction of Hazardous Substances Directive)
<b>UL1449 3rd Edition (AC Suppression)</b>	UL1449 3rd Edition
<b>UL1363 (Power Tap)</b>	UL1363
<b>cUL / CSA (Canada)</b>	cUL
<b>Approvals</b>	Exceeds IEEE 587 category A&B specifications
<b>WARRANTY</b>	
<b>Product Warranty Period (Worldwide)</b>	Lifetime limited warranty
<b>Connected Equipment Insurance (U.S., Canada &amp; Puerto Rico)</b>	\$5,000 <a href="#">Ultimate Lifetime Insurance</a>

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=3306](http://www.tripplite.com/en/products/model.cfm?txtModelID=3306).

Copyright © 2012 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.