

2-Line RJ11/RJ45 Network Surge Suppressor for Network/Phone Lines

MODEL NUMBER: DTEL2











Highlights

- RJ11/RJ45 2-line dial-up surge protector
- Protects against the effects of electrostatic discharge, faulty wiring and lightning

Applications

 Ideal for modems, fax and answering machines

Package Includes

- DTEL2 dataline protector
- 5-in. RJ11 telephone patch cable
- Warranty information and instruction manual

Description

Tripp Lite's DTEL2 surge suppressor is designed to protect data and communications equipment against AC transients caused by lightning, electrostatic discharge and ground surges that can enter equipment from the signal lines or chassis ground. The DTEL2 features RJ45/RJ11 plugs for modems, telephone lines and answering or fax machines.

Features

- Protects against the effects of electrostatic discharge, faulty wiring and lightning
- Comes with RJ11 telephone patch cable

Specifications

SELECTOR		
Selector Type	SURGE SUPPRESSORS	
General Info		
Product Group	SURGE PROTECTORS	
TAA Compliant	No	
OVERVIEW		
Intended Application	Home/Office; Computer Networks	
Style	Direct Plug-In	
Surge Style	DIRECT PLUG-IN	
Surge Type	Network/Server	





ОШТРИТ		
Circuit Breaker (amps)	250	
Outlet Quantity / Type	0	
Number of Outlets	1	
INPUT		
Recommended Electrical Service	120V, 230V	
Input Connection Type	RJ11/RJ45	
Input Cord Length (ft.)	0	
UPC ASSIGNMENT		
Unit Carton UPC#	037332010865	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	0	
Clamping Voltage (RMS)	260	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	Yes	
Telephone/DSL Protection Details	1 line	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
Additional Dataline Protection	4,5 & 3,6 pairs	
SPECIAL FEATURES		
KVM Demo Flag	0	
US & Canada Only Flag	0	
Console Server Demo Flag	0	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
	1	

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.