

## 5m Cisco Compatible SFP+ 10-Gigabit Ethernet (10GbE) Twinax Direct Attach Cable

StarTech ID: SFPCMM5M



The SFPCMM5M Cisco Compatible 5m SFP+ cable is a fully hot pluggable, direct attach cable, supporting 10 Gigabit Ethernet and Fiber Channel applications connected through (Small Form Factor Pluggable) SFP+ ports.

Designed for short length, high speed interconnects, this low power, low latency Twinax cable is a cost-effective alternative to fiber optic cable assemblies and is intended for short distance applications such as point-to-point in-rack and across rack network switch/server connections.

Backed by our 2-year warranty, this 10GBASE-CU SFP+ Cable is compliant with MSA (Multi-Source Agreement) standards, making it a reliable replacement SFP-H10GB-CU5M cable.

### Applications

- Use in 10Gb Ethernet and Fiber Channel applications
- Point-to-point in-rack and across rack network switch/server connections (Storage Area Networks (SAN), Network Attached Storage (NAS), Storage Servers, etc.)

### Features

- Compatible with Cisco equipment
- Compliant with SFP+ MSA Multi-Source Agreement standards
- Support for 1x, 2x, 4x and 8x Fiber Channel data rates
- Compliant with SFF 8431 connector standards
- 24AWG, 100 Ohm impedance
- Support for multi-gigabit data rates up to 10.5Gbps
- Hot-swappable with fiber optic modules
- Low Power consumption <0.5W
- Quick release latching SFP+ connectors

### Technical Specifications

Warranty	2 Years
Cable Jacket Type	PVC - Polyvinyl Chloride
Connector A	1 - SFP+ Latching Plug
Connector B	1 - SFP+ Latching Plug
Impedance	100 Ohm
Cable Length	5 m [16.4 ft]
Product Height	12 mm [0.5 in]
Product Length	5 m [16.4 ft]
Product Weight	316 g [11.2 oz]
Product Width	14 mm [0.6 in]
Wire Gauge	24 AWG
Operating Temperature	04/2/2013egC to 704/2/2013egC
Storage Temperature	-404/2/2013egC to 804/2/2013egC
Package Quantity	1
Shipping (Package) Weight	326 g [11.5 oz]
Included in Package	1 - 5m SFP+ 10-Gigabit Ethernet (10GbE) Twinax Cable

### Certifications, Reports and Compatibility

