

DisplayPort® to HDMI® Active Video and Audio Adapter Converter - DP to HDMI - 1920x1200 - White

StarTech ID: DP2HDSW



The DP2HDSW Active DisplayPort® to HDMI® Adapter features audio pass-through support, which enables you to connect both the audio and video that's output from a DisplayPort-equipped desktop or laptop computer to an HDMI monitor, projector, or display.

Unlike a passive adapter, the DP2HDS actively converts single-mode and dual mode DisplayPort output, which is ideal for graphics cards that do not output dual mode/multi-mode (DP++) signals, such as ATI™ Eyefinity cards.

This active DP to HDMI adapter is compatible with Intel® Thunderbolt™, when connected directly to a supporting DisplayPort over Thunderbol I/O port.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Re-purpose an existing HDMI monitor or projector for use with a new DisplayPort-equipped computer or as a secondary display
- Ideal for digital entertainment centers, home offices, business conference rooms and trade show displays

Features

- Supports resolutions up to 1920x1200 (WUXGA)
- Latching DisplayPort connector port
- DisplayPort 1.1a, HDCP 1.3 compliant
- 5.1 Surround Sound Audio Pass-through
- Works with video cards that aren't capable of outputting DP++ (multi-mode) signals

Technical Specifications

Warranty	2 Years
Converter Type	Active
Audio	Yes
Industry Standards	HDCP DisplayPort 1.1a
Output Signal	HDMI
Connector A	1 - DisplayPort (20 pin)
Connector B	1 - HDMI (19 pin)
Audio Specifications	5.1 Surround Sound
Maximum Digital Resolutions	1920x1200
Wide Screen Supported	Yes
Enclosure Type	Plastic
Color	White
Product Length	200 mm [7.9 in]
Product Width	40 mm [1.6 in]
Product Height	15 mm [0.6 in]
Product Weight	29.8 g [1.1 oz]
Humidity	40%-85%RH
Operating Temperature	0°C to 60°C (32°F to 140°F)
Storage Temperature	0°C to 70°C (32°F to 158°F)
Shipping (Package) Weight	0 kg [0.1 lb]
Included in Package	1 - DisplayPort® to HDMI® Active Adapter

Certifications, Reports and Compatibility

