

50 ft 15m Plenum-Rated Coax High Resolution Monitor / Projector VGA Cable - HD15 to HD15 M/M

StarTech ID: MXT101PMM50



The MXT101PMM50 15m plenum-rated VGA cable delivers a high resolution (1920X1200 and above) VGA connection to your monitor or projector, and can be installed through air plenums, ducts, walls, conduits, ceilings, or anywhere else a CMP/FT6 fire rating is required.

This durably constructed coaxial cable features two HD15 (male) connectors and eliminates the picture "ghosting" and fuzzy images that are inherent to non-coaxial cables, while providing superior EMI interference protection by using ferrite cores near the connector ends.

This 50-foot plenum-rated VGA cable is backed by StarTech.com's Lifetime Warranty.

Applications

- VGA display installations where cable needs to be run through air ducts and plenums, where CMP fire rating is required (educational or commercial installations, etc.)
- Connect a high resolution display to a Desktop PC or video switch, up to 50 feet away

Features

- CMP/FT6 Plenum Fire Rating
- 2x VGA HD15 male connectors
- Triple coaxial + twisted-pair wire for crystal clear display
- Impedance matched at 75 Ohms for full brightness and vibrant picture color from your VGA monitor
- High quality VGA connectors with molded PVC strain relief
- Supports high resolution VGA monitors (1920x1200 and above)

Technical Specifications

Warranty	Lifetime
Cable Jacket Type	PVC - Polyvinyl Chloride
Cable Shield Type	Aluminum-Mylar Foil with Braid
Connector Plating	Nickel
Fire Rating	CMP Rated (Plenum)
Number of Conductors	14
Connector A	1 - VGA (15 pin; High Density D-Sub) Male
Connector B	1 - VGA (15 pin; High Density D-Sub) Male
Impedance	75 Ohm
Cable Length	50 ft [15.2 m]
Color	Black
Connector Style	Straight
Product Height	0.7 in [17 mm]
Product Length	50 ft [15.2 m]
Product Weight	3 lb [1.4 kg]
Product Width	1.3 in [33 mm]
Wire Gauge	28 AWG
Package Quantity	1
Shipping (Package) Weight	3.1 lb [1.4 kg]
Included in Package	1 - 50ft Plenum-Rated Coax VGA Monitor Cable HDDB15 M/M

Certifications, Reports and Compatibility

