

6 ft Mini DisplayPort™ to DVI Adapter Converter Cable – Mini DP to DVI 1920x1200 - White

StarTech ID: MDP2DVIMM6W



The MDP2DVIMM6W Mini DisplayPort to DVI Adapter Cable lets you directly connect your Mini DP video source (Desktop PC, Laptop, Ultrabook, etc.) to a DVI monitor or projector, eliminating the expense of having to upgrade to a Mini DisplayPort-capable monitor.

The adapter cable is 6 feet (1.8 m) in length, and features male-to-male connectors, allowing you to connect your Mini DisplayPort source directly to a DVI display with no additional cabling required.

Compatible with Intel® ThunderboltMonday, July 01, 2013 10:20:25 AMrade;, when connected directly to a supporting DisplayPort over ThunderboltMonday, July 01, 2013 10:20:25 AMrade; I/O port, the adapter supports display or projector resolutions up to 1920x1200 (WUXGA).

MDP2DVIMM6W is a passive adapter that requires a dual-mode DisplayPort port (DisplayPort++), meaning that DVI and HDMI signals can also be passed through the port.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Connect your existing DVI display device (monitor, projector) to a Mini DisplayPort output device
- Ideal for using your DVI monitor as a secondary display

Features

- 1x Male Mini DisplayPort connector, 1x Male DVI connector
- Supports resolutions up to 1920x1200 (WUXGA) and HDTV resolutions up to 1080p
- Compatible with Intel® Thunderbolt™ devices that are capable of outputting a DisplayPort signal





Technical Specifications

Warranty 2 Years Audio No

Chipset ID NXP 3361
Converter Type Passive

Output Signal DVI-D (DVI Digital)

Connector A 1 - Mini-DisplayPort (20 pin) Male

Connector B 1 - DVI-D (25 pin) Male

Wide Screen Supported Yes

Maximum Digital 1920x1200 / 1080p

Resolutions

Color Black

Product Height 0.6 in [15 mm]
Product Width 1.6 in [40 mm]
Product Length 72 in [1830 mm]
Product Weight 3.9 oz [110 g]
Humidity 40%-85%RH

Operating Temperature 0°C to 60°C (32°F to 140°F)
Storage Temperature -10°C to 70°C (14°F to 158°F)

System and Cable DP++ (DisplayPort++) port required from video card or video source for DVI and

Requirements HDM® signal pass-through

Shipping (Package) 0.3 lb [0.1 kg]

Weight

Included in Package 1 - Mini DisplayPort® to DVI Adapter

Certifications, Reports and Compatibility





