

## 15 ft Mini DisplayPort™ to VGA Adapter Converter Cable – mDP to VGA 1920x1200 - Black

StarTech ID: MDP2VGAMM15B



The MDP2VGAMM15B active Mini DisplayPort to VGA converter cable lets you connect your Mini DisplayPortequipped desktop or laptop directly to a VGA monitor or projector at a longer distance than a standard-length cable would support, while saving the expense of additional adapters.

The adapter cable is compatible with Intel® ThunderboltFriday, August 30, 2013 6:57:37 AMrade;, when connected directly to a supporting DisplayPort over Thunderbolt I/O port. Plus, because the converter cable supports video resolutions up to 1920x1200 you can convert a DisplayPort video source to VGA without sacrificing video quality.

The MDP2VGAMM15B is backed by a 2-year StarTech.com warranty and free lifetime technical support.

### Applications

- Connect your existing VGA display device (monitor, projector) to a Mini DisplayPort output device (PC, laptop, Mac, Ultrabook)
- Use your VGA monitor as a secondary display, connected to a Mini DisplayPort output
- Connect a Mini DisplayPort computer to a VGA projector for presentations or meetings in a boardroom or auditorium setting

### Features

- Active Mini DisplayPort to VGA conversion
- Plug-and-Play Installation
- Supports resolutions up to 1920x1200 (WUXGA) and HDTV resolutions up to 1080p
- Compatible with Intel® Thunderbolt<sup>™</sup> devices that are capable of outputting a DisplayPort signal



Hard-to-find made easy\*

#### **Technical Specifications**

Warranty	2 Years
Audio	No
Chipset ID	ANALOGIX 9832
Converter Type	Active
Connector A	1 - Mini-DisplayPort (20 pin) Male
Connector B	1 - VGA (15 pin; High Density D-Sub) Male
Maximum Analog Resolutions	1920x1200 / 1080p (Output)
Maximum Cable Length	180 in [4572 mm]
Maximum Digital Resolutions	1920x1200 / 1080p (Input)
Cable Length	180 in [4572 mm]
Color	Black
Product Height	0.6 in [15 mm]
Product Length	180 in [4572 mm]
Product Weight	3.2 oz [90 g]
Product Width	1.6 in [40 mm]
Humidity	40%-85%RH
Operating Temperature	0°C to 60°C (32°F to 140°F)
Storage Temperature	-10°C to 70°C (14°F to 158°F)
Included in Package	1 - Mini DisplayPort to VGA Adapter Cable
Shipping (Package) Weight	0.4 lb [0.2 kg]

# Certifications, Reports and Compatibility

