

## 10 ft Mini DisplayPort to VGA Adapter Converter Cable – mDP to VGA 1920x1200 - White

StarTech ID: MDP2VGAMM10W



The MDP2VGAMM10W 10ft active Mini DisplayPort to VGA converter cable lets you connect your Mini DisplayPort-equipped device (Desktop PC, Mac®, Laptop, Ultrabook™, etc.) directly to a VGA monitor or projector with no additional adapters or cables required -- a cost-effective solution for enabling your Mini DisplayPort computer to work with a VGA monitor or projector. The cable features a stylish white design, that is well-suited for connecting Mac® computers.

The adapter cable is compatible with Intel® Thunderbolt™, when connected directly to a supporting DisplayPort over Thunderbolt I/O port. Plus, because the converter cable supports video resolutions up to 1920x1200 you can convert a DisplayPort video source to VGA without sacrificing video quality.

The MDP2VGAMM10W is backed by a 2-year StarTech.com warranty and free lifetime technical support.

### Applications

- Use your VGA monitor as a secondary display, connected to a Mini DisplayPort output
- Connect a Mini DisplayPort computer to a VGA projector for presentations or meetings in a boardroom or auditorium setting
- Connect your existing VGA display device (monitor, projector) to a DisplayPort output device (PC, laptop, Mac, Ultrabook)

## Features

- Active Mini DisplayPort to VGA conversion
- Plug-and-Play Installation
- Supports resolutions up to 1920x1200 (WUXGA) and HDTV resolutions up to 1080p
- Compatible with Intel® Thunderbolt™ devices that are capable of outputting a DisplayPort signal

## Technical Specifications

|                             |   |
|-----------------------------|---|
| Warranty                    | 2 Years                                   |
| Adapter Style               | Cable Adapter                             |
| Audio                       | No  |
| Chipset ID                  | ANALOGIX 9832                             |
| Converter Type              | Active                                    |
| Maximum Analog Resolutions  | 1920x1200 / 1080p (Output)                |
| Maximum Cable Length        | 10 ft [3 m]                               |
| Maximum Digital Resolutions | 1920x1200 / 1080p (Input)                 |
| Connector A                 | 1 - Mini-DisplayPort (20 pin) Male        |
| Connector B                 | 1 - VGA (15 pin; High Density D-Sub) Male |
| Humidity                    | 40%-85%RH                                 |
| Operating Temperature       | 0°C to 60°C (32°F to 140°F)               |
| Storage Temperature         | -10°C to 70°C (14°F to 158°F)             |
| Cable Length                | 10 ft [3 m]                               |
| Product Height              | 0.6 in [15 mm]                            |
| Product Length              | 36 in [915 mm]                            |
| Product Weight              | 5.4 oz [153 g]                            |
| Product Width               | 1.3 in [34 mm]                            |
| Shipping (Package) Weight   | 0.3 lb [0.2 kg]                           |
| Included in Package         | 1 - Mini DisplayPort to VGA Adapter Cable |

Certifications, Reports and Compatibility

