

1 Port USB to RS232 DB9 Serial Adapter Cable - M/M

Product ID: ICUSB232V2



The ICUSB232V2 1 Port USB to Serial Adapter converts a USB port into an RS232 DB9 serial port to connect to, monitor, and control a serial device.

Supporting data transfer rates up to 921.6 Kbps, the USB to serial cable is a convenient and cost-saving solution for providing serial connectivity to devices such as point-of-sale terminals, serial modems, industrial equipment, and a wide variety of other RS232 peripherals.

The USB to RS232 converter is easy to install and offers broad operating system compatibility, including Windows® 8, Linux and Mac OS®, for easy integration into mixed environments.

Backed by a StarTech.com 3-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- IT Administrators looking to add legacy functionality to newer notebooks, PCs and servers that lack an integrated RS232 port
- Connect bar code scanners, receipt printers and other point of sale devices
- Connect, monitor and control industrial/automotive sensors and other sensitive equipment
- Connect and program LED and digital signage boards

Features

- USB to Straight-Through RS232 DB9 Serial Adapter
- High-speed 921.6Kbps Baud Rate
- Compatible with Windows® 8, Mac OS X® and Linux
- Compatible with USB 1.1 or higher ports
- USB-powered - no external power adapter required
- Single cable, small footprint design for portability

Hardware	Warranty	3 Years
	Bus Type	USB 2.0
	Chipset ID	Prolific - PL2303RA
	Industry Standards	USB 1.1/2.0 RS232
	Interface	Serial
	Port Style	Cable Adapters
	Ports	1
Performance	Data Bits	5, 6, 7, 8
	FIFO	512 Bytes
	Flow Control	None, Xon/Xoff, RTS/CTS, DTR/DSR
	Max Baud Rate	921.6 Kbps
	MTBF	30,000 Hours
	Parity	Odd, Even, Mark, Space, or None Parity Modes
	Serial Protocol	RS-232
	Stop Bits	1, 1.5, 2
Connector(s)	Connector Type(s)	1 - DB-9 (9 pin, D-Sub) Male 1 - USB A (4 pin) Male
Software	Microsoft WHQL Certified	Yes
	OS Compatibility	Windows® 2000, XP, Vista, 7, 8, 8.1, 10 Windows Server® 2003, 2008 R2, 2012, 2012 R2, 2016 Mac OS® 9.x, 8.x, 10.6 to 10.12 Linux 2.4.31 to 4.4.x <i>LTS Versions Only</i>
Special Notes / Requirements	System and Cable Requirements	One available USB 1.1 (or above) port
Environmental	Humidity	0~65% RH
	Operating Temperature	0°C to 60°C (32°F to 140°F)
	Storage Temperature	-20°C to 80°C (-4°F to 176°F)
Physical Characteristics	Enclosure Type	Plastic
	Product Height	0.8 in [20 mm]
	Product Length	16.9 in [430 mm]
	Product Weight	1.9 oz [52.5 g]
	Product Width	1.4 in [35 mm]

Packaging Information	Shipping (Package) Weight	2.2 oz [62.5 g]
What's in the Box	Included in Package	1 - USB to RS232 Adapter
		1 - Instruction Manual

Product appearance and specifications are subject to change without notice.