

Model Number: P018-002

2-ft. Heavy Duty Computer Power Cord, 16A, 14AWG, IEC-320-C14 to IEC-320-C15



Highlights

- 2-ft. heavy-duty power cord, C14-to-C15
- 100~250V, 15A, 14AWG, SJT
- UL Listed

Description

Tripp Lite's C14-to-C15 power cords allow connection from high voltage network hardware utilizing C15 type connectors to PDU's and UPS systems with C14 type inputs. Heavy-duty 14AWG wire supports voltages up to 250V. Molded ends ensure a lifetime of use.

Applications

Ideal for connecting network hardware with C15 power connections such as servers to PDUs and UPS systems with C14 type inputs.

Package Includes

• 2-ft. C14 to C15 Power Cord

Features

- Heavy-duty power cord supports up to 250V
- Flexible 14AWG wire for easy routing
- Use with Cisco, HP and other hardware that uses C15 type power connections
- UL Listed

Specifications

OVERVIEW			
Intended Application	Compatible with network hardware that uses C15 power input connections		
Cable Type	POWER		
Model Type	Power Cords		
INPUT			
Cable Length (ft.)	2		
Cable Length (m)	0.61		
UPC ASSIGNMENT			
Unit Carton UPC#	037332182555		

PHYSICAL

PITSICAL			
Color	Black		
Style	Power cable		
CONNECTIONS			
Connector A	IEC-320-C15		
Connector B			
	IEC-320-C14		
WARRANTY			
Product Warranty Period (Worldwide)	Lifetime limited warranty		

Related Items

Optional Products

Related Model	Description	Qty.
P018-003	3-ft. Heavy Duty 14AWG Power Cord, C14-to-C15	1
P018-006	6-ft. Heavy Duty 14AWG Power Cord, C14-to-C15	1
P018-010	10-ft. Heavy Duty Computer Power Cord, 16A, 14AWG, IEC-320-C14 to IEC-320-C15	1
P019-004	4-ft. Heavy Duty 14AWG Power Cord, 5-15P - to - C15	1
P019-008	8-ft. Heavy Duty 14AWG Power Cord, 5-15P - to - C15	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at http://www.tripplite.com/sku/P018-002.

Copyright © 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.