

# 1 Port PCI Express Low Profile Parallel Adapter Card - SPP/EPP/ECP

StarTech ID: PEX1PLP



The PEX1PLP PCIe Parallel Adapter card can be installed in a PCI Express (PCIe) x1 slot, allowing you to connect EPP/ECP parallel peripherals to any computer, while relying on a native, single-chip design (Oxford OXPCIe952) that harnesses the capability of true PCI Express - ensuring maximum performance and reliability.

This high performance SPP/EPP/ECP parallel card adds 1 DB25 parallel port, perfect for connecting printers, scanners, CD-R/RW drives, memory card readers, bar code scanners and more. With the added convenience of plug-and-play capability, installing the parallel adapter card is hassle-free! The PCle Parallel card also includes both standard and half-height/low profile mounting brackets for compatibility with almost any system form factor.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

### **Applications**

• Connects any parallel-based peripheral to your PC, including printers, scanners, CD-R/RWs, Zip® drives, and memory card readers

#### **Features**

- SPP/EPP/ECP Parallel port fully supports existing Centronics interface
- Packaged with low profile/half-height bracket attached, includes full profile bracket
- Compliant with PCI Express Base Specification 1.1a
- Compliant with PCI Power Management 1.2





### **Technical Specifications**

Warranty 2 Years

Ports 1

Interface Parallel

Bus Type PCI Express

Card Type Low Profile (SP bracket incl.)

Port Style Integrated on Card

Chipset ID PLX/Oxford - OXPCle952
Connector Type(s) 1 - PCI Express x1 Male

External Ports 1 - DB-25 (25 pin; D-Sub) Female

Maximum Data Transfer Rate Up to 2.5Mbps

OS Compatibility Windows® 8 (32/64bit), 7 (32/64), Vista(32/64), XP(32/64), 2000, ME, 98SE, 95

Windows® Server 2008 R2,

Linux

Product Length 0.8 in [21 mm]
Product Width 4.3 in [110 mm]
Product Height 4.7 in [120 mm]
Product Weight 2.3 oz [65 g]

Operating Temperature 0°C 50°C (32°F to 122°F)
Storage Temperature -20°C 60°C (-4°F to 140°F)

Humidity 5~85% RH Shipping (Package) Weight 4.2 oz [120 g]

Included in Package 1 - Low profile PCI Express Parallel Card

Included in Package 1 - Full Profile Bracket

Included in Package 1 - Driver CD

Included in Package 1 - Instruction Manual





## Certifications, Reports and Compatibility











