

Composite and S-Video to HDMI® Converter with Audio

StarTech ID: VID2HDCON



The VID2HDCON Composite and S-Video to HDMI® Video Converter (with Audio) lets you connect an S-Video or Composite device, along with supporting 3.5mm audio, to your HDMI monitor or television.

Equipped with convenient selector switches for easy configuration, the S-Video/Composite to HDMI converter is able to function with both NTSC and PAL systems, and offers support for output resolutions up to 1600x1200 (PC) or 1080p (TV) to seamlessly integrate with almost any display.

The converter features an integrated 3.5mm audio connection that enables sending the output through a single HDMI cable to your destination display, avoiding the hassle of running a separate audio cable.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Convert VCRs, DVD players, camcorders, video game consoles and other home theater devices to work on HDMI displays

Features

- Functions with NTSC and PAL systems
- PC/TV resolution selector switch for compatibility with many different displays
- 50/60 Hz frame rate conversion
- On Screen Display
- Plug and play installation - no software/drivers required
- Advance 3D motion adaptive de-interlace
- 3D (frame based) motion adaptive YNR/CNR noise reduction

Technical Specifications

Warranty	2 Years
Audio	Yes
Industry Standards	NTSC 3.58 and PAL
Output Signal	HDMI
Connector Type(s)	1 - 3.5 mm Mini-Jack (3 Position) Female
Connector Type(s)	1 - Composite Video (1 x RCA) Female
Connector Type(s)	1 - HDMI (19 pin) Female
Connector Type(s)	1 - S-Video (4 pin; Mini-DIN) Female
Supported Resolutions	PC - 1600x1200, 1280x1024, 1024x768 TV - 1080p, 720p, 576p, 480p
Color	Black
Enclosure Type	Plastic
Product Length	6.5 in [164.5 mm]
Product Width	6.4 in [162.6 mm]
Product Height	1.3 in [33.5 mm]
Product Weight	3.5 oz [100 g]
LED Indicators	1 - Red - S-Video, Yellow - Composite Video
Power Adapter Included	Yes
Input Voltage	110 ~ 240 AC
Input Current	0.3A
Output Voltage	5 DC
Output Current	1A
Center Tip Polarity	Positive
Plug Type	M
Power Consumption	2.5W
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Humidity	20~90% RH
Shipping (Package) Weight	0.7 lb [0.3 kg]
Included in Package	1 - Composite/S-Video to HDMI Converter
Included in Package	1 - Universal Power Adapter (NA/UK/EU/AUS)
Included in Package	1 - Instruction Manual

Certifications, Reports and Compatibility

