



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SRW18US13

SmartRack Slim 18U Swinging Wall-Mount Rack Enclosure Cabinet



Highlights

- Slim design for shallow network switches and patch panels
- 18U with dual threaded front rails
- Locking, reversible front door
- Hinged cabinet swings away from wall bracket for easy equipment access (swing direction is reversible)
- Fully assembled for quick installation
- PCI-Compliant: meets stringent physical security requirements

Description

The SRW18US13 slim 18U Wall-Mount Rack Enclosure is designed to safely store shallow network switches and patch panels. It integrates wall-mounting, easy equipment access and cable management in Telco environments with limited floor space. Ventilated top and bottom panels allows generous airflow to keep equipment operating safely. Top panel offers a convenient cable access cutout with cover. Adjustable front mounting rails have square holes (default position) and tapped holes to accommodate 18U of equipment. A sturdy hinge between the cabinet and the wall-mount bracket allows the cabinet to swing away from the wall for easy access to equipment and cabling. Supports up to 250lbs of equipment. The SRW18US13 comes with a 5-year product warranty.

Package Includes

- SRW18US13 Wall-Mount Rack Enclosure
- Mounting Hardware
- Keys
- Owner's Manual

Features

- 18U slim wall-mounted enclosure
- Dual threaded rail option
- Ventilated top and bottom panels for increased airflow
- Locking, reversible front door
- Hinged cabinet swings away from wall bracket for easy equipment and cable access
- Fully assembled for quick installation
- PCI-Compliant: meets stringent physical security requirements

Specifications

PHYSICAL	
Installed whole system maximum rack depth (inches)	13
Rack Height	18U
Shipping Dimensions (HWD/in)	41.61 x 25.6 x 14.96

Shipping weight (lbs)	98
Unit Dimensions (HWD/in)	EXTERNAL DIMENSIONS: 35.6 x 23.62 x 13
Unit weight (lbs)	83.77
Color	Black
Weight Capacity - Stationary (lbs)	250
Cable Access Hole Measurement (inches)	9.812 x 2.35 (l x w)
SPECIAL FEATURES	
Grounding lug	Front door frame
CERTIFICATIONS	
Certifications	EIA-310-E
NOM (Mexico)	Tested to NOM (Mexico)
Approvals	RoHS
WARRANTY	
Product Warranty Period (Worldwide)	5-year limited warranty

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=5450.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.