



- WEEE

General

- Connections: external, DC power input, USB 3.0 type-B; internal, (2) SATA data and power
- Dual insertion slots fit 2.5" and 3.5" SATA HDD
- Power and activity LED indicators with power button

Transfer Rate

- SuperSpeed USB up to 5 Gbps and SATA up to 3 Gbps

Physical

- Power adapter: 1.5 m (58 in.)
- USB cable: 0.8m (31.5-in.) USB 3.0 type-A male to type-B male cable
- Dimensions: 12.9 x 9.5 x 9.2 cm (5.1 x 3.7 x 3.6 in.)
- Weight: 215 g (7.58 oz.)

Electrical

- Input: 100 – 240 V; 50 – 60 Hz; 1.2 A max.
- Output: +12 V / 3A center post

System Requirements

- Available USB 3.0 Standard-A port
- Windows XP/Vista/7/8 compatible
- Mac 9.x/10.x and Linux supported (excluding PC-based cloning software)

Package Contents

- QuickDock Duo
- Power adapter and USB cable
- Software CD
- Quick install guide

* Take extra precautions against electrical discharges when swapping hard-disk drives. Use the eject button to properly disconnect and remove a drive. Do not handle the drive by its sensitive components or place near speakers, televisions or other magnetic devices. Manhattan accepts no responsibility for lost data.

