

## 4 Port 1U Rackmount USB PS/2 KVM Switch with OSD

Product ID: SV431DUSB



This 4-port USB+PS/2 KVM Switch lets you control multiple PS/2 or USB-controlled computers from a single console (USB keyboard, USB mouse, monitor).

The versatile USB PS/2 KVM switch features convenient pushbutton and hot-key control for quick, reliable switching between connected computers.

A convenient and straight-forward control solution, the USB PS/2 KVM switch supports both manual and auto-scan modes and simple configuration through the built-in OSD.

Designed to ensure maximum space-efficiency, the USB+PS/2 KVM switch features a slim 1U design that fits neatly into a server equipment rack/cabinet and offers rear cable connections to eliminate cable tangles.

Backed by 3 year warranty and free lifetime technical support.

## Rackmount your KVM switch

If you'd like to mount this KVM switch to your server rack, StarTech.com offers a [1U Rackmount Bracket](#) (sold separately) that turns this KVM into a rackmountable KVM.

### Certifications, Reports and Compatibility



### Applications

- Co-location/ISP computer control
- Datacenter computer control
- Manufacturing line computer control
- PC test/burn-in computer control
- Server farms

### Features

- A dependable 3-year warranty provides peace of mind
- Auto-scan function automatically selects computer sequentially
- Hotkey functions allow easy computer access
- Unique cables for secured connection
- OSD security option allows certain PCs to be password protected from unauthorized use
- Rugged, all-metal 1U chassis for use in harsh environments and space-saving cabinets
- Plug-and-play system configuration
- Keyboard and mouse console is USB interface
- Identifies and selects computers by the names assigned

<b>Hardware</b>	Warranty	3 Years
	Audio	No
	Cables Included	No
	Daisy-Chain	No
	KVM Ports	4
	Number of Monitors Supported	1
	PC Interface	USB and PS/2
	PC Video Type	VGA
	Rack-Mountable	Optional
<b>Performance</b>	Aspect Ratio	Wide (16:9)
	DVI Support	No
	Hot-Key Selection	Yes
	IP Control	No
	Maximum Analog Resolutions	1920 x 1440
	Maximum Number of Users	1
	On-Screen Display	No
	Port Selection Support	Push Button and Hotkeys
	Supported Resolutions	1920 x 1440, 1920 x 1200, 1920 x 1080, 1680 x 1050, 1366 x 768, 1280 x 720, 854 x 480
Wide Screen Supported	Yes	
<b>Connector(s)</b>	Console Interface(s)	1 - VGA (15 pin, High Density D-Sub) Female 2 - USB A (4 pin) Female
	Host Connectors	4 - VGA (15 pin, High Density D-Sub) Female
<b>Software</b>	OS Compatibility	OS independent; No software or drivers required
<b>Power</b>	Center Tip Polarity	Positive
	Input Current	0.2A
	Input Voltage	110V-240V AC
	Output Current	0.6A
	Output Voltage	9 DC
	Plug Type	M
	Power Consumption (In Watts)	5.4
	Power Source	AC Adapter Included

<b>Environmental</b>	Humidity	0~80% RH
	Operating Temperature	5°C to 40°C (41°F to 104°F)
	Storage Temperature	-20°C to 60°C (-4°F to 140°F)
<b>Physical Characteristics</b>	Color	Black
	Enclosure Type	Steel
	Product Height	1.7 in [43 mm]
	Product Length	8.7 in [220 mm]
	Product Weight	52.9 oz [1500 g]
	Product Width	5.1 in [130 mm]
<b>Packaging Information</b>	Shipping (Package) Weight	3.8 lb [1.7 kg]
<b>What's in the Box</b>	Included in Package	1 - StarView 4 Port KVM Switch
		1 - Power Adapter
		1 - User Manual

Product appearance and specifications are subject to change without notice.