

2.5in USB 3.0 External Hard Drive Enclosure with Virtual ISO - Portable External SATA HDD

StarTech ID: S2510BU3ISO



The S2510BU3ISO USB 3.0 HDD Enclosure features ISO virtual drive emulation, which lets you turn almost any 2.5-inch SATA hard drive (HDD) or solid state drive (SSD) into an external virtual ROM drive.<./p>

Using hardware based ISO emulation, the enclosure allows you to easily create and mount up to 3 different virtual Blu-ray/DVD/CD ROM images, ensuring maximum performance while eliminating the hassle and expense of complicated virtual ISO software.

The enclosure supports large capacity hard drives (tested with up to 1TB), and also doubles as a standard external hard drive enclosure that can be used to maximize system storage expansion and backup capabilities.

The S2510BU3ISO virtual iSO HDD enclosure is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Useful in help desk environments to install/reimage software and operating systems on computers that do not have optical drives (i.e. Ultrabooks, Netbooks)
- Store up to 3 iSO files of frequently installed applications for ease of portability
- Expand a systems storage capacity with an external drive for backup/archiving

Features

- Use to mount virtual ROMs, and/or as external storage solution
- Hardware based iSO emulation.
- SuperSpeed USB 3.0 compliant host interface with support for up to 5Gbps of bandwidth
- No software or drivers required
- Fits 2.5" form factor SATA drives up to 9.5mm in height





Technical Specifications

Warranty 2 Years
Bus Type USB 3.0

Chipset ID MB86C311/Fujitsu

Drive Installation Fixed
Drive Size 2.5in
Drive Type SATA
Interface USB 3.0

Number of Drives 1

Connector Type(s) 1 - USB 3.0 Mini-B (10 pin; SuperSpeed) Female Drive Connectors 1 - SATA Data & Power Combo (7+15 pin) Female

Hot Swap Capability No

Max Drive Capacity Currently tested with up to 1TB 5400 RPM hard drives

Type and Rate SATA II (3 Gbps)

Type and Rate USB 3.0 - 5 Gbit/s

OS Compatibility Windows 2000/ XP(32/64-bit)/ Server 2003(32/64-bit)/ Vista(32/64-bit)/ 7(32/64-bit)/ Server

2008 R2/8(32/64-bit), Mac OS X, and Linux

Color Black
Enclosure Type Plastic

Max Drive Height0.4 in [9.5 mm]Product Height0.6 in [16 mm]Product Length3.1 in [78 mm]Product Weight2.6 oz [75 g]Product Width5.3 in [135 mm]

LED Indicators 1 - HDD

LED Indicators 1 - iSO_1

LED Indicators 1 - iSO_2

LED Indicators 1 - iSO_3

Power Adapter USB-Powered

Included

Humidity 5-90% RH

Operating 0°C to 60°C (32°F to 140°F)

Temperature

Storage Temperature -20°C to 60°C (-4°F to 140°F)

Note For ISO functionality there needs to be a NTFS formatted partition on the Hard Drive

System and Cable Available USB 3.0 or 2.0 port





Requirements

Included in Package 1 - USB 3.0 2.5" SATA HDD Enclosure w/ ISO

Included in Package 1 - 31in USB 3.0 Cable

Included in Package 1 - Carrying Pouch

Included in Package 1 - Instruction Manual

Shipping (Package) 0.4 lb [0.2 kg]

Weight

Certifications, Reports and Compatibility











