

# USB 3.0 Dual SATA Hard Drive Docking Station with integrated Fast Charge USB Hub UASP support and Fan - White

StarTech ID: SDOCK2U33HFW



The SDOCK2U33HFW USB 3.0 Dual hard drive dock with Fast Charge USB hub enables two SATA 2.5in or 3.5in hard drives (HDD) or solid state drives (SSD) to be connected simultaneously to a computer through USB, while controlling the power status (on/off) of each individual drive independently from the other. The enclosure supports UASP and delivers optimal performance with a USB 3.0 connection, but is also backward compatible with USB 2.0/1.1 host connections.

The Hard Drive Dock features a built-in 2-port USB 3.0 Hub that enables you to connect up to 2 additional USB 3.0 devices to your computer through the same USB connection. One of the ports on the hub also has Fast Charging capabilities, that charges iPad's and other mobile devices as effectively as through a wall plug. This Fast Charge Port has been specially designed for compatibility with a wide range of tablets and smartphones.

With support for UASP, the dock performs up to 70% faster than conventional USB 3.0, when paired with a UASP-enabled host controller to utilize the full potential of your SATA III hard drives.

With support for SATA I/II/III, large capacity drives (tested up to 4TB), and 2.5in or 3.5in hard drives this HDD/SSD docking station is compatible with virtually any SATA hard drive, and greatly increases the storage/backup capabilities of your computer. Plus, configurable power management reduces energy consumption, and extends the life of your drives by avoiding unnecessary access.

The docking station features a built-in 80mm cooling fan that helps increase reliability and lifespan of HDDs by keeping the drives cooler. The variable fan speed control allows for on-the-fly adjustments for any type of HDD, or to balance cooling with noise.

Extend the value of this docking station further with the addition of our <u>SATA to IDE Hard Drive</u> Adapter (SAT2IDEADP), allowing easy insertion of any 2.5 or 3.5in. IDE hard drive into a SATA hard drive dock.

With uniform white design and sleek silver trim, the SDOCK2U33HFW will look great with your Apple® Mac®, and is backed by a 2-year StarTech.com warranty and free lifetime technical support.





### **Applications**

- System administrators who need quick access to drives for imaging
- Backup data quickly to an external data archive
- Easily copy data from one external drive to another in a single external dock through one USB connection
- Technicians who regularly test or benchmark different hard drives and need to swap between them
- IT professional that need to charge tablets and Smart phone devices
- Data recovery specialists who need quick access to drives to recover/retrieve data

#### **Features**

- Supports 2.5in and 3.5in form factor SATA hard drives (HDD) and solid state drives (SSD)
- UASP Compliant
- Built-in USB 3.0 Hub with Fast Charging Port
- 80mm cooling fan with variable speed control (including Off)
- Configurable power management
- SuperSpeed USB 3.0 compliant host interface, with up to 5 Gbps of data bandwidth
- Compatible with SATA revision I/II/III (1.5/3.0/6.0 Gbps) drives
- Plug-and-Play and Hot-Swap compatible
- Dual bay, top slot-loading design with drive doors
- Stylish full white design with silver trim



## **Technical Specifications**

Warranty 2 Years

Chipset ID VIA812+ASM1053E

Drive Size 2.5in & 3.5in

Drive Type SATA Fan(s) Yes

Fans 1 - 80 mm

Filter Type Mesh

Interface USB 3.0

Number of 2

Drives

Drive 2 - SATA Data & Power Combo (7+15 pin) Receptacle

Connectors

Host 1 - USB 3.0 B (9 pin; SuperSpeed) Female

Connectors

Other 1 - USB 3.0 A (5V, 2A; 9 pin; SuperSpeed) Female

Interface(s)

Other 1 - USB 3.0 A (9 pin; SuperSpeed) Female

Interface(s)

Max Drive Currently tested with up to 4TB 7200 RPM 3.5" hard drives and 1TB 7200 RPM 2.5" hard drives

Capacity

Type and Rate SATA III (6 Gbps)
Type and Rate USB 3.0 - 5 Gbit/s

UASP Support Yes

OS Windows XP(32/64-bit)/ Server 2003(32/64-bit)/ Vista(32/64-bit)/ 7(32/64-bit)/ 8(32/64-bit)/ Server

Compatibility 2008 R2, and Mac OSX, and Linux 2.6.31 and up

Color White & Silver
Product Height 145 mm [5.7 in]
Product 185 mm [7.3 in]

Length

Product 829 g [29.3 oz]

Weight

Product Width 122 mm [4.8 in]

LED Indicators 1 - Power/Activity (Drive 1) LED Indicators 1 - Power/Activity (Drive 2)

Center Tip Positive

**Polarity** 

Input Current 1.5A

Input Voltage 100 ~ 240 AC

Output Current 6A
Output Voltage 12 DC





Plug Type

Μ

Power

Yes

Adapter Included

Humidity

20%RH~80%RH

Operating

5°C to 35°C (41°F to 95°F)

Temperature

Storage Temperature -20°C to 50°C (-4°F to 122°F)

Note

Note: Certain devices may not support charging and syncing simultaneously. In these instances

disconnect the device, and set the charge only switch to "on", then reconnect the device.

Shipping

(Package) Weight

1.5 kg [3.3 lb]

Included in

Package

1 - HDD Dock

Included in

1 - USB 3.0 Cable (1m)

Package

Included in

1 - Universal Power Adapter

Package

Included in

3 - Power Cords (NA/UK/EU)

Package

Included in

1 - Instruction Manual

Package





# Certifications, Reports and Compatibility











