



Multi-Card Reader/Writer

Hi-Speed USB, 3.5" Bay Mount, 60-in-1

Part No.: **100915**

Converts an empty, unused PC bay into a digital content management center. The Manhattan Multi-Card Reader/Writer supports most card formats to easily download and transfer digital images and files from many of today's popular flash memory cards. Compatible with up to 60 types of CompactFlash, Microdrive, Magicstor, Memory Stick, MagicGate, SecureDigital, Multimedia, XD and more, the Manhattan Multi-Card Reader/Writer quickly installs into a 3.5" bay.

Convenience without the Media Device

Access digital content without directly connecting the camera or other media devices to the computer. This convenient connection helps conserve battery power by eliminating the need to directly install a digital device to a desktop computer. A front-mount USB port expands power availability to recharge USB devices.

Features:

- Convenient front-mount USB port
- Compatible with CompactFlash, Microdrive, Memory Stick, MagicGate, SecureDigital, Multimedia and XD
- Supports Automatic Card Detection and data transfer speeds up to 480 Mbps
- Eliminates need for direct connection of media device to save battery power
- Plug and play; hot-swappable — Windows and Mac compatible
- Three-Year Warranty

Specifications:

Standards and Certifications

- USB 2.0
- USB 1.1
- CE
- FCC
- WEEE

Connections

- External USB 2.0 type-A female
- Internal 5-pin card reader / 4-pin USB (Molex)

Supports

- CompactFlash Type I/II, CF 3.0, CF 4.0, CF Elite Pro, CF High Speed, CF PRO I/II, Extreme CF, Extreme III CF, Ultra II CF, XS-XS CF, IBM and Hitachi Microdrive, MagicStor, Memory Stick, Memory Stick Duo, Memory Stick Extreme III PRO, Memory Stick Extreme PRO, Memory Stick Micro (M2), Memory Stick PRO, Memory Stick PRO Duo, Memory Stick PRO HG, Memory Stick ROM, Memory Stick Select, Memory Stick Ultra II PRO, High Speed Memory Stick PRO, High Speed Memory Stick PRO Duo, MagicGate, MagicGate Duo, MagicGate PRO, MagicGate PRO Duo, High Speed MagicGate PRO, High Speed MagicGate PRO Duo, SecureDigital (SD), Elite Pro SD, Extreme SD, Extreme III SD, High Speed miniSD*, High Speed SD, microSD / TransFlash, miniSD, Pro SD, SDHC, SDXC, Ultra SD, Ultra II SD, Ultra II SD Plus, Ultra Speed SD, Ultra-X SD, MMC / MMC 4.0 / MMC 4.2, RS-MMC*, High Speed MMC / RS-MMC*, RS-MMC 4.0*, MMCmobile*, MMCplus*, XD / XD 1.21

General

- LED power/activity indicator
- Transfer rates: 480 Mbps / 12 Mbps / 1.5 Mbps
- Material: plastic

Environmental

- Operating temperature: 0 – 70°C (32 – 158°F)
- Storage temperature: -40 – 70°C (-40 – 158°F)
- Operating humidity: 50% non-condensing
- Storage humidity: 95% non-condensing
- Dimensions reader: 90 x 102 x 17 mm (3.5 x 4.0 x 1 in.)
- Dimensions USB cable: 70 cm (27.5 in.)
- Weight: 80 g (2.8 oz.)

System Requirements

- Internal USB connection
- Windows Server 2003/XP/Vista/7/8 and Mac OS 10.5 or higher

Package Contents

- Multi-Card Reader/Writer with (6) mounting screws
- Cable and user manual

*Adapter required (not included)

