933BW • 2233SW • 2233BW • 2433BW







Features:

- Distinctive soft design with rich piano black finish
- Integrated rear cable housing for a clean look
- Up to 1920 x 1080 full HD resolution (2233SW)
- 5ms response, up to 20,000:1 dynamic contrast ratio
- Exclusive Samsung Magic technologies for rich, natural color
- Custom key for one-touch access to preferred picture function
- 16:10 aspect ratio, 16:9 aspect ratio widescreen (2233SW)



2433BW

imagine a sculpture that doubles as a valuable business tool. That's the Samsung 33BW/SW series widescreen LCD monitors. Their soft curves, rich piano black finishes, clear acrylic accent bars and integrated cable housings lend distinctive style and sophistication to your desk. The widescreens mean more room for multitasking, while up to 1920 x 1080 full HD resolution, 5ms response, exclusive picture technologies and up to 20,000:1 dynamic contrast ratio give you fast, colorful, detailed motion video. Beauty inside and out.

Features



19", 21.5", 22" and 24" Widescreen LCD Monitors

Distinctive	Design

Soft corners, rich piano black finish and acrylic accent bar will beautify any desk.

Cable Housing

Integrated rear housing hides cables, for a sleek, clean look.

Up to 1920 x 1080 Full HD

The 2233SW features 1920 x 1080 full HD resolution, giving you the highest resolution possible.

Custom Key

The programmable Custom Key gives you instant one-touch access to your preferred Samsung picture optimization technology. MagicBright 3 gives you seven pre-set modes to choose from. MagicColor enhances color either overall or with regard to natural skin tones. Color Effect lets you view images in grayscale, green, aqua or sepia. And Image Size lets you properly view either 5:4 or 4:3 content on the widescreen without distortion.

2433BW Dimensions





Sync	Specifications		933BW	2233SW	2233BW	2433BW
Native Resolution	Display	Туре	a-si TFT/TN	a-si TFT/TN	a-si TFT/TN	a-si TFT/TN
Peed Pilch immi Appert Ration 1611 01 000-11/500-11 pyramic 1000-11/500-11 pyramic 100		Viewable Size	19" Wide	21.5" Wide	22" Wide	24" Wide
Aspect Rails		Native Resolution	1440 x 900	1920 x 1080	1680 x 1050	1920 x 1200
Contract Ratio		Pixel Pitch (mm)	0.285	0.248	0.282	0.270
Velority Augile (MV)		Aspect Ratio	16:10	16:9	16:10	16:10
Response Time		Contrast Ratio	1000:1/15000:1 Dynamic	1000:1/15000:1 Dynamic	1000:1/20000:1 Dynamic	1000:1/20000:1 Dynamic
Light Source COFL		Viewing Angle (H/V)	170°/160° (CR>10)	160°/160° (CR>10)	170°/160° (CR>10)	170°/160° (CR>10)
Brightness (Typical)		Response Time	5ms	5ms	5ms	5ms
Video Input Signal Maximum Clord Supported Analog RGB		Light Source	CCFL	CCFL	CCFL	CCFL
Maintain Color Supported Analog ROB		Brightness (Typical)	300 cd/m ²	300 cd/m ²	300 cd/m ²	300 cd/m ²
Analog		Panel Surface	Matte	Matte	Matte	Matte
Digital Digital Did (with HDCP) Did (wit	Video Input Signal	Maximum Color Supported	16.7M	16.7M	16.7M	16.7M
Frequency (MV) 30 - 81M/bt(h) / 56 - 754 bt(h) 30 - 81M/bt(h) / 30 -		Analog	Analog RGB	Analog RGB	Analog RGB	Analog RGB
Sync		Digital	DVI (with HDCP)	DVI (with HDCP)	DVI (with HDCP)	DVI (with HDCP)
Property		Frequency (H/V)	30~81kHz(H) / 56~75Hz(V)	30~81kHz(H) / 56~75Hz(V)	30~81kHz(H) / 56~75Hz(V)	30~81kHz(H) / 56~75Hz(V)
Certification, XP, 2000, 98 Certification, XP, 2000, 98 Certification, XP, 2000, 98 Certification, XP, 2000, 98 Input Cornectors 15-in D-said, DVH-0, 3-in AC plug (CEE22) The County of CEE22 The County of		Sync				
	Compatibilty	PC				
Power		Mac				•
Controls Basic	Input Connectors					
Basic Power, Auto Adjustment, Source, Brightness updown, Magichight 3 presets, CSD Menu Power, Auto Adjustment, Source, Brightness updown, Magichight 3 presets, CSD Menu Product Medichight 3 pr	Power	Voltage				
Source, Brightness updrown, Magichight 3 presets, OSD Menu Picture (Brightness, Contrast, Magichight) Spressets, OSD Menu Picture (Brightness, Contrast, Magichight) Picture (Brightness, Contrast, Magichight) Picture (Brightness, Contrast, Magichight) Dicture (Brightness, Contrast, Magichight) Picture (Brightness, Contrast, Magic		Consumption (Max/DPMS)				
Magic Bright, Color Magic Bright, Color Magic Bright, Color Magic Bright, Color Magic Color, Tone, Control, Effect, Gamma), Image (Codarse, Fine, Sharpness, H position, V position), CSD (Language, H position, V position), CSD (Language, H position, V position), CSD (Language, H position), CSD (Language, H position, V position), CSD (Language, H position), V position, Transparency, Deploy Time), Setup (Auto Source, Reset, Off Timer, Customized Key, Image Size) Doc 28/DOC-Cl Doc 28/DOC	Controls	Basic	Source, Brightness up/down, MagicBright 3	Source, Brightness up/down, MagicBright 3	Source, Brightness up/down, MagicBright 3	Source, Brightness up/down, MagicBright 3
Stand Tit Ti		Advanced	Magic Bright), Color (MagicColor, Tone, Control, Effect, Gamma), Image (Coarse, Fine, Sharpness, H position, V position), OSD (Language, H position, V position, Transparency, Display Time), Setup (Auto Source, Reset, Off Timer,	Magic Bright), Color (MagicColor, Tone, Control, Effect, Gamma), Image (Coarse, Fine, Sharpness, H position, V position), OSD (Language, H position, V position, Transparency, Display Time), Setup (Auto Source, Reset, Off Timer,	Magic Bright), Color (MagicColor, Tone, Control, Effect, Gamma), Image (Coarse, Fine, Sharpness, H position, V position), OSD (Language, H position, V position, Transparency, Display Time), Setup (Auto Source, Reset, Off Timer,	Magic Bright), Color (MagicColor, Tone, Control, Effect, Gamma), Image (Coarse, Fine, Sharpness, H position, V position), OSD (Language, H position, V position, Transparency, Display Time), Setup (Auto
Wall Mount (VESA) 75mm 100 mm 100mm 100mm 100mm Magic Technologies Magic Color (Full/ Intelligent) Magic Slack High Gloss Black High G	Features	Plug & Play	DDC 2B/DDC-CI	DDC 2B/DDC-CI	DDC 2B/DDC-CI	DDC 2B/DDC-CI
Cabinet Color		Stand	Tilt	Tilt	Tilt	Tilt
Magic Technologies Magic		Wall Mount (VESA)	75mm	100 mm	100mm	100mm
MagicBright 3 (Custom, Text, Internet, Game, Sport, Movie, Dynamic Contrast) MagicTune (On-screen Asset Management) Operating Conditions Temperature 10° - 40° 10° - 40° 10° - 40° 10° - 40° 10° - 40° 10° - 40° 10° - 80%, non-condensing 10% - 8		Cabinet Color	High Gloss Black	High Gloss Black	High Gloss Black	High Gloss Black
Text, Internet, Game, Sport, Movie, Dynamic Contrast) MagicTune (On-screen Asset Management) Operating Conditions Temperature 10° - 40° 10° - 40° 10° - 40° 10° - 40° 10° - 40° 10° - 40° 10° - 40° 10° - 80%, non-condensing 10% - 80%, non-cond	Magic Technologies	MagicColor (Full/ Intelligent)				•
Asset Management) Temperature 10°~ 40° 10°~ 40		Text, Internet, Game, Sport,	•	•	•	•
Humidity			•	•	•	•
Dimensions and Weight W x H x D With Stand, W x H x D Without Stand Shipping Carton 17.8" x 14.9" x 7.9" 20.4" x 13.6" x 2.8" 20.4" x 13.6" x 2.8" 20.4" x 13.6" x 2.8" 20.4" x 15.9" x 2.8" 20.4" x 15.9" x 5.2" 20.4" x 15.6" x 2.8" 20.4" x 13.6" x 2.8" 20.5" x 17.3" x 5.2" 22.4" x 15.9" x 2.8" 22.4" x 15.9" x 2.8" 23.5" x 16.3" x 5.2" 22.3" x 14.7" x 2.8" 22.4" x 15.9" x 2.8" 22.5" x 19.6" x 5.4" Package Contents Meight (w/Stand, Shipping) 8.8 lbs., 11.9 lbs. 9.7 lbs., 12.9 lbs. 10.6 lbs., 13.7 lbs. 11.7 lbs., 15.0 lbs. Package Contents Package Contents September 15-pin D-sub Cable, DVI-D Cable, Manuals, Driver CD To-pin D-sub Cable, DVI-D Cable, Manuals, Driver CD To-pin D-sub Cable, DVI-D Cable, Manuals, Driver CD Monitor, Power Cable, 15-pin D-sub Cable, DVI-D Cable, Manuals, Driver CD To-pin D-sub Cable, DVI-D Cable, Manuals, Driver CD Monitor, Power Cable, 15-pin D-sub Cable, DVI-D Cable, Manuals, Driver CD Monitor, Power Cable, 15-pin D-sub Cable, DVI-D Cable, Manuals, Driver CD Monitor, Power Cable, 15-pin D-sub Cable, DVI-D Cable, Manuals, Driver CD Monitor, Power Cable, 15-pin D-sub Cable, DVI-D Cable, Manuals, Driver CD Monitor, Power Cable, 15-pin D-sub Cable, DVI-D Cable, Manuals, Driver CD Monitor, Power Cable, 15-pin D-sub Cable, DVI-D Cable, Manuals, Driver CD Monitor, Power Cable, 15-pin D-sub Cable, DVI-D Cable, Manuals, Driver CD Monitor, Power Cable, 15-pin D-sub Cable, DVI-D Cable, Manuals, Driver CD </td <td rowspan="2">Operating Conditions</td> <td>Temperature</td> <td>10°~ 40°</td> <td>10°~ 40°</td> <td>10°~ 40°</td> <td>10°~ 40°</td>	Operating Conditions	Temperature	10°~ 40°	10°~ 40°	10°~ 40°	10°~ 40°
Weight W x H x D Without Stand 17.8" x 13.1" x 2.9 20.4" x 13.6" x 2.8" 23.5" x 16.3" x 2.8" 23.5" x 17.3" x 5.2" 22.4" x 15.9" x 2.8" 23.5" x 16.3" x 5.2" 23.5" x 17.3" x 5.2" 22.4" x 15.9" x 2.8" 23.5" x 16.3" x 5.2" 23.5" x 17.3" x 5.2" 22.4" x 15.9" x 2.8" 23.5" x 10.3" x 5.2" 23.5" x 17.3" x 5.2" 22.4" x 15.9" x 2.8" 23.5" x 10.3" x 5.2" 23.5" x 17.3" x 5.2" 22.4" x 15.9" x 2.8" 23.5" x 10.3" x 5.2" 23.5" x 17.3" x 5.2" 23.5" x 17.3" x 5.2" 23.5" x 17.3" x 5.2" 23.5" x 10.3" x 5.2" 23.5" x		Humidity	10% ~ 80%, non-condensing	10% ~ 80%, non-condensing	10% ~ 80%, non-condensing	10% ~ 80%, non-condensir
Weight (w/Stand, Shipping) 8.8 lbs., 11.9 lbs. 9.7 lbs., 12.9 lbs. 10.6 lbs., 13.7 lbs. 11.7 lbs., 15.0 lbs. Monitor, Power Cable, 15-pin D-sub Cable, DVI-D Cable, Manuals, Driver CD Cable, Manuals, Driver CD Warranty 3 years parts and labor 4 lemc EMC EMC EMC EMC EMC EMC EMC CCFL panel contains mercury, please dispose of property please dispose of property		W x H x D Without Stand	17.8" x 13.1" x 2.9	20.4" x 13.6" x 2.8"	20.3" x 14.7" x 2.8"	22.4" x 15.9" x 2.8"
15-pin D-sub Cable, DVI-D Cable, Manuals, Driver CD Cable, Manuals,		Weight (w/Stand, Shipping)	8.8 lbs., 11.9 lbs.	9.7 lbs., 12.9 lbs.	10.6 lbs., 13.7 lbs.	11.7 lbs., 15.0 lbs.
Green Management Emission Standard	Package Contents		15-pin D-sub Cable, DVI-D	15-pin D-sub Cable, DVI-D	15-pin D-sub Cable, DVI-D	15-pin D-sub Cable, DVI-D
RoHS Compliant Energy Star Compliant Product Recyclability CCFL panel contains mercury, please dispose of properly please dispose of properly Product Recyclability CCFL panel contains mercury, please dispose of properly Product Recyclability CCFL panel contains mercury, please dispose of properly Product Recyclability CCFL panel contains mercury, please dispose of properly Product Recyclability	Warranty		3 years parts and labor	3 years parts and labor	3 years parts and labor	3 years parts and labor
RoHS Compliant Energy Star Compliant Product Recyclability CCFL panel contains mercury, please dispose of properly please dispose of properly Product Recyclability CCFL panel contains mercury, please dispose of properly Product Recyclability CCFL panel contains mercury, please dispose of properly Product Recyclability CCFL panel contains mercury, please dispose of properly Product Recyclability	-	Emission Standard	EMC	EMC	EMC	EMC
Energy Star Compliant Product Recyclability CCFL panel contains mercury, please dispose of properly please dispose of properly CCFL panel contains mercury, please dispose of properly Product Recyclability CCFL panel contains mercury, please dispose of properly please dispose of properly Product Recyclability CCFL panel contains mercury, please dispose of properly please dispose of properly						
Product Recyclability		·				
			CCFL panel contains mercury,	CCFL panel contains mercury,	CCFL panel contains mercury,	CCFL panel contains mercury
		Packaging Recyclability	Packing materials recyclable	Packing materials recyclable	Packing materials recyclable	Packing materials recyclable



Product Information: 1-866-542-7214 www.samsungmonitors.com Product Support: 1-800-SAMSUNG

