## **NEC V Series**

## 19" and 22" LCDs ideal for general business users



Step up to flat-panel display performance without emptying your pockets. With affordable LCD monitors for a variety of users, NEC V Series monitors have set a new standard in value in the display product category. V Series monitors offer you a perfect opportunity to take advantage of the many benefits offered by flat-panel monitors without having to break your budget. The 19" (18.5" VIS) NEC V191W and 22" (21.6" VIS) NEC V221W deliver ideal visual display solutions to corporate and small-to-medium-sized business users, adding clarity to presentation and document creation and vibrant splashes of color to web surfing. Their wide-format screens (16:9 aspect ratio) provide a work area that's significantly larger than standard aspect ratio screens, allowing you to simultaneously view multiple/side-by-side application windows.

**Enhanced screen performance.** With contrast ratios of 1000:1 (typical) and brightness quality as high as 300 cd/m², outstanding LCD monitor front-of-screen visual performance is NEC's #1 goal. The V Series delivers vibrant colors and flicker-free images that make your time in front of the monitor more comfortable and productive. NEC's Rapid Response<sup>TM</sup> technology provides for uninterrupted display of full-motion video with response times as quick as 5ms. This remarkably quick motion makes these models better than ever for presentations and streaming web video.

## **Series Features & Benefits**

**LCD** screen provides a more comfortable and productive visual experience with crisp, sharp and accurate text and images

Wide-format screen (16:9 aspect ratio) increases productivity by expanding your working area to view multiple application windows

**Rapid Response technology** delivers virtually uninterrupted, undistorted viewing of high-speed, full-motion video

**ECO Mode1™ and 2** help save power, reduce heat and extend the life of the display by allowing the user to dim the backlight based on their specific requirements

**Carbon footprint meter** helps track and calculate the reduction of green gas emissions

**On Screen Display (OSD®)** puts you in complete control of your screen setting adjustments

**No Touch Auto Adjust™** reduces setup time and provides optimal image settings upon initial power-on

**Windows® Vista certification** maximizes the monitor's resolution capabilities

**Wall/arm mounting capability** adds flexibility and comfort, while freeing up valuable desktop space (using third-party product)

**RoHS compliance** ensures the displays are free of hex-chrome, cadmium, PBDE and PBB, with reduced mercury and lead

**ENERGY STAR 5.0 compliance/low power consumption** reduces electrical costs and lowers total cost of ownership

**NEC Display Solutions' quality and reliability** provide peace of mind with a 3-year limited parts and labor warranty (including backlight) and unrivaled customer service and technical support



Model	V191W	V221W
Display Viewable Image Size Pixel Pitch Pixels Per Inch Brightness (typical) Contrast Ratio (typical) Viewing Angle (typical) Response Time (typical) Display Colors	18.5" 0.3mm 85 280 cd/m² 1000:1 170°V / 176°H (85U/85D/88L/88R) (CR > 5) 5ms More than 16.7million	21.6" 0.248mm 90 300cd/m² 800:1 178° (89U89D/89L/89R) (CR > 5) 5ms (rise & fall) More than 16.7million
Synchronization Range Horizontal Vertical	31.5 - 81 KHz 55 - 76 Hz	31.5 - 81 KHz 55 - 76 Hz
Input Signal Video Sync	Analog 0.7 Vp-p / 75 Ohms Separate Sync: TTL Level (positive/negative)	Analog 0.7 Vp-p / 75 Ohms Separate Sync: TTL Level (positive/negative)
Input	VGA 15-pin D-Sub	VGA 15-pin D-Sub
Resolutions Supported	640 x 400 @ 70 Hz 720 x 400 @ 70 Hz 640 x 480 @ 60-75 Hz 800 x 600 @ 56-75 Hz 832 x 624 @ 75 Hz 1024 x 768 @ 60-75 Hz 1152 x 864 @ 70-75 Hz 1280 x 960 @ 60 Hz 1280 x 1024 @ 60 Hz 1360 x 768 @ 60 Hz 1366 x 768 @ 60 Hz	720 x 400 @ 70 Hz 640 x 480 @ 60-75 Hz 800 x 600 @ 56-75 Hz 832 x 624 @ 75 Hz 1024 x 768 @ 60-75 Hz 1152 x 864 @ 70-75 Hz 1280 x 960 @ 60-75 Hz 1280 x 1024 @ 60-75 Hz 1280 x 1024 @ 60-75 Hz 1360 x 768 @ 60 Hz 1366 x 768 @ 60 Hz 1440 x 900 @ 60 Hz 1440 x 1050 @ 60 Hz 1600 x 1200 @ 60 Hz 1680 x 1050 @ 60 Hz 1680 x 1050 @ 60 Hz 1920 x 1080 @ 60 Hz
Native Resolution	1366 x 768 @ 60 Hz	1920 ×1080 @ 60 Hz
Additional Features	Ultra-thin bezel, ECO Mode1 and 2, carbon footprint meter, Windows Vista-certified	Ultra-thin bezel, ECO Mode1 and 2, carbon footprint meter, Windows Vista-certified
Touch Integratable	No	No
Voltage Rating	100-240V @ 50/60 Hz	100-240V @ 50/60 Hz
Power Consumption (typical) On Power Savings Mode	21W / 13W (ECO2) 0.5W	40W (max.) / 23W (ECO) 1W
Dimensions (W x H x D) Net (with stand) Net (without stand)	17.5 x 13.3 x 7.6 in. / 445.4 x 338.2 x 193.8mm 17.5 x 10.6 x 2.5 in. / 445.4 x 270.1 x 63.5mm	20.3 x 14.7 x 7.6 in. / 514.5 x 372.5 x 193.6mm 20.3 x 12.2 x 2.7 in. / 514.5 x 310.2 x 68.5mm
Weight Net (with stand) Net (without stand)	7.1 lbs. / 3.2 kg 6.4 lbs. / 2.9 kg	9.5 lbs. / 4.3 kg 8.8 lbs. / 4 kg
VESA Hole Configuration Specifications	100 x 100mm	100 x 100mm
Environmental Conditions Operating Temperature Operating Humidity Operating Altitude Storage Temperature Storage Humidity Storage Altitude	5 - 35°C / 41 - 95°F 30 - 80% 2000m / 6562 ft. -10 - 60° C / 14 - 140° F 10 - 85% 12,192m / 40,000 ft.	5 - 35°C / 41 - 95°F 30 - 80% 2000m / 6562 ft. -10 - 60° C / 14 - 140° F 10 - 85% 12,192m / 40,000 ft.
Limited Warranty	3 years parts and labor, including backlight	3 years parts and labor, including backlight
Technical Support	M - F (7am - 7pm CST)	M - F (7am - 7pm CST)



