

NEC AccuSync™ Series

17"-23" flat-panel monitors ideal for small-to-medium-sized business users



High-quality LCD monitors don't necessarily have to be associated with high-end price tags. NEC AccuSync Series monitors have set a new standard in value for the flat-panel monitor category, offering you a perfect opportunity to take advantage of the many benefits offered by the latest display technology without having to break your budget. The 17" NEC AccuSync AS171, 19" AS191, and widescreen 19" AS191WM, 22" AS221WM and 23" AS231WM deliver eco-friendly, technology-rich and cost-conscious display solutions to small-to-medium-sized businesses and home office users. The widescreen models increase productivity by expanding your working area to simultaneously view multiple application windows.

It's easy to be green. In addition to consuming up to 50% less energy than conventional LCD displays of the same size and containing 50% less mercury content than comparable displays, the NEC AccuSync Series is loaded with features that promote environmental consciousness, including: ECO Mode™, a carbon footprint meter, compliance with ENERGY STAR 5.0, TCO 5.0 and EPEAT™ Silver, and a significant reduction in packaging materials to help reduce shipping costs and environmental waste.

Series Features and Benefits

Energy efficiency is optimized as a result of the display's "green" technology

ECO Mode function helps save power, reduce heat and extend the life of the display by allowing the user to dim/reduce the brightness

Intelligent Power Manager (IPM) system shifts the monitor to a lower power consumption level or automatically powers it down when it is on but not in use

Carbon footprint meter helps track and calculate the savings of green gas emissions

EPEAT Silver compliance ensures the displays reduce hazardous waste and electricity usage, resulting in lower energy costs and increased protection for the environment

ENERGY STAR 5.0 and TCO 5.0 compliance reduce electrical costs and lowers total cost of ownership

Ambix® dual-input technology allows for digital/analog compatibility with upgraded video cards and software as well as connection to two systems

Touch integration-enabling design increases application options (AS191WM, AS221WM & AS231WM)

Built-in multimedia speakers provide sound for business applications such as conferencing (AS191WM, AS221WM & AS231WM)

NaViSet™ software (available via download) offers an expanded and intuitive interface, allowing you to more easily adjust display settings via mouse and keyboard

Rapid Response technology delivers virtually uninterrupted, undistorted viewing of high-speed, full-motion video

NEC Display Solutions' quality and reliability provide peace of mind with a 3-year limited parts and labor warranty (including backlight) and unrivaled customer service and technical support

Model	AccuSync AS171	AccuSync AS191	AccuSync AS191WM	AccuSync AS221WM	AccuSync AS231WM
Display					
Viewable Image Size	17"	19"	19" widescreen	22" widescreen	23" widescreen
Pixel Pitch	0.264mm	0.294mm	0.284mm	0.282mm	0.265mm
Pixels Per Inch	96 @ native resolution	86 @ native resolution	90 @ native resolution	90 @ native resolution	96 @ native resolution
Brightness (typical)	250 cd/m ²	250 cd/m ²	250 cd/m ²	250 cd/m ²	250 cd/m ²
Contrast Ratio (typical)	1000:1	900:1	1000:1	1000:1	1000:1
Viewing Angle (typical)	85°/85°/85°/85° (CR > 10)	85°/85°/85°/85° (CR > 5)	88°/88°/88°/88° (CR > 5)	88°/88°/88°/88° (CR > 5)	85°/85°/88°/88° (CR > 5)
Response Time (typical)	5ms	5ms	5ms	5ms	5ms
Display Colors	More than 16.7million	More than 16.7million	More than 16.7million	More than 16.7million	More than 16.7million
Synchronization Range					
Horizontal	31.5-81.1 KHz	31.5-81.1 KHz	31.5-81.1 KHz	31.5-82.3 KHz	31.5-82.3 KHz
Vertical	56 - 76 Hz	56 - 76 Hz	56 - 75 Hz	56 - 75 Hz	56 - 75 Hz
Inputs	VGA, DVI-D	VGA, DVI-D	VGA, DVI-D	VGA, DVI-D	VGA, DVI-D
Resolutions Supported	720 x 400 @ 70 Hz 640 x 480 @ 60-75 Hz 800 x 600 @ 56-75 Hz 832 x 624 @ 75 Hz 1024 x 768 @ 60-75 Hz 1152 x 864 @ 75 Hz 1152 x 870 @ 75 Hz 1280 x 960 @ 60-75 Hz 1280 x 1024 @ 60-75 Hz	720 x 400 @ 70 Hz 640 x 480 @ 60-75 Hz 800 x 600 @ 56-75 Hz 832 x 624 @ 75 Hz 1024 x 768 @ 60-75 Hz 1152 x 864 @ 75 Hz 1152 x 870 @ 75 Hz 1280 x 960 @ 60-75 Hz 1280 x 1024 @ 60-75 Hz	720 x 350 @ 70 Hz 720 x 400 @ 70 Hz 640 x 480 @ 60-75 Hz 800 x 600 @ 56-75 Hz 800 x 600 @ 56-75 Hz 1024 x 768 @ 60-75 Hz 1024 x 768 @ 75 Hz 1152 x 864 @ 75 Hz 1152 x 870 @ 75 Hz 1280 x 720 @ 60 Hz 1280 x 768 @ 60 Hz 1280 x 960 @ 60 Hz 1280 x 960 @ 75 Hz 1280 x 1024 @ 60-75 Hz 1360 x 768 @ 60 Hz 1440 x 900 @ 60-75 Hz	720 x 350 @ 70 Hz 720 x 400 @ 70 Hz 640 x 480 @ 60-75 Hz 640 x 480 @ 66 Hz 800 x 600 @ 56-75 Hz 1024 x 768 @ 60-75 Hz 1024 x 768 @ 75 Hz 1152 x 864 @ 75 Hz 1152 x 870 @ 75 Hz 1280 x 720 @ 60 Hz 1280 x 768 @ 60-75 Hz 1280 x 960 @ 60 Hz 1280 x 960 @ 75 Hz 1280 x 1024 @ 60-75 Hz 1360 x 768 @ 60 Hz 1440 x 900 @ 60-75 Hz 1400 x 1050 @ 60-75 Hz 1680 x 1050 @ 60 Hz	720 x 350 @ 70 Hz 720 x 400 @ 70 Hz 640 x 480 @ 60-75 Hz 640 x 480 @ 66 Hz 800 x 600 @ 56-75 Hz 832 x 600 @ 56-75 Hz 1024 x 768 @ 60-75 Hz 1024 x 768 @ 75 Hz 1152 x 864 @ 75 Hz 1152 x 870 @ 75 Hz 1280 x 720 @ 60 Hz 1280 x 768 @ 60-75 Hz 1280 x 960 @ 60 Hz 1280 x 960 @ 60 Hz 1280 x 1024 @ 60-75 Hz 1360 x 768 @ 60 Hz 1440 x 900 @ 60-75 Hz 1400 x 1050 @ 60-75 Hz 1680 x 1050 @ 60 Hz 1920 x 1080 @ 60 Hz
Native Resolution	1280 x 1024	1280 x 1024	1440 x 900	1680 x 1050	1920 x 1080
Additional Features	Tilt, push-button release stand, 2-step ECO Mode (ECO Mode 1&2), carbon footprint meter, cable management, sRGB, digital smoothing, 5-preset AccuColor control, No Touch Auto Adjust, DDC/CI, NaViSet software, Plug and Play (VESA DDC 1/2B), VESA DPMS power management, VESA mount, OSD user control	Tilt, one-touch ECO Mode key, carbon footprint meter, cable management, sRGB, digital smoothing, 5-preset AccuColor control, No Touch Auto Adjust, DDC/CI, NaViSet software, Plug and Play (VESA DDC 1/2B), VESA DPMS power management, VESA mount, OSD user control	Tilt, 2-step ECO Mode (ECO Mode 1&2), carbon footprint meter, cable management, DVI-D with HDCP, sRGB, digital smoothing, 5-preset AccuColor control, No Touch Auto Adjust, DDC/CI, NaViSet software, Plug and Play (VESA DDC 1/2B), VESA DPMS power management, VESA mount, OSD user control	Tilt, 2-step ECO Mode (ECO Mode 1&2), carbon footprint meter, cable management, DVI-D with HDCP, sRGB, digital smoothing, 5-preset AccuColor control, No Touch Auto Adjust, DDC/CI, NaViSet software, Plug and Play (VESA DDC 1/2B), VESA DPMS power management, VESA mount, OSD user control	Tilt, 2-step ECO Mode (ECO Mode 1&2), touch-integratable, carbon footprint meter, cable management, DVI-D with HDCP, sRGB, digital smoothing, 5-preset AccuColor control, No Touch Auto Adjust, DDC/CI, NaViSet software, Plug and Play (VESA DDC 1/2B), VESA DPMS power management, VESA mount, OSD user control
Regulatories and Compliance	UL /C-UL or CSA, PCT (Gost), C-tick, FCC Class B/Canadian DOC, MPR II / MPR III, PSB, NOM, Windows Vista, TUV GS, TUV Ergonomie, CE, GEEA/ Energy label, SASO, ISO 9241-307, Pb free, RoHS, EPEAT Silver, ENERGY STAR 5.0 and TCO 5.0 compliant, Windows 7	UL /C-UL or CSA, PCT (Gost), C-tick, FCC Class B/Canadian DOC, MPR II / MPR III, PSB, NOM, Windows Vista, TUV GS, TUV Ergonomie, CE, GEEA/ Energy label, SASO, ISO 9241-307, Pb free, RoHS, EPEAT Silver, ENERGY STAR 5.0 and TCO 5.0 compliant, Windows 7	UL /C-UL or CSA, PCT (Gost), C-tick, SB-50 (California), FCC Class B/Canadian DOC, MPR II / MPR III, PSB, NOM, Windows Vista, TUV GS, TUV Ergonomie, CE, GEEA/ Energy label, SASO, ISO 9241-307, Pb free, RoHS, EPEAT Silver, ENERGY STAR 5.0 and TCO 5.0 compliant, Windows 7	UL /C-UL or CSA, PCT (Gost), C-tick, SB-50 (California), FCC Class B/Canadian DOC, MPR II / MPR III, PSB, NOM, Windows Vista, TUV GS, TUV Ergonomie, CE, GEEA/ Energy label, SASO, ISO 9241-307, Pb free, RoHS, EPEAT Silver, ENERGY STAR 5.0 and TCO 5.0 compliant, Windows 7	UL /C-UL or CSA, PCT (Gost), C-tick, SB-50 (California), FCC Class B/Canadian DOC, MPR II / MPR III, PSB, NOM, Windows Vista, TUV GS, TUV Ergonomie, CE, GEEA/ Energy label, SASO, ISO 9241-307, Pb free, RoHS, EPEAT Silver, ENERGY STAR 5.0 and TCO 5.0 compliant, Windows 7
Touch-Capable	No	No	Yes	Yes	Yes
Voltage Rating	AC100-120V / AC 220-240V	AC100-120V / AC 220-240V	AC100-120V / AC 220-240V	AC100-120V / AC 220-240V	AC100-120V / AC 220-240V
Power Consumption (typical)					
On	21W	24W	21W	24W	25W
ECO Mode 1/2	18W / 14W	20W / 15W	18W / 15W	21W / 17W	22W / 18W
Power Savings Mode	0.40W	0.40W	0.4W	0.42W	0.42W
Dimensions (W x H x D)					
Net (with stand)	14.7 x 14.7 x 8.1 in. / 373.2 x 373.1 x 205.1mm	16.2 x 15.9 x 8.1 in. / 412.5 x 403.1 x 205.1mm	17.3 x 13.7 x 8.3 in. / 439.4 x 347.1 x 209.8mm	19.9 x 15.4 x 8.7 in. / 505.2 x 390.9 x 221.8mm	21.5 x 14.9 x 8.7 in. / 546 x 378.6 x 221.8mm
Net (without stand)	14.7 x 12.2 x 2.5 in. / 373.2 x 310.2 x 69mm	16.2 x 13.4 x 2.7 in. / 412.5 x 341.2 x 69mm	17.3 x 11.8 x 2.5 in. / 439.4 x 299.8 x 64.6mm	19.9 x 13.5 x 2.6 in. / 505.2 x 342.9 x 65.2mm	21.5 x 13.1 x 2.6 in. / 546 x 334 x 65.2mm
Weight					
Net (with stand)	8.6 lbs. / 3.9 kg	9.7 lbs. / 4.4 kg	9.7 lbs. / 4.4 kg	11 lbs. / 5 kg	11.9 lbs. / 5.4 kg
Net (without stand)	7.7 lbs. / 3.5 kg	8.8 lbs. / 4 kg	9 lbs. / 4.1 kg	10.4 lbs. / 4.7 kg	11 lbs. / 5 kg
VESA Hole Configuration Specifications	100 x100mm	100 x100mm	100 x100mm	100 x100mm	100 x100mm
Environmental Conditions					
Operating Temperature	5-35°C / 41-95°F	5-35°C / 41-95°F	5-35°C / 41-95°F	5-35°C / 41-95°F	5-35°C / 41-95°F
Operating Humidity	20-80%	20-80%	20-80%	20-80%	20-80%
Operating Altitude	2000m / 6562 ft.	2000m / 6562 ft.	2000m / 6562 ft.	2000m / 6562 ft.	2000m / 6562 ft.
Storage Temperature	-10-60°C / 14-140°F	-10-60°C / 14-140°F	-10-60°C / 14-140°F	-10-60°C / 14-140°F	-10-60°C / 14-140°F
Storage Humidity	10-85%	10-85%	10-85%	10-85%	10-85%
Storage Altitude	12,192m / 40,000ft	12,192m / 40,000ft	12,192m / 40,000 ft.	12,192m / 40,000 ft.	12,192m / 40,000 ft.
Limited Warranty	3 year parts and labor, including backlight	3 year parts and labor, including backlight	3 year parts and labor, including backlight	3 year parts and labor, including backlight	3 year parts and labor, including backlight
Technical Support	M - F (7am - 7pm CST)	M - F (7am - 7pm CST)	M - F (7am - 7pm CST)	M - F (7am - 7pm CST)	M - F (7am - 7pm CST)



OSD is a registered trademark, and AccuSync, ECO Mode, NaViSet, No Touch Auto Adjust and Rapid Response are trademarks of NEC Display Solutions. All other brand or product names are trademarks or registered trademarks of their respective holders. Product specifications subject to change. 3/10 ver. 4.

©2010 NEC Display Solutions of America, Inc. All rights reserved.

NEC Display Solutions

500 Park Boulevard, Suite 1100
Itasca, IL 60143
866-NEC-MORE

NEC