VG732m

17" LCD MONITOR

WITH ENERGY STAR[®], HEIGHT ADJUST AND MULTIMEDIA

Full multimedia performance.

The ViewSonic® 17" VG732m offers a feature-rich, price-performance solution for today's business applications with mixed data, audio, graphics and video content. It's equipped with features not normally offered in value-positioned displays. With its FAST 5MS VIDEO RESPONSE, the VG732m provides ULTRA-SMOOTH STREAMING VIDEO and scrolling text. OptiSync® analog and digital inputs ensure seamless compatibility with the installed base of VGA-output sources as well as pure digital DVI connectivity. Advanced ergonomic functions such as HEIGHT ADJUST AND SWIVEL ALLOW FOR ERGONOMIC FLEXIBILITY. Integrated stereo speakers provide a rich, uncluttered multimedia experience. For a no-compromise display solution on a strict business budget, choose the endless possibilities of the VG732m.



5MS RESPONSE FOR MULTIMEDIA EXCELLENCE

- ClearMotiv® 5ms video response time
 Fast 5ms video response delivers broadcast-quality video.
- > Dynamic Structure™ technology Innovative liquid crystal composition and pixel matrix accelerate video response for seamless video and intense graphics.
- High brightness and contrast ratio 250-nit brightness (typ) and 1000:1 contrast ratio (typ) for rich, detailed images.
- > 1280x1024 optimum resolution
- OptiSync® digital/analog inputs expand your connectivity Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- AutoTune® Function Automatically optimizes display settings without requiring user adjustments.
- > Height adjustment and wall-mount versatility
 Ergonomic flexibility with height adjustment
 and 360° swivel base and VESA° wall-mount interface.
- > Multimedia enhanced

 Save workspace and enjoy rich, stereo sound with two built-in stereo speakers
- > Windows Vista approved
- > PC and Mac® compatible
- > ENERGY STAR® 5.0 qualified





VG732m

17" LCD MONITOR WITH ENERGY STAR®, HEIGHT ADJUST AND MULTIMEDIA







HEIGHT ADJUST










LCD	Туре	17" color TFT active matrix SXGA LCD
	Display Area	13.3" horizontal x 10.6" vertical; 17.0" diagonal
	Optimum Resolution	1280x1024
	Contrast Ratio	1000:1 (typ); 100,000:1 (dynamic)
	Viewing Angles	160° horizontal, 160° vertical @ contrast ratio > 5:1
	Response Time	5ms (typ)
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	250 cd/m2 (typ)
	Panel Surface	Anti-glare
VIDEO INPUT	Analog/Digital	RGB analog (75 ohms, 0.7 Vp-p)/DVI-D
	Frequency	F _h : 24~82kHz, F _v : 50~75Hz
	Sync	H/V separated (TTL)
COMPATIBILITY	PC	VGA up to 1280x1024 non-interlaced
	Mac**	Power Mac [™] G3/G4/G5 up to 1280x1024
CONNECTOR	Analog/Digital	15-pin mini D-sub/DVI-D
	Audio In	Stereo mini audio line in
	Power	3-pin AC plug
POWER	Voltage	AC 100–240V (universal), 50–60Hz (auto switch)
	Consumption	25W (typ)
AUDIO	Speakers	2x1.5-watt
CONTROLS	Basic	Power, 1, down, up, 2, mute
	OnView®	Auto image adjust, brightness, contrast, input selection,
		ViewMatch® color adjust (sRGB, 9300K, 7500K, 6500K, 5400K)
		information (mode, model number, serial number), audio
		(volume, mute), manual image adjust (H. size, H. position,
		V. position, fine tune, sharpness), setup menu (language,
		resolution notice, OSD position, OSD timeout, OSD
		background), memory recall
ERGONOMICS		Height adjustment range 3.2", tilt, swivel range 360°
OPERATING	Temperature	32-104°F (0-40°C)
CONDITIONS	Humidity	10–90% (non-condensing)
DIMENSIONS	Physical with stand	15.2" x 18.7" x 9" (386.8mm x 475.2mm x 230mm)
(W x H x D)	Physical without stand	15.2" x 14.4" x 2.6" (386.8mm x 366.6mm x 67mm)
WEIGHT	Net with stand	11.1 lb. (5.0 kg)
	Net without stand	8.2 lb. (3.7 kg)
	Gross with stand	15.4 lb. (7.0 kg)
REGULATIONS		UL, cUL, FCC-B, CB, CE, ENERGY STAR®, NOM, GS, ICES
		003, TUV-S, ERGO, TCO'05, GOST-R, SASO, BSMI, CCC, PSB
		C-TICK, RoHS, EPEAT-Silver
RECYCLE/DISPOSAL		The lamp in this product contains mercury. Please dispose of
		in accordance with local, state or federal laws.
POWER MANAGEMENT		ENERGY STAR® 5.0 standards
POWER MANAG	SEMENT	LIVENGT STAIL 5.0 Stational Co.
		LCD display, VGA cable, DVI cable, power cable,
POWER MANAG PACKAGE CONT		





ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2010 ViewSonic Corporation. All rights reserved. [14823-018-03/10] VG732m-1