Learn Big IN2100EP Series



Dashboard



Ahead in the Classroom

For educators & district administrators seeking a digital projector for the classroom the InFocus Learn Big IN2100EP projector series provides essential features and performance at an affordable price.

InFocus IN2100EP series DLP® Projectors with BrilliantColor[™] technology eliminate the trade-off between color fidelity and performance. This new projector series combines a 5 segment color wheel with 2500 lumens and a 2000:1 contrast ratio. Advanced connectivity options include multiple computer and audio inputs; a wireless-ready port for easy upgrades to InFocus LiteShow II; and an RS-232 port for integration with classroom technology control systems.

The IN2100EP series is available in two resolutions:

- Good SVGA (800x600); for older PCs + DVD players
- Better XGA (1024x768); the current industry standard





Make the grade

The IN2100EP series is built to last with DLP® technology

promising lower cost of ownership, longer life and improved reliability than other technologies such as LCD.

These projectors are dust-free, having eliminated fan filters and lamp screen maintenance the IN2100EP series is rated for 24x7 operation. The lamp lasts up to 3000 hours and when necessary can be quickly changed without removing an installed projector from the ceiling, saving time and maintenance expense. Installation options are many, including ceiling-mount, wallmount and cart-mount options to keep the IN2100EP secure.

Just the Facts

2500 Lumens	bright images in high ambient light environments
Connectivity	(2) computer in, (2) audio in, RS232 and Wireless-Ready port
Lamp life	2500 norm, 3000 eco offers a lower operating cost
BrilliantColor™ Technology	brighter, more realistic colors
DLP [®] Technolgy	superior reliability and lower total cost of ownership
Warranty	standard 3-year projector, 1-year lamp warranty
Remote	newly designed, easy to use remote with more functions
Security	Kensington [®] lock and PIN code feature

The IN2100EP projector series is first to ship with the new Learn Big 2 remote control with enhanced functionality

INFOCUS SPECIFICATIONS*

Display TechnologyTexas Instruments DLP® Technology.55" LVDS DDP230 /w BrilliantColor™Brightness2500 Im normal, 1800 Im ecoContrast Ratio2000:1Input Sources(2) D-sub HD15, S-Video, Composite Video, USB, (2) Audio-in, RS232Output SourcesMonitor Loop-thru (HD15), Audio out, DC output: 5V 2AMax Resolution**IN2102EP: XGASupported Aspect Ratio4:3 (default), 5:4, 16:9, 16:10Video CompatibilityNTSC/NTSC4.43/PAL/PAL-M/PAL-N/SECAM and SDTV(480/576), EDTV(480/576), IDTV(720p/1080)Number of Colors16.7 Million, True colorColor Wheel5 segment (RGBYW)H-Synch Range31 ~ 79 KHzV-Synch Range50 ~ 85 HzKeystone Correction+/- 20 deg. (Vertical)Min Image Size (width)0.61 mMax Image Size (width)0.61 mMax Image Size (width)1.97 - 2.16 (Distance/Width)Projection Distance1.2 - 10 mImage Offset115%Projection MethodsFront, Rear, Ceiling-Front, CeilingRearAudio200W normal, 170W ecoProduct Uleyshy100-240/ac, 50/60HzOperating Temperature5 - 35° CMax Houges Size (Valva)100-240/ac, 50/60HzOperating Temperature5 - 35° CMax Intude10000 fShipping Viefn1.58(A)Shipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Volts normal, 220 Watts ecoPower Consumption250 Volts normal, 220 Watts ecoPower Consumption <t< th=""><th>Native Resolution**</th><th>IN2102EP: SVGA IN2104EP: XGA</th></t<>	Native Resolution**	IN2102EP: SVGA IN2104EP: XGA
Contrast Ratio2000:1Input Sources(2) D-sub HD15, S-Video, Composite Video, USB, (2) Audio-in, RS232Output SourcesMonitor Loop-thru (HD15), Audio out, DC output: SV 2AMax Resolution**IN2102E: XGASupported Aspect Ratio4:3 (default), 5:4, 16:9, 16:10Video CompatibilityNTSC/NTSC4.43/PAL/PAL-M/PAL-N/SECAM and SDTV(480i/576i), EDTV(480i/576p), HDTV(720p/1080i)Number of Colors16.7 Million, True colorColor Wheel5 segment (RGB/W)H-Synch Range50 ~ 85 HzKeystone Correction+/- 20 deg. (Vertical)Min Image Size (width)0.61 mMak Inge Size (width)0.61 mMak Inge Size (width)1.97 - 2.16 (Distance/Width)Projection Distance1.2 - 10 mImage Offset115%Projection MethodsFront, Rear, Ceiling-Front, CeilingRearAudio2000 mrmal, 170W ecoProduct DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product OlorBlack and SilverShipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Supply100-240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Supply100-240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude100000 ft<	Display Technology	Texas Instruments DLP® Technology .55″ LVDS DDP2230 /w BrilliantColor™
Input Sources(2) D-sub HD15, S-Video, Composite Video, USB, (2) Audio-in, RS232Output SourcesMonitor Loop-thru (HD15), Audio out, DC output: SV 2AMax Resolution**IN2104EP: XGASupported Aspect Ratio4:3 (default), 5:4, 16:9, 16:10Video CompatibilityNTSC/VITSC4.43/PAL/PAL-M/PAL-M/SECAM and SDTV(480i/576i), EDTV(480p/576p), HDTV(720p/1080i)Number of Colors16.7 Million, True colorColor Wheel5 segment (RGBYW)H-Synch Range51 ~ 79 KHzV-Synch Range50 ~ 85 HzKeystone Correction+/- 20 deg. (Vertical)Min Image Size (width)6.09 mZoom Ratio1.1:1Throw Ratio (distance/image width)1.97 - 2.16 (Distance/Width)Projection Distance1.2 - 10 mImage Offset115%Product DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product ColorBlack and SilverShipping Weight11.61bs (5.8kg)Shipping Weight11.61bs (5.8kg)Shipping Weight11.61bs (5.8kg)Shipping Weight100~240Vac, 50/60HzOperating Temperature5 - 35° CMax Aktide10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Français/ Deutsch/ Italiano / Korean / Norwegian/ Portuge/s Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Durch / Polish / Jurkish / Danish / FinnishLamp Life2	Brightness	2500 lm normal, 1800 lm eco
Output SourcesMonitor Loop-thru (HD15), Audio out, DC output: 5V 2AMax Resolution**IN2102EP: XGASupported Aspect Ratio4:3 (default), 5:4, 16:9, 16:10Video CompatibilityNTSC/NTSC4.43/PAL/PAL-N/FAL-N/SECAM and SDTV(480)/576), EDTV(480)/576), HDTV(720p/1080i)Number of Colors16.7 Million, True colorColor Wheel5 segment (RGBYW)H-Synch Range50 ~ 85 HzKeystone Correction+/- 20 deg. (Vertical)Min Image Size (width)0.61 mMax Image Size (width)0.61 mMax Image Size (width)1.97 - 2.16 (Distance/Width)Projection Distance1.2 - 10 mImage Offset115%Projection MethodsFront, Rear, Ceiling-Front, CeilingRearAudio2W speakerControlR5232, USBLamp200W normal, 170W ecoProduct DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product OlorBlack and SilverShipping Weight1.16lbs (5.8kg)Shipping DimensionsHeight: 9.4" (239mm) Length: 9.5" (240mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Supply100-240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShipping Weight1.16lbs (Farngais/ Deutsch/ Italiano / Korean / Norwegian / Portugués / Russian / Simplified Chinese / Spanish / Francisis/ Deutsch/ Jtaliano / Korean / Norwegian / Portugués / Russian / Simplified Chinese / Spanish / FinnishLamp Life2500 daysAudible Noise35dB	Contrast Ratio	2000:1
Max Resolution**IN2102EP : XGA IN2104EP : SXGASupported Aspect Ratio4/3 (default), 5/4, 16:9, 16:10Video CompatibilityNTSC/NTSC4.43/PAL/PAL-M/PAL-N/SECAM and SDTV(480i/576i), EDTV(480p/576p), HDTV(720p/1080i)Number of Colors16.7 Million, True colorColor Wheel5 segment (RGBYW)H-Synch Range51 ~ 79 KHzV-Synch Range50 ~ 85 HzKeystone Correction+/- 20 deg. (Vertical)Min Image Size (width)0.61 mMax Image Size (width)6.09 mZoom Ratio1.1:1Throw Ratio (distance/image width)1.97 - 2.16 (Distance/Width)Projection Distance1.2 - 10 mImage Offset115%Projection MethodsFront, Rear, Ceiling-Front, CeilingRearAudio2W speakerControlR5232, USBLamp200W normal, 170W ecoProduct DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product ColorBlack and SilverShipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Supply100~240Vac, 50/60HzOperating Temperature5 - 33° CMax Altitude10000 ftShips with (HW accessory only)Power cond, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Français / Deutsch/Italiano / Korean / Norwegian/ Portugués / Russian / Simplified Chinese / Spanish / Françitional Chinese / Spanish / Françitional Chinese / Spanish / Françitional Chinese / Spanish / Fra	Input Sources	(2) D-sub HD15, S-Video, Composite Video, USB, (2) Audio-in, RS232
IN2104EP : SXGASupported Aspect Ratio4:3 (default), 5:4, 16:9, 16:10Video CompatibilityNTSC/NTSC4.43/PAL/PAL-N/SECAM and SDTV(480i/576i), EDTV(480p/576p), HDTV(720p/1080i)Number of Colors16.7 Million, True colorColor Wheel5 segment (RGBYW)H-Synch Range31 ~ 79 KHzV-Synch Range50 ~ 85 HzKeystone Correction+/- 20 deg. (Vertical)Min Image Size (width)0.61 mMax Image Size (width)6.09 mZoom Ratio1.1 : 1Throw Ratio (distance/mage width)1.97 - 2.16 (Distance/Width)Projection Distance1.2 - 10 mImage Offset115%Projection MethodsFront, Rear, Ceiling-Front, CeilingRearAudio2W speakerControlRS232, USBLamp200W normal, 170W ecoProduct DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product ColorBlack and SilverShipping Weight11.6lbs (5.8kg)Shipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Consumption250 Watts normal, 220 Watts ecoPower Supply100~240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesErigits/ Français/ Deutsch/ Italiano / Korean / Norwegian/ Portugués / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedi	Output Sources	Monitor Loop-thru (HD15), Audio out, DC output: 5V 2A
Video CompatibilityNTSC/NTSC4.43/PAL/PAL-M/PAL-N/SECAM and SDTV(480i/576i), EDTV(480p/576p), HDTV(720p/1080i)Number of Colors16.7 Million, True colorColor Wheel5 segment (RGBYW)H-Synch Range31 ~ 79 KHzV-Synch Range50 ~ 85 HzKeystone Correction+/-20 deg. (Vertical)Min Image Size (width)0.61 mMax Image Size (width)6.09 mZoom Ratio1.1 : 1Throw Ratio (distance/mage width)1.97 - 2.16 (Distance/Width)Projection Distance1.2 - 10 mImage Offset115%Projection MethodsFront, Rear, Ceiling-Front, CeilingRearAudio2W speakerControlRS232, USBLamp200W normal, 170W ecoProduct DimensionsHeight: 43" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product ColorBlack and SilverShipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Supply100~240Vac, 50/60HzOperating Temperature5 - 35" CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Francias/ Deutsch/ Italiano / Korean / Norwegian / Portugués / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / FinnishLamp Life2500 hours normal, 3000 hours eco***Audible Noise35dB normal, 32dB ecoProtugués / Russian / Jimplifed Chinese /	Max Resolution**	
EDTV(480p/576p), HDTV(720p/1080i)Number of Colors16.7 Million, True colorColor Wheel5 segment (RGBYW)H-Synch Range50 ~ 85 HzKeystone Correction+/- 20 deg. (Vertical)Min Image Size (width)0.61 mMax Image Size (width)6.09 mZoom Ratio1.1 : 1Throw Ratio (distance/image width)1.97 - 2.16 (Distance/Width)Projection Distance1.2 - 10 mImage Offset115%Projection MethodsFront, Rear, Ceiling-Front, CeilingRearAudio2W speakerControlR5232, USBLamp200W normal, 170W ecoProduct DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product OlorBlack and SilverShipping Weight11.6lbs (5.8kg)Shipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Supply100~240Vac, 50/60HzOperating Temperature5 - 35° CMax Alitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Français/ Deutsch/ Italiano / Korean / Norwegian/ Portugués / Russian / Simplified Chinese / Spanish / Traditional Chinese / Span	Supported Aspect Ratio	4:3 (default), 5:4, 16:9, 16:10
Color Wheel5 segment (RGBYW)H-Synch Range31 ~ 79 KHzV-Synch Range50 ~ 85 HzKeystone Correction+/- 20 deg (Vertical)Min Image Size (width)0.61 mMax Image Size (width)6.09 mZoom Ratio1.1 : 1Throw Ratio (distance/image width)1.97 - 2.16 (Distance/Width)Projection Distance1.2 - 10 mImage Offset115%Projection MethodsFront, Rear, Ceiling-Front, CeilingRearAudio2W speakerControlR5232, USBLamp200W normal, 170W ecoProduct DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product ColorBlack and SilverShipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Supply100-240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShipping Vieght500 hurs, normal, 3000 hours eco***Autible Noise35dB normal, 32dB ecoProjector Warranty3 years, (24x7 operation compatible)Lamp Warranty1 yearAccessories Warranty90 daysApprovalsC-Tick mark (Australia) NOM certification (Mexico), CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Video Compatibility	
H-Synch Range31 ~ 79 KHzV-Synch Range50 ~ 85 HzKeystone Correction+/- 20 deg. (Vertical)Min Image Size (width)0.61 mMax Image Size (width)6.09 mZoorn Ratio1.1 : 1Throw Ratio (distance/image width)1.97 - 2.16 (Distance/Width)Projection Distance1.2 - 10 mImage Offset115%Projection MethodsFront, Rear, Ceiling-Front, CeilingRearAudio2W speakerControlRS232, USBLamp200W normal, 170W ecoProduct DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product ColorBlack and SilverShipping Weight11.6lbs (5.8kg)Shipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Supply100~240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Français/ Deutsch/ Italiano / Korean, Norwegian/ Porturgués / Deutsch/ Italiano / Korean, Norwegian/ Dritugués / Ducth / Polish / Turkish / Danish / FinnishLamp Life2500 hours normal, 3000 hours eco****Audible Noise35dB normal, 32dB ecoProjector Warranty1 yearAccessories Warranty90 daysApprovalsC-Tick mark (Australia) NOM certification (Mexico), CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia	Number of Colors	16.7 Million, True color
V-Synch Range50 ~ 85 HzKeystone Correction+/- 20 deg. (Vertical)Min Image Size (width)0.61 mMax Image Size (width)6.09 mZoom Ratio1.1 : 1Throw Ratio (distance/image width)1.97 - 2.16 (Distance/Width)Projection Distance1.2 - 10 mImage Offset115%Projection MethodsFront, Rear, Celling-Front, CeilingRearAudio2W speakerControlRS232, USBLamp200W normal, 170W ecoProduct DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product ColorBlack and SilverShipping Weight11.61bs (5.8kg)Shipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Consumption250 Watts normal, 220 Watts ecoPower Supply100-240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Français/ Deutsch/ Italiano / Korean / Norwegian/ Portugués / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / FinnishLamp Life2500 hours normal, 320B ecoProjector Warranty3 years, (24X7 operation compatible)Lamp Warranty1 yearAccessories Warranty90 daysApprovalsC-Tick mark (Australia) NOM certification (Mexico), CE (Europe), UL & CUL (USA and Cana	Color Wheel	5 segment (RGBYW)
Keystone Correction+/- 20 deg. (Vertical)Min Image Size (width)0.61 mMax Image Size (width)6.09 mZoom Ratio1.1 : 1Throw Ratio (distance/image width)1.97 - 2.16 (Distance/Width)Projection Distance1.2 - 10 mImage Offset115%Projection MethodsFront, Rear, Ceiling-Front, CeilingRearAudio2W speakerControlRS232, USBLamp200W normal, 170W ecoProduct DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product ColorBlack and SilverShipping Weight11.6lbs (5.8kg)Shipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Supply100-240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Français/ Deutsch/ Italiano / Korean / Norwegian/ Portugués / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / FinnishLamp Life2500 hours normal, 320B ecoProjector Warranty3 years, (24X7 operation compatible)Lamp Warranty1 yearAccessories Warranty90 daysApprovalsC-Tick mark (Australia) NOM certification (Mexico), CE (Europe), UL & CUL (USA and Canada), FCC (USA), IR	H-Synch Range	31 ~ 79 KHz
Min Image Size (width)0.61 mMax Image Size (width)6.09 mZoom Ratio1.1 : 1Throw Ratio (distance/image width)1.97 - 2.16 (Distance/Width)Projection Distance1.2 - 10 mImage Offset115%Projection MethodsFront, Rear, Ceiling-Front, CeilingRearAudio2W speakerControlRS232, USBLamp200W normal, 170W ecoProduct DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product Queght6.9 lbs (3.1kg)Product ColorBlack and SilverShipping Weight11.6lbs (5.8kg)Shipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Supply100~240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/Français/ Deutsch/ Italiano / Korean / Norwegian / Português / Russian / Simplified Chinese / Spanish / Traditional Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / FinnishLamp Life2500 hours normal, 3000 hours eco***Audible Noise35dB normal, 32dB ecoProjector Warranty1 yearAccessories Warranty90 daysApprovalsC-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & e K (South Korea), CCC (China), PSB (Singapore) <td>V-Synch Range</td> <td>50 ~ 85 Hz</td>	V-Synch Range	50 ~ 85 Hz
Max Image Size (width)6.09 mZoom Ratio1.1 : 1Throw Ratio (distance/image width)1.97 - 2.16 (Distance/Width)Projection Distance1.2 - 10 mImage Offset115%Projection MethodsFront, Rear, Ceiling-Front, CeilingRearAudio2W speakerControlRS232, USBLamp200W normal, 170W ecoProduct DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product Veight6.9 lbs (3.1kg)Product ColorBlack and SilverShipping Weight11.6lbs (5.8kg)Shipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Supply100~240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Français/ Deutsch/ Italiano / Korean / Norwegian / Portuguès / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / FinnishLamp Life2500 hours normal, 302d B ecoProjector Warranty3 years, (24x7 operation compatible)Lamp Warranty1 yearAccessories Warranty90 daysApprovalsC-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Keystone Correction	+/- 20 deg. (Vertical)
Zoom Ratio1.1 : 1Throw Ratio (distance/image width)1.97 - 2.16 (Distance/Width)Projection Distance1.2 - 10 mImage Offset115%Projection MethodsFront, Rear, Ceiling-Front, CeilingRearAudio2W speakerControlRS232, USBLamp200W normal, 170W ecoProduct DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product Weight6.9 lbs (3.1kg)Product ColorBlack and SilverShipping Weight11.6lbs (5.8kg)Shipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Supply100~240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Français/ Deutsch/ Italiano / Korean / Norwegian/ Portugués / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / FinnishLamp Life2500 hours normal, 320B ecoProjector Warranty3 years, (24x7 operation compatible)Lamp Warranty1 yearAccessories Warranty90 daysApprovalsC-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Min Image Size (width)	0.61 m
Throw Ratio (distance/image width)1.97 - 2.16 (Distance/Width)Projection Distance1.2 - 10 mImage Offset115%Projection MethodsFront, Rear, Ceiling-Front, CeilingRearAudio2W speakerControlR5232, USBLamp200W normal, 170W ecoProduct DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product OirBlack and SilverShipping Weight11.6lbs (5.8kg)Shipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Supply100~240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Français/ Deutsch/ Italiano / Korean / Norwegian/ Portugués / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / FinnishLamp Life2500 hours normal, 3208 ecoProjector Warranty3 years, (24x7 operation compatible)Lamp Warranty1 yearAccessories Warranty9 daysApprovalsC-Tick mark (Australia) NOM certification (Mexico), CE (Europe), (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Max Image Size (width)	6.09 m
Projection Distance1.2 - 10 mImage Offset115%Projection MethodsFront, Rear, Ceiling-Front, CeilingRearAudio2W speakerControlR5232, USBLamp200W normal, 170W ecoProduct DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product OlorBlack and SilverShipping Weight11.6lbs (5.8kg)Shipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Supply100~240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Français/ Deutsch/ Italiano / Korean / Norwegian/ Porituguès / Russian / Simplified Chinese / Spanish / FinnishLamp Life2500 hours normal, 320B ecoProjector Warranty3 years, (24x7 operation compatible)Lamp Warranty1 yearAccessories Warranty90 daysApprovalsC.Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Zoom Ratio	1.1 : 1
Image Offset115%Projection MethodsFront, Rear, Ceiling-Front, CeilingRearAudio2W speakerControlRS232, USBLamp200W normal, 170W ecoProduct DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product OlorBlack and SilverShipping Weight11.6lbs (5.8kg)Shipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Supply100~240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Français/ Deutsch/ Italiano / Korean / Norwegian/ Portugués / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / FinnishLamp Life2500 hours normal, 3000 hours eco***Audible Noise35dB normal, 32dB ecoProjector Warranty1 yearAccessories Warranty90 daysApprovalsC-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Throw Ratio (distance/image width)	1.97 - 2.16 (Distance/Width)
Projection MethodsFront, Rear, Ceiling-Front, CeilingRearAudio2W speakerControlRS232, USBLamp200W normal, 170W ecoProduct DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product OlorBlack and SilverShipping Weight11.6lbs (5.8kg)Shipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Consumption250 Watts normal, 220 Watts ecoPower Supply100~240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Français/ Deutsch/ Italiano / Korean / Norwegian / Português / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / FinnishLamp Life2500 hours normal, 3000 hours eco***Audible Noise35dB normal, 32dB ecoProjector Warranty1 yearAccessories Warranty90 daysApprovalsC-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Projection Distance	1.2 - 10 m
Audio2W speakerControlRS232, USBLamp200W normal, 170W ecoProduct DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product Weight6.9 lbs (3.1kg)Product ColorBlack and SilverShipping Weight11.6lbs (5.8kg)Shipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Supply100~240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Français/ Deutsch/ Italiano / Korean / Norwegian / Português / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / FinnishLamp Life2500 hours normal, 3000 hours eco***Audible Noise35dB normal, 32dB ecoProjector Warranty1 yearAccessories Warranty90 daysApprovalsC-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CC (China), PSB (Singapore)	Image Offset	115%
ControlRS232, USBLamp200W normal, 170W ecoProduct DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product Weight6.9 lbs (3.1kg)Product ColorBlack and SilverShipping Weight11.6lbs (5.8kg)Shipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Consumption250 Watts normal, 220 Watts ecoPower Supply100~240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Français/ Deutsch/ Italiano / Korean / Norwegian/ Portugués / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / FinnishLamp Life2500 hours normal, 3000 hours eco***Audible Noise35dB normal, 32dB ecoProjector Warranty1 yearAccessories Warranty90 daysApprovalsC-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Projection Methods	Front, Rear, Ceiling-Front, CeilingRear
Lamp200W normal, 170W ecoProduct DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product Weight6.9 lbs (3.1kg)Product ColorBlack and SilverShipping Weight11.6lbs (5.8kg)Shipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Supply100~240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Français/ Deutsch/ Italiano / Korean / Norwegian/ Português / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / FinnishLamp Life2500 hours normal, 3000 hours eco***Audible Noise35dB normal, 32dB ecoProjector Warranty1 yearAccessories Warranty90 daysApprovalsC-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Audio	2W speaker
Product DimensionsHeight: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)Product Weight6.9 lbs (3.1kg)Product ColorBlack and SilverShipping Weight11.6lbs (5.8kg)Shipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Supply100~240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Français/ Deutsch/ Italiano / Korean / Norwegian/ Português / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / FinnishLamp Life2500 hours normal, 3000 hours eco***Audible Noise35dB normal, 32dB ecoProjector Warranty1 yearAccessories Warranty90 daysApprovalsC-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CC (China), PSB (Singapore)	Control	RS232, USB
Product Weight6.9 lbs (3.1kg)Product ColorBlack and SilverShipping Weight11.6lbs (5.8kg)Shipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Consumption250 Watts normal, 220 Watts ecoPower Supply100~240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/Français/ Deutsch/ Italiano / Korean / Norwegian/ Português / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / FinnishLamp Life2500 hours normal, 3000 hours eco***Audible Noise35dB normal, 32dB ecoProjector Warranty1 yearAccessories Warranty90 daysApprovalsC-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Lamp	200W normal, 170W eco
Product ColorBlack and SilverShipping Weight11.6lbs (5.8kg)Shipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Supply100~240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish / Français / Deutsch / Italiano / Korean / Norwegian / Português / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / FinnishLamp Life2500 hours normal, 3000 hours eco***Audible Noise35dB normal, 32dB ecoProjector Warranty1 yearAccessories Warranty90 daysApprovalsC-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Product Dimensions	Height: 4.3" (105mm) Length: 9.5" (240mm) Width: 11.7" (296mm)
Shipping Weight11.6lbs (5.8kg)Shipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Supply100~240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Français/ Deutsch/ Italiano / Korean / Norwegian/ Português / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / FinnishLamp Life2500 hours normal, 3000 hours eco***Audible Noise35dB normal, 32dB ecoProjector Warranty1 yearAccessories Warranty90 daysApprovalsC-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Product Weight	6.9 lbs (3.1kg)
Shipping DimensionsHeight: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)Power Consumption250 Watts normal, 220 Watts ecoPower Supply100~240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Français/ Deutsch/ Italiano / Korean / Norwegian/ Português / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / FinnishLamp Life2500 hours normal, 3000 hours eco***Audible Noise35dB normal, 32dB ecoProjector Warranty1 yearAccessories Warranty90 daysApprovalsC-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Product Color	Black and Silver
Power Consumption 250 Watts normal, 220 Watts eco Power Supply 100~240Vac, 50/60Hz Operating Temperature 5 - 35° C Max Altitude 10000 ft Ships with (HW accessory only) Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteries Menu Languages English/ Français/ Deutsch/ Italiano / Korean / Norwegian/ Português / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / Finnish Lamp Life 2500 hours normal, 3000 hours eco*** Audible Noise 35dB normal, 32dB eco Projector Warranty 1 year Accessories Warranty 90 days Approvals C-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Shipping Weight	11.6lbs (5.8kg)
Power Supply100~240Vac, 50/60HzOperating Temperature5 - 35° CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Français/ Deutsch/ Italiano / Korean / Norwegian/ Português / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / FinnishLamp Life2500 hours normal, 3000 hours eco***Audible Noise35dB normal, 32dB ecoProjector Warranty3 years, (24x7 operation compatible)Lamp Warranty1 yearAccessories Warranty90 daysApprovalsC-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Shipping Dimensions	Height: 9.4" (239mm) Length: 13" (330mm) Width: 16.5" (427mm)
Operating Temperature5 - 35° CMax Altitude10000 ftShips with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Français/ Deutsch/ Italiano / Korean / Norwegian/ Português / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / FinnishLamp Life2500 hours normal, 3000 hours eco***Audible Noise35dB normal, 32dB ecoProjector Warranty3 years, (24x7 operation compatible)Lamp Warranty1 yearAccessories Warranty90 daysApprovalsC-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Power Consumption	250 Watts normal, 220 Watts eco
Max Altitude 10000 ft Ships with (HW accessory only) Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteries Menu Languages English/ Français/ Deutsch/ Italiano / Korean / Norwegian/ Português / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / Finnish Lamp Life 2500 hours normal, 3000 hours eco*** Audible Noise 35dB normal, 32dB eco Projector Warranty 3 years, (24x7 operation compatible) Lamp Warranty 1 year Accessories Warranty 90 days Approvals C-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Power Supply	100~240Vac, 50/60Hz
Ships with (HW accessory only)Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteriesMenu LanguagesEnglish/ Français/ Deutsch/ Italiano / Korean / Norwegian/ Português / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / FinnishLamp Life2500 hours normal, 3000 hours eco***Audible Noise35dB normal, 32dB ecoProjector Warranty3 years, (24x7 operation compatible)Lamp Warranty1 yearAccessories Warranty90 daysApprovalsC-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Operating Temperature	5 - 35° C
Menu Languages English/ Français/ Deutsch/ Italiano / Korean / Norwegian/ Português / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / Finnish Lamp Life 2500 hours normal, 3000 hours eco*** Audible Noise 35dB normal, 32dB eco Projector Warranty 3 years, (24x7 operation compatible) Lamp Warranty 1 year Accessories Warranty 90 days Approvals C-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Max Altitude	10000 ft
Português / Russian / Simplified Chinese / Spanish / Traditional Chinese / Swedish / Dutch / Polish / Turkish / Danish / Finnish Lamp Life 2500 hours normal, 3000 hours eco*** Audible Noise 35dB normal, 32dB eco Projector Warranty 3 years, (24x7 operation compatible) Lamp Warranty 1 year Accessories Warranty 90 days Approvals C-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Ships with (HW accessory only)	Power cord, USB(AB), VGA cable, Carry Case, Remote w/ batteries
Audible Noise 35dB normal, 32dB eco Projector Warranty 3 years, (24x7 operation compatible) Lamp Warranty 1 year Accessories Warranty 90 days Approvals C-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Menu Languages	Português / Russian / Simplified Chinese / Spanish / Traditional
Projector Warranty 3 years, (24x7 operation compatible) Lamp Warranty 1 year Accessories Warranty 90 days Approvals C-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Lamp Life	2500 hours normal, 3000 hours eco***
Lamp Warranty 1 year Accessories Warranty 90 days Approvals C-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Audible Noise	35dB normal, 32dB eco
Accessories Warranty 90 days Approvals C-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Projector Warranty	3 years, (24x7 operation compatible)
Approvals C-Tick mark (Australia) NOM certification (Mexico),CE (Europe), UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Lamp Warranty	1 year
UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)	Accessories Warranty	90 days
Security Kensington® slot, Pin code		UL & CUL (USA and Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)
	Security	Kensington® slot, Pin code

* Product specifications, terms, and offerings are subject to change at any time without notice.

** Resolution support may be product specific.

*** Actual lamp life may vary based on the ambient environment and projector usage. Conditions that may affect lamp life include temperature, altitude, and rapidly switching the projector on and off.



4.3"/ 11cm



LiteShow II

This wireless adaptor enables cable-free presentations through any of the InFocus IN2100EP projector series. Switch presenters in seconds and transmit data, audio and stunning video over a 300' (95m) range.

Warranty

Providing the highest quality products and support is very important to InFocus. Just one reason why the IN2102EP and IN2104EP digital projectors come standard with a 3-year limited factory warranty on the projector (including parts and labor), 1-year limited lamp-replacement warranty and a 5-year DLP® chipset warranty. Extended product & lamp warranty programs are also available. For more information about warranty and service programs in your region, please visit: www.infocus.com/service

Optional Accessories

InFocus carries a full line of optional accessories specifically designed to work with your new IN2100 Series projector, a complete list may be found at **www.infocus.com**

Projection Screens 4:3 (SC-PD-100) 16:10 (SC-PDW-106) LiteShow II Wireless Adaptor (INLITESHOW2) Advanced Remote Control (HW-COMMANDER) Rollercase (CA-ROLLERCASE-UNIV) Ceiling Mount (SP-CEIL-UNIV) Security Locks (SEC-LOCK-01) InFocus Certified Replacement Lamp (SP-LAMP-039) Cables & Adaptors



www.InFocus.com

InFocus Corporate Headquarters: 27500 SW Parkway Avenue Wilsonville, Oregon 97070-9215, USA • Phone: (1) 503-685-8888 (1) 800-294-6400 • Fax: (1) 503-685-8887

In Europe: InFocus International BV • Louis Armstrongweg 110 • 1311 RL Almere The Netherlands • Phone: (31) 20 5792000 • Fax: (31) 36 5392999 Freephone: 008000 4636287 (008000 INFOCUS)

In Asia: 19 Tanglin Road • 7th Floor Singapore 247909 • Telephone: (65) 6334-9005 • Fax: (65) 6333-4525

©2007 InFocus Corporation. All rights reserved. Specifications are subject to change without further notice. InFocus and InFocus The Big Picture are either trademarks or registered trademarks of InFocus Corporation in the United States and other countries. DLP, the DLP logo, and the DLP medallion are trademarks of Texas Instruments. All trademarks are used with permission or are for identification purposes only and are the property of their respective companies. LB_2102_2104_2106_E_01.04.08. Part Number: 805-1173-00