# AOC®

# e2243Fwsk

| Cabinet Color | Piano-black Glossy Bezel, Back Cover and Base |
|---|---|
| Panel | TFT Active Matrix LCD, WLED Backlight<br>22" Class, Widescreen 16:9 Aspect Ratio<br>21.5" Viewable Image Size, Diagonal |
| Pixel Pitch | 0.248 x 0.248mm |
| Display Area | 476.6mm x 268.1mm |
| Brightness | 250 cd/m2 (typ) |
| Contrast Ratio | 50,000,000:1 (dynamic) |
| Response Time | 5ms (typical) |
| Viewing Angle | Horizontal: 170 Degrees (CR>10)<br>Vertical: 160 Degrees (CR>10) |
| Scanning Frequency | Horizontal: 30K~83KHz<br>Vertical: 55~75 Hz |
| Pixel Frequency | 148.5MHz |
| Maximum Resolution | 1920x1080x60Hz |
| Recommended Resolution | 1920x1080@60Hz |
| Supported Resolutions | 640x480@60/72/75Hz, 800x600@56/60/72/75Hz,<br>1024x768@60/70/75Hz, 1280x1024@60/75Hz, 1440x900@60Hz,<br>1680x1050@60Hz, 1920x1080@60Hz |
| Color | 16.7M |
| Analog Input | Analog: 0.7Vp-p(standard), 75 OHM, Positive |
| Connectors | Analog RGB Signal:  15-pin D-sub Male |
| Power Source | Universal 110~240VAC, 50/60Hz , External Power Brick |
| Power Consumption | 25 Watts ( Max. ) |
| Plug & Play | DDC/2B, DDC/CI |
| User Control | Left, Right, Power, Source/Auto, Menu |
| OSD Languages | 14 Languages including English, French and Spanish |
| Regulations | cCSAus, FCC, CE, TUV/S, ROHS, EPA 5.0, EPEAT Silver |
| Other Features | Ultra Slim (12.9mm), Illuminating Touch Key, Mercury Free WLED,<br>Low Power Consumption, Power Saving Mode, Off Timer, Eco<br>Package, User Friendly Graphical OSD Menu, includes e-Saver<br>Power Saving Software |
| Dimensions (WxHxD mm) | Monitor: 514.2x386.1x182.0, Carton:  577x522x124 |
| Dimensions (WxHxD inches) | Monitor: 20.2x15.2x7.2, Carton: 22.7x20.6x4.9 |
| Weight | 5.5 lbs (2.5 kgs) Net<br>11.9 lbs (5.4 kgs) Gross |
| Loading Qty w/pallet | 20' =  648 pcs.; 40' Std = 1440 pcs. |
| UPC Code | 685417034185 |

Note: Specifications are subject to change without notice.
A08/10