

AOC®

e2060Sda



Cabinet Color	Black with Hairline Texture
Panel	TFT Active Matrix, LED Backlight 20", 16:9 Aspect Ratio 20" Viewable Image Size, Diagonal
Pixel Pitch	0.276 x 0.276mm
Display Area	442.8mm x 249.1mm
Brightness	250 cd/m2 (typ)
Contrast Ratio	20,000,000:1 (dynamic)
Response Time	5ms (typical)
Viewing Angle	Horizontal: 170 Degrees (CR>10) Vertical: 160 Degrees (CR>10)
Scanning Frequency	Horizontal: 30K~80KHz Vertical: 50~75 Hz
Pixel Frequency	108.0MHz
Maximum Resolution	1600x900x60Hz
Recommended Resolution	1600x900@60Hz
Supported Resolutions	640x480@60/72/75Hz, 800x600@56/60/72/75Hz, 1024x768@60/70/75Hz, 1600x900@60Hz
Color	16.7M
Signal Input	Analog: 0.7Vp-p(standard), 75 OHM, Positive
Digital Input	DVI-D with HDCP*
Connectors	Analog RGB Signal: 15-pin D-sub Male Digital Signal: 24-pin DVI-D
Power Source	Universal 110~240VAC, 50/60Hz
Power Consumption	On: 35 Watts Max, Standby: <0.5W
Plug & Play	DDC/2B, DDC/CI
User Control	Left/Eco, Right/Aspect, Source/Auto, Power
OSD Languages	15 Languages including English, French and Spanish
Regulations	cTUVus, FCC, CE, TUV/S, ROHS, EPA 5.1, EPEAT Gold, Windows 7 Logo
Built-in Speakers	2Wx2
Other Features	User Friendly Graphical OSD Menu, VESA 100mm Wall Mount Compliant**, Kensington Security Slot, Includes eSaver, iMenu and Screen+ Software
Dimensions (WxHxD mm)	Monitor: 511x373x185, Carton: 534x420x115
Dimensions (WxHxD inches)	Monitor: 20.1x14.7x7.3, Carton: 21.0x16.5x4.5
Weight	2.68 kg, 5.9 lbs Net 3.93 kg, 8.6 lbs Gross
Loading Qty w/pallet	20' = 1020 pcs.; 40' Std = 2100 pcs.
UPC Code	685417050581

Note: Specifications are subject to change without notice. *High-bandwidth Digital Content Protection: Enables viewing of High-Definition contents. **Wall mount arm & bracket not included. Windows 7 and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries.