HP 2010i 50.8 cm (20 inch) Diagonal LCD Monitor

- **Movies, photos and gaming as you've never seen them**
  With 15,000:1 dynamic contrast ratio and HD Ready 1600 x 900 resolution, you'll get brilliant widescreen viewing. The 16:9 aspect ratio is perfect for watching movies, and the 5 ms response time reduces blur.

- **Energy-saving features**
  Designed with the environment in mind, the HP 2010i LCS monitor is ENERGY STAR® qualified and lowers power consumption with the two-lamp panel. So you'll save money and electricity without compromising on image quality.

- **Smart design, comfortable viewing**
  The tilt-and-swivel HP 2010i monitor ensures comfort, while QuickView modes help optimise the display for videos, photos or games. A slim profile and built-in speakers mean you'll have plenty of desk space left over.

HP 2010i 50.8 cm (20 inch) Diagonal LCD Monitor

Specifications	**Display Size:** 50.8 cm (20") 16:9 wide diagonal and viewable image **Display type:** Wide Thin Film Transistor Liquid Crystal Display active matrix **Surface treatment:** Antiglare polarizer, Antistatic **Pixel pitch:** 0.276 mm **Refresh response time:** 5 ms on-off (typical) **Brightness:** 250 cd/m2 (typical) **Contrast ratio:** 1000:1 static (typical), up to 15000:1 dynamic (typical) **Viewing angle:** 170° horizontal and 160° vertical
Interface specifications	**Video input signal:** Digital (DVI-D with HDCP) and Analog (15-pin D-sub VGA) **Display resolution:** 1600 x 900 @ 60Hz max **Recommended resolution:** All VESA modes up to 1600 x 900 @ 60Hz (native recommended) **Scan rates:** 50 to 76 Hz vertical, 24 to 83 kHz horizontal
Features	**Multimedia:** Integrated active speakers (2 x 2W per channel) with HP Power Sound and front volume control **Physical security features:** Kensington lock (sold separately) **Display moving angle:** Swivel; tilt range from +25 to -5 degrees; standard VESA 4 hole pattern 100 mm x 100 mm screw wall-mounting option with removable base **Plug and play:** Yes
Power	**Power Supply and Power Requirements:** Internal AC adapter **Power Consumption:** 28 watts maximum on operating mode; 1 watt max in power saving mode
User controls	**Display User Control Options:** Brightness, Contrast, Colour, Image Control, OSD Control, Management, Information, Factory Reset, Source Control, Exit and Languages: English, German, French, Spanish, Italian, Dutch, Simplified Chinese, Traditional Chinese, Japanese, Brazilian Portuguese
Mechanical specifications	**Dimensions (W x D x H):** 502.5 x 183 x 372 mm **Weight:** 5.2 kg **Package Dimensions (W x D x H):** 568 x 171 x 450 mm **Package Weight:** 7.2 kg **Operating Temperature Range:** 5 to 35° C, 20 to 80% relative humidity non-condensing **Storage Temperature Range:** -20 to 60° C, 5 to 95% relative humidity non-condensing
Regulatory	**Compliance Industry Standards:** ISO 13406-2, ETL, FCC approval, MPR-II, NOM, CE Marking, CISPR , VCCI, GOST (Russia), BNCI, SEMKO, Microsoft® Windows® certified (Microsoft Windows 2000, Microsoft Windows XP, Microsoft Vista and Microsoft Windows 7)
Additional Information	**Warranty:** Limited one-year parts and repair labour warranty (may vary depending on the country) **Box Content:** Monitor, AC power cable (1.9 m), DVI cable (1.8 m), Audio cable (1.8 m), Documentation CD, Limited Warranty Card **Ordering info:** WC030AA#B1S (France, Italy, Netherlands, Germany, Austria, Poland, Slovakia, Czech Republic), UPC 884962691618; WC030AA#UUG (Belgium), UPC 884962691601; WC030AA#ABU (UK & Ireland), UPC 884962691540; WC030AA#AR8 (Switzerland), UPC 884962691557; WC030AA#ABY (Denmark), UPC 884962691564; WC030AA#B1Q (Turkey, Greece, Russia), UPC 884962691625; WC030AA#ABB (Rest of Europe), UPC 884962691533; WC030AA#ABT (Israel), UPC 884962691571; WC030AA#ACQ (South Africa), UPC 884962691588; WC030AA#AB6 (French Africa), UPC 884962691632; WC030AA#B13 (English Africa), UPC 884962691649; WC030AA#ABV (Middle East), UPC 884962691595