

HP Compaq L5009tm 38,1 cm (15") LCD Touchscreen Monitor

A completely new and unique way of sensing touch delivered in a durable design

Make routine activities easier and enjoy a more productive workplace with the newly developed touch panel technology built into the HP Compaq L5009tm Touchscreen Monitor, which enables quick and easy onscreen interactivity in point-of-sale (POS), hospitality, educational, banking, manufacturing, and kiosk environments.



Feel the difference

Acoustic Pulse Recognition (APR) is an improved technology that it is built into each HP Compaq L5009tm monitor. Consisting only of a glass overlay mounted in front of the display, together with a small electronic controller board, APR technology provides a new set of benefits that have only been partially achieved before by other touch technologies. Unlike older Surface Acoustic Wave (SAW) technology, which listens for your finger to activate the screen, APR technology identifies screen taps more easily by recognizing a wider array of sounds created when the glass is touched at a given position. So whether you use a pen, a credit card, finger or a fingernail to tap from screen to screen, your inputs will be recognized.

Durable touch technology

The HP Compaq L5009tm monitor's glass screen provides high durability and is a more damage-resistant alternative to film-coated display screens. It also features a stable, removable base, which is engineered specifically for the physical demands of high-traffic touchscreen use.

Create a more efficient environment

Retain more of your profits with the HP Compaq L5009tm by allowing your customers to locate products on the shelf with the ease of touch browsing or by pleasing them with fast check-outs. Touchscreen technology also increases available workspace, virtually eliminating the need for a separate keyboard and mouse, helping your business become more efficient and productive.

HP support from around the world

Your business needs are covered with the HP Compaq L5009tm. Each monitor has a three year limited warranty backed by HP's worldwide service and support and is compatible with HP business products.





SPECIFICATIONS	
Panel type	Active Matrix TFT (thin film transistor)
Viewable image area	38,1 cm (15")
Viewing angle	120° horizontal, 100° vertical
Brightness	225 nits
Contrast ratio	400:1
Response rate	17 ms
Native resolution	1024 x 768
Input signal	VGA
Input power	Auto-Sensing, 100 to 240 VAC, 50 Hz to 60 Hz
Power consumption	30 watts maximum, 22 watts typical, standby <4 watts
Dimensions	with stand: 35.0 x 17.5 x 31.0 cm without stand: 35.0 x 5.5 x 28.0 cm
Weight	4.8 kg
Ergonomic features	Tilt range: -5° to +90°, base and stand: detachable
Environmental	Operating temperature: 0°C to 40°C; Operating humidity: 20 to 80% RH
Certification and compliance	UL listed, CSA, FCC approval, NOM, ISE for Cambodia, PSB for Singapore, BSMI for Taiwan, MIC for Korea, CCC for China, C-Tick for Australia, S-Mark for Argentina
Warranty	Limited 3 years parts, labour and on-site service, including backlight. Availability varies by region. Certain restrictions and exclusions apply. For details, contact HP Customer Support or Service

For more information, please visit www.hp.com/eur/monitors