

1529L 15" LCD Multifunction Touchmonitor



Applications

- Point of Service
- Point-of-Sale
- Loyalty systems
- Kiosk information systems
- Light industrial
- Gaming/amusement
- Home control
- Internet access points

Elo's 1529L touchmonitor expands the company's high profile family of reliable, easily integrated, multifunction touch solutions that meet the requirements of any systems integrator, OEM, or value-added reseller. The new retail-rugged 1529L includes options for a three-track magnetic stripe reader (MSR), biometric fingerprint reader, and a 2 x 20 vacuum fluorescent rear-facing display.

The new 1529L has been designed for touch from the ground up, with such features as spill-resistant sealing, a stable tilt base that is removable or reversible for wall mounting, a VESA mounting option, connectivity incorporated within the monitor, reducing the number of power bricks and communication cables, and side controls with lockout for public use.

Elo's 1529L touchmonitor offers a wide range of connectivity, including serial and USB, and a choice of Acoustic Pulse Recognition (APR), AccuTouch five-wire resistive, CarrollTouch infrared, IntelliTouch surface wave, and surface capacitive touch technologies.

The 1529L is also available as an all-in-one touchcomputer. See the 1529L Touchcomputer data sheet.

Benefits

- Integrated peripherals in a compact design
- Easy and efficient installation - reduced cables and power bricks
- Choice of reliable Elo touch technologies for exceptional display quality
- Broadest range of input options - works with any stylus
- Desktop, wall or VESA mounting



Optional rear-facing vacuum fluorescent display



Optional fingerprint reader (top), and MSR (right), with short stand

1529L 15" LCD Multifunction Touchmonitor Specifications

TOUCHMONITOR

Case/bezel color	Dark gray or beige (optional on some configurations)
Base	Short, tall or no stand
Display	Size 15" diagonal
Type	Active matrix TFT LCD
Aspect ratio	4 x 3
Useful screen area	Horizontal 11.98" (304 mm); Vertical 8.98" (228 mm)
Monitor dimensions (max. with short stand)	Width 13.99" (355 mm) Height 11.27" (286 mm) Depth 10.44" (265 mm) Dimensions vary with stand position and options selected
Optimal (native) resolution	1024 x 768
Other supported resolutions	1024 x 768 at 60, 65, 70, 75 Hz; 832 x 624 at 75 Hz; 800 x 600 at 56, 60, 72, 75 Hz; 720 x 400 at 70 Hz; 720 x 350 at 70 Hz; 640 x 480 at 60, 66 (Mac), 72, 75 Hz
Colors	16.2 million colors, 6 bit with dithering
Brightness	LCD panel: 350 cd/m ²
LCD panel with touchscreen	AccuTouch: 287 cd/m ² ; IntelliTouch 322 cd/m ² ; CarrollTouch 322 cd/m ² ; surface capacitive 294 cd/m ²
Response time	25 msec (typical)
Viewing angle (from center)	Horizontal (left/right): ±75° or 150° total; Vertical (up/down): 75°/50° or 125° total
Contrast ratio	400:1
Power dissipation	30 W max (typical)
Input video format	RGB Analog; DVI-D
Input video signal connector	Mini D-Sub 15-Pin VGA type; DVI-D connector
Input frequency	Horizontal 31–60 kHz; Vertical 56–75 Hz
Power supply	Type: AC/DC input internal; AC input (line) voltage: 85-265 VAC, 47-63 Hz; DC input: 12V ± 0.75V
Temperature	Operating: 0° C to 40° C; Storage: -20° C to 60° C
Humidity	Operating: 20% to 80%; Storage: 5% to 95%; noncondensing
Weight	Actual: 14.44 lb (6.55 kg); Shipping: 21.16 lb (9.6 kg) (approx. with touch, short stand only)
Warranty monitor	3 years
Backlight lamp life	Minimum 40,000 hours to half brightness
Agency approvals	UL/cJUL (*recognized component), FCC-A, TÜV-GS, CE, VCCI, C-Tick
Speakers	Two watt/channel speakers located in display head
On-screen display (OSD)	Side-mounted with lockout function for public use
User's controls	OSD control menu: power, up, down, menu; OSD controls: contrast, brightness, V-position, H-position, RGB, volume, YUV, phase, clock, OSD H-position, OSD V-position, OSD Time, auto adjust, OSD language (English, French, Dutch, Spanish, Japanese), input select; OSD disable/enable: power, OSD menu
Mounting options	75 mm VESA mount; removable base
Other features	Energy save mode (less than 2 watts); 2 stage DPMS; VESA DDC Plug & Play; security lock receptacle
OPTIONAL REAR FACING CUSTOMER DISPLAY 20 x 2 VACUUM FLUORESCENT	
Type	Vacuum Fluorescent Display (VFD), 2 rows, 20 characters/row
Characters	5 x 7 dot-matrix configuration, 9.5 mm height, 6.2 mm width
Format/color	ASCII/blue-green
OPTIONAL MAGNETIC STRIPE READER	
Tracks	3
Message format	ASCII
Card speed	3 to 50 inch/sec (7.6 to 127 cm/sec)
OPTIONAL FINGERPRINT READER	
Type	Optical
Verifying time	<1 sec
Sensing prism hardness	7 Mohs
Resolution	356 x 292 pixels
Image speed	Capture: 600 ms/frame; Transfer: 500 bytes/ms
Image capture error rate	<0.1%

Find out more about Elo's extensive range of touch solutions. Go to www.elotouch.com, or simply call the office nearest you.

Corporate Headquarters

Elo TouchSystems
301 Constitution Drive
Menlo Park, CA 94025-1110

800-ELO-TOUCH

Tel 1-650-361-4700
Fax 1-650-361-4747
eloinfo@elotouch.com

Europe Headquarters

Tel +32 (0)16 35 21 00
Fax +32 (0)16 35 21 01
elosales@elotouch.com

Asia-Pacific Headquarters

Tel +81 (45) 478-2161
Fax +81 (45) 478-2180
www.tps.co.jp

Latin America Headquarters

Tel 1-305-428-5210
Fax 1-305-717-4909
www.elotouch.com.ar

Tyco Electronics Corporation reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Elo TouchSystems, AccuTouch, CarrollTouch, and IntelliTouch are trademarks of Tyco Electronics Corporation. All other trademarks are the property of their respective owners.
Copyright 2006 Tyco Electronics Corporation ELO-161 10/06