

EN-7522C

22" Premium Wide Scen LCD DVR Monitor



Features

- 22" DVR LCD monitor
- Metal industrial cabinet
- LCD protection glass
- 1680x1050 max. resolution
- 1000:1 contrast
- 3D comb filter / deinterlace
- 160° / 160° viewing angle
- Multiple interface connectivity
- Built-in speaker
- PIP/PBP multi-display feature
- Cable management stand included

Specifications

Screen Size	22"
Resolution	1680 x 1050 @ 60 Hz
Pixel Pitch	0.282 x 0.282 mm
Brightness	300cd/m ²
Contrast Ratio	1000:1
Aspect Ratio	16:10
Viewing Angle (H/V)	160°/160°
Color Depth	16.7 million
Response Time	<5ms
Video System	NTSC/PAL
Frequency (H)	60 ~ 75 KHz
Frequency (V)	55 ~ 75Hz
Built-in Speakers	Yes (2W x 2)
Video In/Out (BNC Type)	2/2
S-Video In/Out	1/1
VGA In (15 Pin D-Sub)	1
DVI-D/HDMI In	1/1
Audio In	3 (L + R)
PC Stereo In/Out	1
Filter Type	3D Comb Filter/DeInterlace
Multi-Display Function	PIP/PBP
Trigger Sensor	Yes (NO/NC)
MTBF (approx.)	50,000 hours
Regulations	RoHS, TUV-NRTL (same as UL), CB, FCC(A), CE-EMC(LVD)
Parts/Labor	2 Years/2 Years
VESA Mount Size	100 x100 mm (BS M4 x 10 mm screw)
Power Consumption	< 60 W
Power Source	12VDC / 5A
Dimensions (w/stand)	508 x 371 x 140 mm / 20" x 15" x 5.5"
Weight	8.4 kg / 18.5 lbs
Operating Temp.	10°C ~ 40° C / 50°F ~ 104°F

Ordering Information

- **EN-7522C:** 22" DVR LCD Monitor, 1680x1050 max. resolution

EN-7542H

42" Premium Wide Screen LCD DVR Monitor



Features

- 42" premium wide screen LCD DVR monitor
- Full High Definition (FHD) with 1920 x 1080 max. resolution
- 900:1 contrast
- Metal industrial cabinet
- 3D comb filter / deinterlace
- 178° / 178° viewing angle
- Multiple interface connectivity
- Multi-language menu support
- Built-in speaker
- PIP / PBP multi-display feature

Specifications

Screen Size	42"
Resolution	1920 x 1080 @ 60 Hz
Pixel Pitch	0.484 x 0.484 mm
Brightness	550cd/m ²
Contrast Ratio	1000:1
Aspect Ratio	16:9
Viewing Angle (H/V)	178°/178°
Color Depth	16.7 millions
Response Time	< 8ms (G to G)
Video System	NTSC/PAL
Frequency (H)	30 ~ 80 KHz
Frequency (V)	56 ~ 75Hz
Built-in Speakers	Yes (4W x 2)
Video In/Out (BNC Type)	2/2
S-Video In/Out	1/1
VGA In (15 Pin D-Sub)	1
Component	1
DVI-D/HDMI In	1/1
Audio In/Out (RCA Type)	3 (L + R)
PC Stereo In/Out	1
Filter Type	3D Comb Filter/DeInterlace
Multi-Display Function	PIP/PBP
Trigger Sensor	Yes (NO/NC)
MTBF (approx.)	50,000 hours
Regulations	RoHS, TUV-NRTL (same as UL), CB, FCC(A), CE-EMC(LVD)
Parts/Labor	2 Years/2 Years
VESA Mount Size	400 x 200 mm (BS M8 x 16mm screw)
Power Consumption	< 230W
Power Source	AC100 ~ 240V (50/60 Hz)
Dimensions (w/stand)	1026 x 685.8 x 297.2 mm / 40.4" x 27" x 11.7"
Net Weight	34 kg / 75 lbs (w/stand) 26 kg / 57.3 lbs (w/out stand)
Operating Temp.	10°C ~ 40° C / 50°F ~ 104°F

Ordering Information

- **EN-7542H:** 42" Premium Wide Screen LCD DVR Monitor