







SPECIFICATIONS

Туре	. Fully-enclosed dynamic stereo headphones
Impedance	. 16 Ω
Sensitivity	. 105 dB
Frequency response	. 10 Hz to 24,000 Hz
Maximum input power	. 100 mW
Driver units	. 10.5 mm
Cord	. 1.2 m OFC litz wire (Straight Plug)
Plug	. 3.5 mm 3P mini-plug (Gold Plated)
Weight	. 5 g (without cord)
Accessories	. Additional Ear Tips (XS/S/M/L) x2

٦

FEATURES

- Low-resonance double layer vibration plates: for clear high and middle frequency performance and powerful bass >
- Ergonomic, sealing design: for a comfortable fit and exceptional noise isolation >
- Self-fit holder: ensures a secure, snug fit for active use >

OTHER CORE AUDIO MODELS



Г

INDIVIDUAL PACKAGE DIMENSIONS

INDIVIDUAL PACKAGE DIMENSIONS		mm			inches			
MODEL	Master Carton	Inner Carton	W	н	D	W	н	D
SE-CLX40-K	100	10	88	174	40	3.4	6.8	1.5
SE-NC31C-K	20	10	105	160	45	4.1	6.2	1.7
SE-CE11	100	10	103	177	33	4.1	7.0	1.3
SE-CL07	100	10	65	170	25	2.6	6.7	1.0
SE-M290	10	N/A	227	297	113	8.9	11.7	4.4

This product is NOT compatible with the first generation iPhone, or any other device that features a recessed audio input. Specifications and design subject to change without notice. Pioneer and the Pioneer logo are trademarks or registered trademarks of Pioneer Corporation. iPhone and iPod are trademarks of Apple Inc., registered in the U.S. and other countries. (C) 2011 Pioneer Electronics (USA) Inc.