

## 300Mbps Wireless N VoIP ADSL2+ Modem Router

### TD-VG3631

#### ⦿ Features:

- High speed DSL modem, NAT router and wireless access point in one device providing a one-stop networking solution
- Wireless N speed up to 300Mbps makes it ideal for heavy bandwidth consuming or interruption sensitive applications like online gaming, Internet calls and even the HD video streaming
- Supporting both traditional land lines and VoIP network offers you a multiple choice when making phone calls.
- Various call features such as caller ID, call waiting, call holding, call forwarding, 3-way conference calls and voicemail
- USB 2.0 port supports Storage Sharing (Samba or FTP), Media Server, Print Server<sup>1</sup> and multi accounts
- Ethernet WAN (EWAN) offers another broadband connectivity option for connecting to Cable, VDSL or Fiber modems
- IP based Bandwidth Control makes it easier for you to manage the bandwidth of devices that connected to the modem router
- Wi-Fi On/Off Button allows users to simply turn their wireless radio on or off
- Easy one-touch WPA wireless security encryption with the WPS button
- Easy Setup Assistant<sup>2</sup> with multi-language support provides a quick & hassle free installation
- SPI and NAT firewall protects end-user devices from potential attacks from the Internet
- Interface Grouping binds specific LAN ports to PVCs for an enjoyable IPTV<sup>3</sup> experience



#### ⦿ Description:

TP-LINK's TD-VG3631 300Mbps Wireless N VoIP ADSL2+ Modem Router is the ultimate in home or office connectivity devices offering a plethora of functionality in one robust product. The device provides users with the ability to access and share an internet connection, using a wired or 300Mbps wireless connection. With its VoIP functions, users can save on phone costs using traditional land lines or VoIP telephony services with caller ID, call waiting, call holding, call forwarding, 3-way conference calls and voice mail functionality. Additionally, using the device's 2 USB sharing ports, users can share printers, files and media across the network or around the world with ftp functions as well as add USB storage to enable voicemail functions.

<sup>1</sup> The USB Printer Setup Wizard supports Windows 7 32bit, Vista 32bit, XP 32/64bit, Windows 2003, 2000 currently. For the printer compatibility information, please visit [www.tp-link.com](http://www.tp-link.com).

<sup>2</sup> The Easy Setup Assistant utility supports Windows 2000/XP/Vista and Windows 7 operating system at present.

<sup>3</sup> IPTV applications may require subscribing to IPTV services from an ISP.


## Specifications:

HARDWARE FEATURES	
Interface	4 10/100Mbps RJ45 Ports 4 RJ11 Port 2 USB 2.0 Port
Button	1 Power On/Off Button 1 WPS Button 1 Wi-Fi On/Off Button 1 RESET Button
External Power Supply	12VDC/1.5A
Dimensions (Wx Dx H)	256x 177x 51 mm (10.1x 7.0x 2.0 in.)
IEEE Standards	IEEE 802.3, 802.3u
ADSL Standards	Full-rate ANSI T1.413 Issue 2 ITU-T G.992.1(G.DMT) ITU-T G.992.2(G.Lite) ITU-T G.994.1 (G.hs) ITU-T G.995.1
ADSL2 Standards	ITU-T G.992.3 (G.dmt.bis), ITU-T G.992.4 (G.lite.bis)
ADSL2+ Standards	ITU-T G.992.5
VoIP Standards	SIP (RFC3261), ITU-T G.729/G.722/G.711a/G.711 $\mu$
Antenna Type	Omni directional, Detachable, Reverse SMA
Antenna Gain	2 x 5dBi
WIRELESS FEATURES	
Wireless Standards	IEEE 802.11 b, 802.11g, 802.11n
Frequency	2.400-2.4835GHz
EIRP	<20dBm(EIRP)
Wireless Security	Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, Wireless MAC Filtering
SOFTWARE FEATURES	
Quality of Service	Bandwidth Control
Port Forwarding	Virtual server, DMZ, ACL(Access Control List)
VPN Pass-Through	PPTP, L2TP, IPSec Pass-through
ATM/PPP Protocols	ATM Forum UNI3.1/4.0 PPP over ATM (RFC 2364) PPP over Ethernet (RFC2516) IPoA (RFC1577/2225) PVC - Up to 8 PVCs

## Specifications:

Advanced Features	<p>Ethernet WAN (EWAN)            Parent Control            Traffic Shaping(ATM QoS) UBR, CBR, VBR-rt, VBR-nrt;            Dynamic Host Configuration Protocol (DHCP), DHCP relay;            Network Address Translation (NAT);            PVC/Ethernet Port Grouping            Static Routing, RIP v1/v2 (optional);            DNS Relay, DDNS,            IGMP snooping V1/2            IGMP Multicast,            UPnP</p>
VoIP Features	<p>Two RJ-11 FXS ports for connecting to regular telephones            One RJ-11 FXO port for PSTN Fixed-line            Call forwarding, Call waiting, Voice activity detection (VAD), 3-way conference call, etc.            USB Voicemail</p>
Security	<p>NAT Firewall,            SPI Firewall,            MAC / IP / Packet / URL Filtering</p>
USB Sharing	<p>Storage Sharing            FTP Server            Media Server            Print Server</p>
Management	<p>Web Based Configuration(HTTP),            Remote management,            Telnet management,            Command Line Interface,            SSL for TR-069,            SNMP v1/2c,            SNMP over EOC,            Web Based Firmware Upgrade,            CWMP(TR-069),            Diagnostic Tools</p>
<b>OTHERS</b>	
Certification	CE, FCC, RoHS
System Requirements	Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ or Windows 7, MAC® OS, NetWare®, UNIX® or Linux.
Environment	<p>Operating Temperature: 0°C ~40°C (32°F ~104°F)            Storage Temperature: -40°C ~70°C (-40°F ~158°F)            Operating Humidity: 10%~90% non-condensing            Storage Humidity: 5%~90% non-condensing</p>

## Diagram:



## Package:

- 300Mbps Wireless N VoIP ADSL2+ Modem Router TD-VG3631
- External Splitter
- RJ-11 Telephone Cable
- RJ-45 Ethernet Cable
- Telephony Feature Guide
- Quick Installation Guide
- Resource CD
- Power Adapter