

Fully Rugged Tablet PC**T10L****Durabook Tough Features**

Drop Resistance	26 drops of 36 inches to 2"plywood over concrete with unit off and using SSD as data storage.2 units to pass. Mil Std 810G-516.6, Procedure IV
Spill Resistance	Mil Std 810G-506.5, Procedure II.
Shock Resistance	Non-Operating SINE WAVE Vibration: 6Hz~500Hz 2.62Grms, 30mins/axis, 3axes, 30 minutes per axis Operating Random Vibration:Power Spectral Density ranges = 0.00001 to 0.01 G ² /Hz, Frequency ranges = 1 to 200Hz. Overall GRMS = 0.52. 90 minutes in all three axes, 270 minutes total. Unit is operating, and disk accessing.
IP Rating(Dust & Water Resistance)	International Standard IEC 60529, IP65

System Specifications

Processor	Intel® Pineview-M CPU N450 1.66 GHz, FSB 667MHz
System Memory	One SO-DIMM Socket for 2GB RAM Module
Storage	1.8" SATA HDD (5mm thickness)Optional SATA SSD
Display	10.4" XGA (1024x768) LED backlight TFT LCD with touch screen panel
Chipset	ICH8-M
Audio	• HD Audio • Mic. Array for VOIP • One sealed speaker nominal power: 2W
Webcam	2 mega pixels resolution webcam
I/O Ports	• DC-in with rubber plug • docking connector(contact pin type)
Wireless/Communications	One Express mini card for WLAN support CCX function (roaming) WLAN card support IEEE 802.11 b/g/n with 1x2 MIMO Internal Bluetooth module and Internal 3G module(option)
Power Supply	• AC power input:100V-240V,50Hz-60Hz, 65W, Output: 19V • Battery pack: Hot Swappable twin battery packs(total 53.28Watt)
Security	• Administrator password • TPM1.2 • Boot password • Finger Print Scanner(factory option)
Integrated options	RFID reader support ISO 14443A/B and 15693 1D/2D Barcode scanner with red ray scanning
Operating System	Microsoft Windows® XP Tablet Edition Microsoft Windows Vista® Business Microsoft Windows® 7 professional
Dimensions & Weight	260mm(W) x 263mm(D) x30~33.2mm(H) / 10.23"(W) x 10"(D) x 1.18"(H) Approximately 1.32Kg / 2.9lbs with one 3cell battery
Certification	CE,FCC,CEI,CB,FCC ID,CUS
Optional Docking Station	Host slot x1, USB 2.0 x 4, Power cord connector x 1, Battery charging bay x 2 RJ-45 jack for 10/100M Ethernet LAN x 1



- The specification and pictures are subject to change without notice.
- All brand names are registered trademarks of their respective owners.
- Battery life may vary based on setting and usage.

DURABOOK

GAMMATECH COMPUTER CORPORATION
 Email: sales@gammatechusa.com
 Tel : 1-510-492-0828
<http://www.gammatechusa.com>