

Data Sheet

HDMI and DVI/VGA Dual-Monitor Docking Station for Laptops - USB 3.0

Product ID: USB3SDOCKHDV



The USB3SDOCKHDV Dual Video Universal USB 3.0 Laptop Docking Station with Audio and Ethernet lets you add dual HD video outputs, as well as audio and Gigabit Ethernet connections to any notebook or Ultrabook[™] computer through a single USB 3.0 connection.

This versatile USB 3.0 docking station features three external monitor outputs (HDMI, DVI-D and VGA) that can be used in either HDMI and DVI-D, or HDMI and VGA combinations to expand or mirror your desktop. Each video output supports HD video resolutions (2048x1152 max) and HD video playback for an ideal solution to expanding your notebook's video capability.

An all-in-one mobile solution, the universal docking station combines a USB 3.0 hub (backward compatible with USB 2.0/1.1), Gigabit Ethernet RJ45 and headphone and microphone audio connectors into a single universal port replicator, perfect for enhancing laptop connectivity.

With a range of convenient connections, the dock is ideal for hoteling in shared workspaces, and for hot desks.

www.startech.com 1 800 265 1844



Data Sheet

Plus, unlike some proprietary docking stations designed only to work with specific laptop models, this universal laptop dock works with multiple brands. All you need is your laptop's USB 3.0 port and you can be up and running quickly. With universal support, you can use this dock with different laptops now, or in the future.

Backed by a StarTech.com 3-year warranty and free lifetime technical support.

www.startech.com 1 800 265 1844



Data Sheet

Certifications, Reports and Compatibility





⊂ F©

Applications

- Ideal for hoteling in shared workspaces, or for short-term hot desk applications
- Turn a laptop into a multi-monitor workstation (up to 3 screens total) for increased productivity
- Add dual video outputs to a laptop or small form factor computer, where the video card cannot be replaced
- Connect a wide variety of peripherals at home/office to a laptop all from a single USB connection

Features

- Connect dual displays using either HDMI + DVI-D, or HDMI + VGA combinations
- 10/100/1000 Mbps compatible RJ45 Ethernet port
- Speaker and Microphone support via 3.5mm stereo mini-jacks
- Supports HD resolutions on both connected displays
- Adds 3 USB 3.0 ports
- Universal compatibility, works with virtually all USB 3.0 equipped laptop brands
- Fully compliant with USB 3.0 specifications, with support for transfer rates up to 5 Gbps
- Supports the Windows® Aero® interface
- Kensington Security Slot

www.startech.com 1 800 265 1844



Hard-to-find made easy*

Data Sheet

	Warranty	3 Years
Hardware	4K Support	No
	Bus Type	USB 3.0
	Chipset ID	DisplayLink - DL-3900 Genesys - GL3520 Realtek - RTL8211E
	Displays Supported	2
	Fast-Charge Port(s)	No
	Industry Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, USB 3.0
Performance	Audio Specifications	The HDMI port supports audio output
	Auto MDIX	Yes
	Compatible Networks	10/100/1000 Mbps
	Full Duplex Support	Yes
	Maximum Analog Resolutions	2048x1152 (VGA)
	Maximum Data Transfer Rate	5 Gbps (USB 3.0) 2 Gbps (Ethernet; Full-Duplex)
	Maximum Digital Resolutions	1920x1200 (DVI-D) 1920x1080 (HDMI)
	Type and Rate	USB 3.0 - 5 Gbit/s
Connector(s)	Connector Type(s)	1 - DVI-D (25 pin) Female
		1 - HDMI (19 pin) Female
		1 - RJ-45 Female
		1 - USB Type-B (9 pin) USB 3.0 Female
		1 - VGA (15 pin, High Density D-Sub) Female
		2 - 3.5 mm Mini-Jack (3 Position) Female
		3 - USB Type-A (9 pin) USB 3.0 Female
Software	OS Compatibility	Windows® XP SP3 (32-bit), Vista, 7, 8, 8.1, 10 Mac OS® 10.6 to 10.12
Special Notes / Requirements	System and Cable Requirements	Available AC electrical outlet
		HDMI (and either DVI-D or VGA if dual display is desired) enabled display device(s) e.g. monitor, projector, HTDV, etc. with cables
		USB 3.0 enabled computer system with available USB 3.0 port

www.startech.com 1 800 265 1844

StarTechcom

Hard-to-find made easy*

Data Sheet

Power	Center Tip Polarity	Positive
	Input Current	0.9 A
	Input Voltage	100 ~ 240 AC
	Output Current	4 A
	Output Voltage	5 DC
	Plug Type	В
	Power Consumption (In Watts)	20
	Power Source	AC Adapter Included
Environmental	Humidity	0~90% RH
	Operating Temperature	0°C to 40°C (32°F to 104°F)
	Storage Temperature	-10°C to 60°C (14°F to 140°F)
Physical Characteristics	Cable Length	3 ft [0.9 m]
	Color	Black
	Enclosure Type	Plastic
	Product Height	1.7 in [44 mm]
	Product Length	12 in [304 mm]
	Product Weight	10.2 oz [289 g]
	Product Width	7 in [178 mm]
Packaging Information	Shipping (Package) Weight	26.8 oz [760 g]
What's in the Box	Included in Package	1 - Docking Station
		1 - 0.9m USB 3.0 Cable
		1 - Universal Power Adapter (NA/EU/UK/AU)
		1 - Installation CD
		1 - Instruction Manual

Product appearance and specifications are subject to change without notice.

www.startech.com 1 800 265 1844