



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: BP72V18-2US

BP72V18-2US - 72V External 2U Rack / Tower Battery Pack for select UPS Systems

Highlights

- Extends the runtime of select Tripp Lite Rackmount and tower UPS systems with 72VDC external battery connector
- Daisychain connector supports the addition of multiple BP72V18-2US external battery packs



Description

BP72V18-2US rack / tower external battery pack offers extended battery runtime when used in conjunction with compatible 72V Tripp Lite Rack and Tower UPS systems. Supports 2U installation in 19 inch 4 post racks with included accessories. Optional 2POSTRMKITWM enables 2 post rackmount installation. Optional 2-9USTAND accessory enables tower placement. Supports the connection of multiple BP72V18-2US external battery packs with built-in daisychain connector. Includes heavy gauge cabling with high current DC connector for simple installation in rackmount and tower configurations. Compatible with these UPS Systems - SMART3000RMOD2U, SU3000RTLX2U, SU3000RTLX3U, SU3000RTLX3UHV, SU3000RTLXCD2U, SU3000RTLXCD3U, SU3000RTXR3U, SU3000RTXR3UHW, SU3000XL, SU3000XLCD, SUINT3000RTLX2U, SUINT3000RTLX3U and other Tripp Lite UPS systems that specify the use of this battery pack.

Applications

- Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems

Package Includes

- BP72V18-2US external battery pack
- 4 post rack mounting hardware
- Warranty information
- Instruction manual

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports 4 post rackmount installation using only 2 rack spaces (2U) with included accessories
- Supports 2 post rackmount installation with optional 2POSTRMKITWM accessory
- Supports upright tower installation with optional 2-9USTAND accessory
- Supports multi-battery pack installation via built-in daisychain connector
- Includes heavy gauge cabling with high current DC connectors for simple installation

Specifications

| BATTERY | |
|--------------------------|--|
| DC system voltage (VDC) | 72 |
| Connects to UPS via | Attached cable with black 3-point DC connector |
| Typical battery lifespan | 4-6 years typical (North America) |

| PHYSICAL | |
|---|--|
| Shipping Dimensions (HWD/in) | 9.3 x 26.4 x 29.3 |
| Shipping Dimensions (HWD/cm) | 23.6 x 67.1 x 74.4 |
| Shipping weight (lbs) | 134.4 |
| Shipping weight (kg) | 61 |
| Unit Dimensions (HWD/in) | 3.4 x 17.3 x 20.8 |
| Unit Dimensions (HWD/cm) | 8.6 x 44 x 52.8 |
| Unit weight (lbs) | 88.2 |
| Unit weight (kg) | 40 |
| Material of construction | Steel |
| Form factors supported | Ships with 4 post rackmount installation accessories; Use 2-9USTAND accessory for upright tower placement option |
| WARRANTY | |
| Product Warranty Period (U.S. & Canada) | 2-year limited warranty |
| Product Warranty Period (International) | 1-year limited warranty |
| Product Warranty Period (Mexico) | 1-year limited warranty |
| Product Warranty Period (Puerto Rico) | 1-year limited warranty |
| Optional Coverage | 3 year, 5 year, next day and on-site warranty coverage available |

Related Items

Optional Products

| Related Model | Description | Qty. |
|------------------------------|--|------|
| WEXT3-BP72V | 3-Year Extended Warranty - For All 72V Battery Packs | 1 |
| WEXT5-BP72V | 5-Year Extended Warranty - For All 72V Battery Packs | 1 |
| 2POSTRMKITWM | Enables 2-Post Rackmount or Wallmount Installation of Select Rackmount UPS Systems | 1 |
| 2-9USTAND | Enables Tower Placement of Rackmount UPS Systems | 1 |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=5638.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.