



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: BP24V36-2US

### BP24V36-2US - 24V External 2U Rackmount Battery Pack for select UPS Systems

#### Highlights

- Extends the runtime of select Tripp Lite Rackmount UPS systems with 24VDC external battery connector
- Daisychain connector supports the addition of multiple BP24V36-2US external battery packs



#### Description

BP24V36-2US rackmount external battery pack offers extended battery runtime when used in conjunction with compatible 24V Tripp Lite Rackmount UPS systems. Supports 2U installation in 19 inch 4 post racks with included accessories. Optional 2POSTRMKITWM enables 2 post rackmount installation. Supports the connection of multiple BP24V36-2US external battery packs with built-in daisychain connector. Includes heavy gauge cabling with high current DC connector for simple installation in horizontal rackmount configuration only. Compatible with these UPS Systems - SMART750RMXL2U, SU1000RTXL2UA, SU1000RTXLCD2U, SU750RTXL2U, SU750RTXLCD2U, SUIINT1000RTXL2UA and other Tripp Lite UPS systems that specify the use of this battery pack.

#### Applications

- Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems

#### Package Includes

- BP24V36-2US external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

#### Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports 4 post rackmount installation using only 2 rack spaces (2U) with included accessories
- Supports 2 post rackmount installation with optional 2POSTRMKITWM accessory
- Supports multi-battery pack installation via built-in daisychain connector
- Includes heavy gauge cabling with high current DC connectors for simple installation

#### Specifications

BATTERY	
DC system voltage (VDC)	24
Connects to UPS via	Attached cable with red/black 75 amp DC connector
Typical battery lifespan	4-6 years typical (North America)
PHYSICAL	

Shipping Dimensions (HWD/in)	8.9 x 23.6 x 22.4
Shipping Dimensions (HWD/cm)	22.6 x 59.9 x 56.9
Shipping weight (lbs)	71.1
Shipping weight (kg)	32.3
Unit Dimensions (HWD/in)	3.4 x 17.3 x 14
Unit Dimensions (HWD/cm)	8.6 x 7.9 x 35.6
Unit weight (lbs)	59.4
Unit weight (kg)	27
Material of construction	Steel
Form factors supported	Rackmount
<b>WARRANTY</b>	
Product Warranty Period (U.S. & Canada)	2-year limited warranty
Product Warranty Period (International)	1-year limited warranty
Product Warranty Period (Mexico)	1-year limited warranty
Product Warranty Period (Puerto Rico)	1-year limited warranty
Optional Coverage	3 year, 5 year, next day and on-site warranty coverage available

## Related Items

### Optional Products

Related Model	Description	Qty.
<a href="#">WEXT3-BP24V</a>	3-Year Extended Warranty - For All 24V Battery Packs	1
<a href="#">WEXT5-BP24V</a>	5-Year Extended Warranty - For All 24V Battery Packs	1
<a href="#">2POSTRMKITWM</a>	Enables 2-Post Rackmount or Wallmount Installation of Select Rackmount UPS Systems	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=5629](http://www.tripplite.com/en/products/model.cfm?txtModelID=5629).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.