



---

## Highlights

- Outstanding performance for virtualization with maximum memory capacity and CPU performance
- Improve service with unparalleled RAS features and innovative management
- Manage growth and reduce risk on a BladeCenter® platform with proven stability



# IBM BladeCenter HS22V

*High-performance blade server optimized for virtualization and energy efficiency*

## Optimized for virtualization

The IBM BladeCenter HS22V has been designed specifically for use in virtualized environments. With 18 DIMM slots supporting up to 288 GB of DDR3 memory, the HS22V allows you to fit more and larger virtual machines per blade. Durable solid-state drives and hardware RAID-0 and -1 provide outstanding reliability when virtualizing multiple workloads on a single blade. An embedded hypervisor enables easy deployment of industry-leading third-party virtualization solutions. Combine the HS22V with Virtual Fabric for IBM BladeCenter for a flexible, easy, fast and reliable I/O solution that helps reduce cost and complexity.

## Built for performance

The HS22V provides outstanding performance with support for the latest Intel® Xeon® processors, support for maximum memory capacity, fast memory throughput and high-speed I/O.

## Designed for energy efficiency

The HS22V offers a flexible, energy-smart design. The HS22V supports up to two 1.8" solid-state drives that consume significantly less power than traditional spinning hard disk drives. New enhanced power management capabilities assist in power planning for the data center while IBM Systems Director Active Energy Manager™ provides tracking, monitoring and measuring of energy usage.

Select configurations of the HS22V are part of the IBM Express Advantage® Portfolio designed to meet the needs of midsized businesses. Easy to manage, Express® models and configurations vary by country.





© Copyright IBM Corporation 2010

IBM Systems and Technology Group  
Route 100  
Somers, New York 10589

Produced in the United States of America  
October 2010  
All Rights Reserved

IBM, the IBM logo, [ibm.com](http://ibm.com) and BladeCenter are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both. If these and other IBM trademarked terms are marked on their first occurrence in this information with a trademark symbol (® or ™), these symbols indicate U.S. registered or common law trademarks owned by IBM at the time this information was published. Such trademarks may also be registered or common law trademarks in other countries. A current list of IBM trademarks is available on the web at “Copyright and trademark information” at [ibm.com/legal/copytrade.shtml](http://ibm.com/legal/copytrade.shtml)

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft and Windows are trademarks of Microsoft Corporation in the United States, other countries, or both.

Other product, company or service names may be trademarks or service marks of others.



Please Recycle

## IBM BladeCenter HS22V at a glance

<b>Form factor/height</b>	Single-wide (30 mm)
<b>Processor</b> (max)	Choice of two Intel Xeon 5500 or 5600 series processors, supports advanced, standard, basic and low voltage
<b>Number of processors</b> (std/max)	1/2
<b>Cache</b> (max)	At least 4 MB L3 cache (12 MB max)
<b>Memory</b> (max)	18 DDR-3 VLP DIMM slots (up to 288 GB of total memory capacity and memory speeds up to 1333 MHz) with memory sparing
<b>Expansion slots</b>	1 CIOv slot (standard PCIe daughter card) and 1 CFFh slot (high-speed PCIe daughter card) for a total of 8 ports of I/O to each blade, including 4 ports of high-speed I/O or 8 ports of virtual I/O using Virtual Fabric for IBM BladeCenter
<b>Disk bays</b> (total/hot-swap)	Up to two 1.8" solid-state drives (fixed)
<b>Maximum internal storage</b>	Up to 100 GB
<b>Network interface</b>	Virtual Fabric Adapter ships integrated in some models Broadcom 5709S onboard NIC with dual Gigabit Ethernet ports with TOE
<b>RAID support</b>	RAID-0, -1 and -1E (optional RAID-5 with battery-backed cache)
<b>Systems management</b>	Unified Extensible Firmware Interface (UEFI), IBM Integrated Management Module, Predictive Failure Analysis, optional embedded hypervisor for virtualization, IBM Systems Director Active Energy Manager, light path diagnostics, IBM Systems Director and IBM ServerGuide
<b>Operating systems supported</b>	Microsoft® Windows®, Red Hat Enterprise Linux®, SUSE Linux Enterprise, VMware, Oracle Solaris
<b>Limited warranty</b>	3-year customer replaceable unit and on-site limited warranty

## For more information

### World Wide Web

U.S. [ibm.com/bladecenter](http://ibm.com/bladecenter)

Canada [ibm.com/systems/can/en/servers/bladecenter](http://ibm.com/systems/can/en/servers/bladecenter)