



Pan/Tilt Network Camera PT8133/33W



1MP • PoE (PT8133)
802.11n • WPS (PT8133W)

VIVOTEK PT8133 (PoE)/ 33W (WLAN) are equipped with a 1MP sensor enabling viewing resolution of 1280x800 at 30 fps. Users need look no further for an all-in-one camera capable of capturing high quality, high resolution video. The camera is designed for indoor surveillance applications such as retail stores, offices, or homes.

With flexible 350-degree pan and 125-degree tilt, PT8133/33W gives users more comprehensive control over a monitored site. The PT8133/33W supports the industry-standard H.264 compression technology, drastically reducing file sizes and conserving valuable network bandwidth. With MPEG-4 and MJPEG compatibility also included, video streams can also be transmitted in any of these formats for versatile applications. The streams can also be individually configured to meet different constraints, thereby further reducing bandwidth and storage requirements. Users can thus receive multiple streams simultaneously in different resolutions, frame rates, and image qualities for viewing on different platforms.


In addition, PT8133 is integrated with Power over Ethernet functionality, while PT8133W boasts 802.11b/g/n compatible wireless connection, making installation easier and more cost-efficient. The WPS function of PT8133W makes wireless configuration easy and straightforward. Together with the bundled, multi-lingual 32-channel recording software ST7501, users can set up an easy-to-use IP surveillance system with ease.

Features


- 1-Megapixel CMOS Sensor
- 30 fps @ 1280x800
- Real-time H.264, MPEG-4 and MJPEG Compression (Triple Codec)
- Built-in 802.3af Compliant PoE (PT8133)
- Built-in 802.11b/g/n WLAN (PT8133W)
- Wi-Fi Protected Setup (WPS) for Easy and Secure Wireless Network Connection (PT8133W)



Technical Specifications

Models	PT8133 (PoE) PT8133W (Wireless)	Intelligent Video	Video Motion Detection	Triple-window video motion detection
System Information		Alarm and Event	Alarm Triggers	Video motion detection, manual trigger, periodical trigger, system boot, recording notification
CPU	Multimedia SoC (System-on-Chip)	Alarm Events	Alarm Events	Event notification using HTTP, SMTP, FTP and NAS server File upload via HTTP, SMTP, FTP and NAS server
Flash	128 MB	General	Connectors	RJ-45 for Network/PoE connection DC-Jack for DC 12V power input
RAM	128 MB	LED Indicator	LED Indicator	System power and status indicator WPS indicator (PT8133W)
Camera Features		Power Input	Power Input	12V DC IEEE 802.3af PoE Class 2 (PT8133)
Image Sensor	1/4" Progressive CMOS	Power Consumption	Power Consumption	Max. 5.52W (PoE) Max. 5.1W (Wireless)
Maximum Resolution	1280x800	Dimensions	Dimensions	Ø 110 mm x 120 mm
Lens Type	Fixed-focal	Weight	Weight	Net: 293 g
Focal Length	f = 3.6 mm	Safety Certifications	Safety Certifications	CE, LVD, FCC Class B, VCCI, C-Tick
Aperture	F1.8	Operating Temperature	Operating Temperature	0°C ~ 50°C (32°F ~ 122°F)
Field of View	58.39° (horizontal) 35.58° (vertical) 69.34° (diagonal)	Warranty	Warranty	24 months
Shutter Time	1/5 sec. to 1/32,000 sec.	System Requirements	Operating System	Microsoft Windows 7/Vista/XP/2000
Minimum Illumination	0.3 Lux @ F1.8, 50 IRE	Web Browser	Web Browser	Mozilla Firefox 7 ~ 10 (streaming only) Internet Explorer 7.x or 8.x
Pan Range	350° (-175° ~ +175°)	Other Players	Other Players	VLC: 1.1.11 or above QuickTime: 7 or above
Tilt Range	125° (-35° ~ +90°)	Included Accessories	CD	User's manual, quick installation guide, Installation Wizard 2, ST7501 32-channel recording software
Pan/tilt/zoom Functionalities	20 preset positions Auto pan mode Auto patrol mode	Power Adapter	Power Adapter	DC 12V, 1.5A
Video		Others	Others	Quick installation guide, warranty card, camera mounting kit Antenna (PT8133W)
Compression	H.264, MJPEG & MPEG-4	Dimensions		
Maximum Frame Rate	H.264: 30 fps at 1280x800 MPEG-4: 30 fps at 1280x800 MJPEG: 30 fps at 1280x800			
Maximum Streams	2 simultaneous streams			
S/N Ratio	Above 62dB			
Video Streaming	Adjustable resolution, quality and bitrate Configurable video cropping for bandwidth saving			
Image Settings	Adjustable image size, quality and bit rate Time stamp, text overlay, flip & mirror Configurable brightness, contrast, saturation, sharpness, white balance, exposure control, gain, backlight compensation, privacy masks Scheduled profile settings			
Audio				
Audio Capability	Audio input			
Compression	GSM-AMR, G.711			
Interface	Internal microphone			
Effective Range	5 meters			
Network				
Users	Live viewing for up to 10 clients			
Protocols	IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, UDP, RTSP/RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, PPPoE, CoS, QoS, SNMP, 802.1X			
Interface	10Base-T/100 Base-TX Ethernet (RJ-45)			
ONVIF	Ver. 1.02			

Compatible Accessories

Enclosures	Wireless
 <p>AE-132 Outdoor dome housing with smoked cover (PT8133)</p>	 <p>N600AG Outdoor wireless access point</p>
 <p>AE-131 Outdoor dome housing with transparent cover (PT8133)</p>	 <p>N500AG Outdoor wireless access point</p>
Mounting Kits	
 <p>AM2000 Wall mount kit</p>	
PoE Kits	
 <p>MS-POE-IJAF PoE Injector, 802.3af Compliant (PT8133)</p>	

All specifications are subject to change without notice. Copyright © 2012 VIVOTEK INC. All rights reserved. P/N: 971006000

Distributed by:



VIVOTEK INC.
6F, No.192, Lien-Cheng Rd., Chung-Ho, New Taipei City, 235, Taiwan, R.O.C.
|T: +886-2-82455282 | F: +886-2-82455532 | E: sales@vivotek.com

VIVOTEK USA, INC.
2050 Ringwood Avenue, San Jose, CA 95131
|T: 408-773-8686 | F: 408-773-8298 | E: salesusa@vivotek.com

Ver 1.1