

SECURITY CAMERA



A SUPER RESOLUTION PERSPECTIVE









VIEW YOUR WORLD -

IN SUPER RESOLUTION.

- ▼ CLEAR-NIGHT TECHNOLOGY
- ▼ VANDAL RESISTANT
- **▼ FLEXIBLE INSTALLATION**

PROFESSIONAL-GRADE

For high performance video with Super Resolution (600 TVL) detail

WATCH DAY OR NIGHT

Digital Noise Reduction improves night vision clarity and recording efficiency

VERSATILE DESIGN

Install indoors or outdoors, on walls or ceilings

FEATURES

- Advanced Sony Super HAD™ II image sensor
- Video image processor delivers 600TV lines of resolution
- · Night Vision up to 50ft (15m) away in total darkness1
- ClearNight imaging technology ensures clear night vision and improves recording efficiency up to 30%
- 3.6mm wide angle lens for wide area coverage (80° FOV)2
- IP66 rated aluminum housing for indoor / outdoor installations3









SECURITY CAMERA

PRODUCT INFORMATION

LDC6051	7-78597-60510-5
Package Weight:	1.05 kg / 2.3 lbs
Package Dimensions: (W x D x H)	216mm/8.5" (w) x 172mm/6.7" (d) x 140.5mm/4.1 (h)
Package Cube:	0.13 Cbf / 0.003681 Cbm
Contents:	1x Camera, 1x 60ft BNC / Power extension cable 1x BNC female / RCA male adapter 1x 12V DC power adapter

DISCLAIMERS

- IR illumination range under ideal conditions. Objects at or beyond this range may be partially or completely obscured, depending on the camera application.
- 2. Field of view, diagonal.
- Not intended for submersion in water. Installation in a sheltered location recommended.

SPECIFICATIONS

Image Sensor: 1/3" Sony Super HAD™ II

Video Format: NTSC

Effective Pixels: H: 768 V: 494
Resolution: 600 TV Lines
Scan System: 2:1 Interlace
Sync System: Internal

S / N Ratio: 50dB (AGC Off)

Iris: AES

AES Shutter Speed: 1/60 ~ 1/100,000 sec.

Min. Illumination: 0.2 Lux without IR LED

O Lux with IR LED

Video Output: Composite 1.0Vpp @ 75ohm

Lens / Lens Type: 3.6mm F2.0 / Fixed

FOV (Diagonal): 80°
Termination: BNC Type

IR LED Qty / Type: 14 pieces / 850nm


Night Vision Range: 50ft. / 15m Power Requirement: 12V DC \pm 10% Power Consumption Max.: 250mA (w / IR)

Operating Temp. Range: $14^{\circ} \sim 122^{\circ}F / -10^{\circ} \sim 50^{\circ}C$

Operating Humidity Range: < 90% RH Environmental Rating: IP66

Weight (including stand): 0.8lbs. / 0.4kg

INSTALLATION DIAGRAM





www.lorextechnology.com

Lorex Technology Inc.