

# **VIDEO BABY MONITOR**

# THE WIRELESS WAY TO STAY AWARE

- 3.5" LCD color monitor
- Record video to SD card
- Remote viewing
- Two-way talk
- Completely portable



# **RECORD VIDEO AND AUDIO.**

Capture your child's precious moments with manual or sound-activated recording.

# VIEW REMOTELY.

Connect the monitor to a computer to view from anywhere in the world using Skype™\*

# **KEEP BABY HAPPY & COMFORTABLE.**

Soothe and comfort your baby with built-in lullabies, intercom, room-temperature monitor, and feeding timer.

## SLEEP EASY.

Monitor while you sleep with audio monitor, indicator lights, and sound-activated recording.

## PRIVATE AND SECURE.

Monitor with confidence knowing the digital signal is secure, private, and can't be picked up by neighbors.





# **VIDEO BABY MONITOR**

### FEATURES

- Sound activated video to SD card recording
- Compact, rechargeable video monitor
- View remotely via Skype™
- Talk with Baby intercom
- Temperature monitoring with alarm
- Sooth Baby with built-in lullabies
- See Baby at all times with automatic night vision
- Secure, interference free, long range digital signal
- High contrast 3.5" color LCD monitor
- Grows with your family (expandable up to 4 cameras)

## REMOTE VIEWING



FEEDING TIMER



See what's happening while you are away. View video from the handheld monitor from anywhere in the world using Skype.

Keep track of feedings with a built-in timer.

### REMOTE LULLABIES



Featuring built-in lullabies, the LIVE SD3.5 can help soothe your baby. Select a lullaby and watch your baby fall asleep.

### TEMPERATURE MONITORING

The LIVE SD3.5 includes an electronic temperature sensor so you can monitor the climate in the baby's room. A built-in alarm will even warn you if



the temperature changes outside of your selected range.



## CAPTURE, STORE AND SHARE



Instantly capture those special events in your child's life with one-touch video recording or set it to record upon hearing your baby. Playback videos on the handheld monitor, or transfer them easily to a PC or Mac<sup>4</sup> and share them on sites such as Facebook<sup>™</sup> and Youtube<sup>™</sup>.

1. Battery life : Up to 4 hr

- Up to 450ft / 150m reception line of sight. Actual range will vary depending on obstructions.
   Additional cameras sold separately.
- Additional cameras sold separately.
   microSD card reader not included.



# **VIDEO BABY MONITOR**

#### TALK WITH BABY



Two-way audio between the camera and monitor means you can talk to baby, even if you are not in the same room.

#### GROWS WITH YOUR FAMILY



Add up to 3 additional cameras. As your family grows, the LIVE Capture can expand right along with you. Have a camera in the baby's room, play room, living room, or even pointing at the front door.

#### AUDIO MONITOR



Conserve battery life and sleep peacefully by using it as an audio monitor. With the LCD monitor turned off, you can continue to hear your baby while eliminating distractions for a peaceful sleep.

#### VIEW DAY OR NIGHT MULTIPLE VIEWING OPTIONS



Keep an eye on baby all night long with crystal clear automatic night vision. Check on little ones without the risk of waking them up.

MONITOR DOCKING CRADLE



Viewing modes include Single Channel, Scan (switch between single channels automatically), and Quad Split-Screen.

#### PRIVATE AND SECURE



Digital signal with FHSS technology ensures a private and secure transmission between the camera and handheld monitor.



No more plugging and unplugging of power cables so you can quickly get going. Simply slide the monitor into the docking cradle and remove it when it's fully charged.

### **AUDIO INDICATOR LIGHTS**



Audio indicator lights on the monitor indicate the level of noise being picked up by the camera. This extra pair of ears helps you be aware of what your baby is up to when you are in a noisy room.






# **IDEO BABY MONITOR**



#### MEASUREMENTS





## **SPECIFICATIONS**

#### GENERAL

Transmission Frequency: Transmission Power: Unobstructed Effective Range: Spread Spectrum: Modulation Mode: Operating Tempurature:

ISM 2,400~2,483.5 MHz 14dBm 150ft/46m indoor / 450ft/138m outdoor, line of sight FHSS GFSK 14 ~ 122° Fahrenheit / - 10 ~ +50° Celsius) <85%

#### Operating Humidity: CAMERA

Image Sensor: Lens: Total Picture Pixels: Minimum Illumination: Night Vision Distance: View Angle: Power Consumption (Max.): Power Supply: Dimensions ( $W \times D \times H$ ): Weight:

CMOS 4.9mm F2.8 656 x 488pxl (NTSC) O Lux (IR on) 15 FT (5m) Diagonal 31° Max 450mA 5V DC 84mm x 67mm x 158mm / 3.3" x 2.6" x 6" 0.3 lbs / 0.14 kg

## PRODUCT INFORMATION

#### MONITOR

3.5"
320 x 240
-81dBm
550mA
5V DC
126mm x 22mm x 76mm / 5" x 0.9" x 3"
0.35lbs / 0.6kg

67mm/

2.6

#### CONNECTIVITY & COMPATIBILITY

#### iPhone<sup>™</sup>, iPad<sup>™</sup>, iPod touch<sup>™</sup> Requirements:

- Skype for iPhone 3.0 and above
- Skype for iPad 3.5 and above • iPhone 4S/4/3GS, iPad (1st generation and above), iPod touch (3rd generation and above) iOS 4.0 and above
- **PC Requirements:**
- Skype for Windows<sup>™</sup> version 4.2 and above
  Windows 7/Vista/XP SP2
- 1 Ghz processor or better

#### **Mac Requirements:**

- Skype for Mac OS v. 5.3 and above
  Mac OS v. 10.5.8 and above
- 1 GHz or higher Intel processor
   PowerPC<sup>™</sup> not supported
- For the latest device compatibility list, visit www.lorextechnology.com

MODEL	CONFIGURATION	PACKAGE	W x D x H	WEIGHT	CUBE	UPC Code	
LW2401	NA version	Retail	299 x 80 x 236mm /	1 kg / 2.3lbs	0.0056 CBM x 0.199 CBF	7-78597-24010-8	
			11.8 x 3.2 x 9.3″				
Includes:	Wireless camera, 3.5" LCD monitor, Monitor charging cradle, 2 x Power adapters, 1GB microSD memory card, USB cable, CD						
MODEL	CONFIGURATION	PACKAGE	WxDxH	WEIGHT	CUBE	UPC Code	
LW2401P	UK version	Retail	299 x 80 x 236mm / 11.8 x 3.2 x 9.3″	1kg / 2.3lbs	0.0056 CBM x 0.199 CBF	7-78597-24012-2	
Includes:	Wireless camera, 3.5" LC	D monitor, Moni	tor charging cradle, 2 x Powe	er adapters, 1GB micro	SD memory card, USB cable	e, CD	
MODEL	CONFIGURATION	PACKAGE	WxDxH	WEIGHT	CUBE	UPC Code	
LW2401AC1	Accessory camera	white box	233 x 91 x 74mm / 9.2 x 3.6 x 2.9″	0.3kg / 0.7lbs	0.0016 CBM x 0.554 CBF	7-78597-24011-5	
Includes:	Wireless camera, Power adapter						
MODEL	CONFIGURATION	PACKAGE	WxDxH	WEIGHT	CUBE	UPC Code	
ACC241BAT	T Rechargeable battery kit	white box	77 x 59 x 25mm / 3 x 2.3 x 1″	0.1kg / 0.3lbs	0.0002 CBM x 0.004 CBF	7-78597-24102-0	
Includes:	Rechargeable battery			·	·		
MODEL	CONFIGURATION	PACKAGE	WxDxH	WEIGHT	CUBE	UPC Code	
ACC241CRD	L Handheld monitor docking cradle	white box	130 x 100 x 44mm / 5.1 x 3.9 x 1.7″	0.15kg / 0.33lbs	0.0006 CBM x 0.02 CBF	7-78597-24104-4	
Includes:	Docking cradle						



250 Royal Crest Court Markham, Ontario L3R 3S1 Canada

3700 Koppers Street Baltimore, Maryland 21227 USA

#### www.lorextechnology.com

©2011 Lorex Technology Inc.

As our product is subject to continuous improvement, Lorex Technology & subsidiaries reserve the right to modify product design, specifications & prices without notice and without incurring any obligation. E&OE