

#### Notice:

©2012 EverFocus Electronics Corp. All rights reserved.

EverFocus® Paragon<sup>™</sup> NeVio<sup>™</sup> and Polestar<sup>™</sup> are registered trademarks of EverFocus Electronics Corp. Product features and specifications are subject to change without notice. No parts or contents of this catalog may be reproduced or transmitted in any form or by any means without permission from EverFocus.

- Not all models featured are available in all countries. For accessories and other product information, please visit www.everfocus.com and select your country.
- Safety Precaution: Please read all operating instructions and installation manuals carefully before using all products. EverFocus is not responsible for network performance and/or other manufacturers' products(s) that reside on the network.
- · All product weights and dimensions are approximate
- · All products may be subject to export control regulations.
- · All product photographs were taken for explanation purposes. Actual images may differ
- This catalog is design in the USA and printed in Taiwan.

Safari®, iPhone®, iPad® iTunes® are registered trademarks of Apple® Inc. Android TM is a registered trademark of Google® Inc. Blackberry® is a registered trademark of RIM®

All other trademarks are property of their respective owners.



EverFocus Electronics Corp. is a leading manufacturer of CCTV cameras, DVRs, access control systems and other CCTV and access control peripherals. With offices located around the world including the U.S.A., U.K., Germany, China, India, Japan and Taiwan, EverFocus provides quality products, highly skilled technical support, project design consultation, various dealer/distributor programs, educational trainings and our new financing program to meet the demands of our customers worldwide. We believe the key component to success lies in the development and quality of our products and excellent customer service. EverFocus is system and solutions provider that is able to meet the needs of any size company.



## ENDEAVOR 264









Quality Management System ISO9001 Certifications



Quality Management Syste ISO14001 Certifications



# **HDcctv**

#### **HDcctv Cameras & DVRs**

Domes, Bullets, Box,	PTZ5-11	
DVRs		ł

# IP

IP Cameras & NVRs	
Domes, Bullet, Box, PTZ	16-26
NVRs & Encoders	27-31

# **Analog CCTV**

Color Cameras Domes, Module, Bullet, Box, PTZ, IR,
Digital Video Recorders Compact, Full Size, DVD, Hot-Swap, 4-32 Channel

# **Mobile Video Surveillance**

Mobile Cameras Domes, Bullet, License Plate Cameras, Wedge Cameras
Mobile DVRs 2-12 Channel Mobile DVRs

# Accessories

### **Accessories for All Products**

Monitors	
Monitor Mounts	
Storage Expansion, Hard Drive Readers	
Lens, Power Supplies	
PTZ Accessories	
Mounting Brackes, IR Illuminators	
Software	
Ouad	





# EHH5200 HDcctv 1080p Outdoor Vandal Dome



### **Features**


- HDcctv Megapixel real time 1920x1080 or 1280x720 HD video over coax for superlative image detail
- True day/night operation with automatic ICR module
- 3.3-12mm Megapixel A/I IR Corrected Lens
- · Easy to use OSD setup menu
- The flexible angle viewing of its 3-Axis design allows wall or ceiling mounting
- Vandal Resistant construction able to withstand intentional damage
- IP66 weather resistant rating means that it will withstand the elements in outdoor conditions
- IR distance up to 100 feet
- Surface Mount; optional L bracket available
- Supports video outputs of 1080i60/50; 1080p30/25; 720p60/50/30/25 (field select)
- S/D Analog Test TV Out for setup, aim and focus using a standard hand held test monitor
- Dual power source 12VDC/24VAC



### Specifications

opeemeations			
Part Number	EHH5200		
Pickup Device	1/2.7" 2 Megapixel CMOS sensor		
Image Area Size	1920 x 1080	Φ 6.61mm; (w x h) 5.76 x 3.24mm	
illiage Area Size	1280 x 720	Φ 4.41mm; (w x h) 3.84 x 2.16mm	
Sensitivity	0.5 lux/F=1.4; 0 lux IR ON		
True Day/Night	Yes (Auto IR cut filter removal)		
Effective Pixels		1920x1080	
S/N Ratio	45dB		
Resolution Main Output	Supports video outputs of 1080i60/50; 1080p30/25; 720p60/50/30/25 (field select)		
Video Format Test Output	NTSC/PAL selectable 1V p-p (in test mode only)		
Electronic Shutter	Auto, 1/60(1/50)~1/8000		
Lens Type	Megapixel Varifocal lens, Auto Iris, f=3.3~12mm, F=1.4		
Backlight Compensation	On/Off selectable		
Auto Gain Control	High/Middle/Low/Off selectable		
Auto White Balance	AWB/One Push WB/Manual WB/Indoor/Outdoor		
Language Support	Multi-Language		
Image Flip		H_MIR/V_MIR/Rotate	
Gamma Correction	PC/TV selectable		
OSD Menu	yes (controlled from rear 5-axis joystick control)		
Weatherproof	IP66 Weather Resistant		
Vandal Resistant	Yes		
Power Source	12VDC/24VAC		
Power Consumption	12VDC: 3.3W max, 24VAC: 5.5W max.		
Dimensions	4.8" x 4.2"		
Weight	1.6 lbs		
Operating Temperature	-10° ~ 50°C/ 14° ~ 122°F		
Certifications		FCC, CE	

#### Dimensions: mm/in



#### **Ordering Info**

EHH5200: 720/1080 Megapixel over coax Vandal Dome

