

Wireless N H.264 Megapixel Surveillance Camera

TL-SC3430N

⦿ Features:

- 1.3 megapixel progressive scan CMOS sensor produces high definition video quality
- Wireless 802.11b/g/n with WPS, up to 150Mbps
- SD card local storage and Network Attached Storage (NAS) for convenient video recording
- H.264, MPEG-4 and MJPEG video streaming for different quality requirements and bandwidth environments
- Multiple easy remote viewing options; watch live video via 3G mobile phones, laptops or tablets
- Email or FTP notifications triggered by motion detection, audio detection or scheduled timer offer sensitive invasion alerts
- 10x digital zoom for detailed close-ups
- 2-way audio allows users to listen and speak remotely
- Advanced SSL/HTTPS encryption and IP filter protect users' privacy from malicious intrusions
- Free bundled software supports simultaneous monitoring of up to 16 cameras
- Quick universal plug and play installation



⦿ Description:


Complying with the IEEE 802.11n standard, TL-SC3430N is a fantastic solution for homes, shops, banks, offices and other buildings that require flexible longer range surveillance deployment. The camera supports multiple storage options that allow video to be recorded to a local PC, SD card or NAS, enabling high capacity storage. Equipped with a high performance 1.3 Mega-Pixel sensor, it can provide HD images that are more useful with more image detail. Moreover, live video can be accessed through the Internet on a PC/laptop, or even via 3G mobile devices.

With simple installation, event alerts, 2-way audio and other practical functions, the TL-SC3430N is a perfect choice for the advanced viewer with attention to detail.

◎ Specifications:

| Wireless | |
|-----------------------------|---|
| Wireless Data Rates | IEEE 802.11 b/g/n, Up to 150Mbps |
| Wireless Encryption | Supports WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryption |
| Camera | |
| Image sensor | 1/4" Progressive scan CMOS sensor |
| Resolution | 1.3 Megapixel (1280 x 1024) |
| Lens | F1.9, f4.5 mm |
| Digital Zoom | 10x Digital |
| Minimum Illumination | 0.5 Lux at F1.9 |
| Video | |
| Video Compression Mode | H.264/MPEG-4/MJPEG |
| Frame Rate vs. Resolution | Max. 15 fps at 1280x1024 (1.3 Mega-Pixel) Max. 30 fps at 640x480 (0.3 Mega-Pixel) |
| Audio | |
| Audio Communication | 2-Way full duplex |
| Audio Input | Built-in microphone & audio sensor |
| Audio Output | External output connector |
| Audio compression | G.711 μ law, a law, and AMR |
| Alarm and Event Management | |
| Input trigger | Motion detection, audio detection, schedule and network link down |
| Output notification | SD memory card, Network Attached Storage, FTP and SMTP |
| Network | |
| Protocol | Bonjour, TCP/IP, DHCP, PPPoE, ARP, ICMP, FTP, SMTP, DNS, NTP, UPnP, RTSP, RTP, RTCP, HTTP, TCP, UDP, 3GPP/ISMA RTSP |
| Security | Multiple password-protected user levels, HTTPS encryption, IP Filter |
| Interface | |
| Network Interface | RJ-45 for Ethernet 10/100 Base-T |
| Power Connector | DC power jack |
| Audio Output | 3.5 mm jack for line out |
| Slot | SD/SDHC memory card slot |
| Button | Reset push button, WPS button |
| Interface | |
| Power | 12V DC, Max 12W |
| Bundled Management Software | Viewing and recording up to 16 cameras (For Windows use only) |
| Operating Temperature | 0 °C ~ 40 °C (32 °F ~ 104 °F) |
| Operating Humidity | 10%~90%RH, Non-condensing |
| Dimensions (H x W x D) | 3.9 x 2.5 x 1.2 in. (99 x 63 x 30mm) |

Diagram:



Package

- Wireless N H.264 Megapixel Surveillance Camera TL-SC3430N
- Power Adaptor
- RJ-45 Ethernet Cable
- Quick Installation Guide
- Resource CD
- Camera Mount Kit