

Sequence

Features

- Mica-filled poly laminate cone woofers with rubber surrounds
- Voice matched to integrate seamlessly with other Sequence speakers
- Baffle and grille fully paintable to match any décor
- Integrated C-clamp mounting system
- Powder coated metal grilles
- 6.5" Woofers through entire line
- 1/2" Titanium anodized dome tweeter
- Dual voice coil speaker utilizes dual cone technology



SPECIFICATIONS	730-101	730-102	730-103
Power Handling	5-60 watts	5-60 watts	5-80 watts
Frequency Response	58Hz to 20,000Hz	60Hz to 20,000Hz	55Hz to 20,000Hz
Impedance	8 Ohms nominal	8 Ohms nominal (per channel)	8 Ohms nominal
Efficiency	90dB	90dB	90dB
Woofer	6.5"	6.5" Dual cone	6.5"
Tweeter	1/2"		1/2"
Overall Dimensions	9" X 3" (229 mm X 76 mm)	9" X 3" (229 mm X 76 mm)	12 1/8" X 8 3/4" X 3" (308 mm X 222 mm X 76 mm)
Required Cut Out	7 1/2" Diameter (191 mm)	7 1/2" Diameter (191 mm)	10 7/8" X 7 3/8" (276 mm X 187 mm)

Rough-in Kits

6.5" Rough-in Kits Ceiling | 730-560

6.5" Rough-in Kits Wall | 730-561

8" Rough-in Kits Ceiling | 730-580

- New construction pre-drywall application

