

# VT2405LED

**24" (23.6" VIEWABLE) HDTV/PC**

**WITH RS232/IR CONTROL AND  
HOSPITALITY FEATURES**

## A brilliant solution for Hospitality and Commercial TV Applications

ViewSonic's new 23.6" VT2405LED Commercial HD TV featuring "edge white" LED technology delivers brilliant image clarity, high contrast with saturated colors while consuming very low power. Versatile connectivity is provided through 2 HDMI inputs in addition to PC and traditional YPbPr component video. A RS232 control port is combined with IR pass through providing automated control for hospitality and commercial installations. Internal programming is offered for users to control the specific operation of the TV. This includes features such as front panel lockout, volume limitation, active inputs on power up and programmable channel range. Extreme audio includes internal. SRS Surround performance with SPDIF digital output.



### PROFESSIONAL GRADE 32" HDTV




- > **23.6" Mercury-Free LED Panel Technology**  
23.6" edge-lit HD panel uses less energy while producing vivid picture clarity, rich colors, deeper blacks and brighter whites.
- > **RS232 Serial Interface with IR Pass Through**  
Easy automation of TV control and pass through of remote control functions
- > **Hospitality Set-up menu**  
Enable/disable inputs and menus, define channel range, defaults volume level control
- > **USB Cloning**  
Easy duplication of hospitality set-up calibration using USB drive.
- > **Advanced Image Processing Delivers Professional Image Quality**  
Advanced motion adaptive video processor provides crisp video performance
- > **OptiSync® Technology Provides Extreme Connectivity**  
3X HDMI inputs, PC, YPbPr, S and A/V video, and USB for viewing JPEG images, ATSC / QAM TV tuner.
- > **Multimedia ready**  
5W SRS TruSurround HD audio, SPDIF Digital audio output, Dolby Digital
- > **Low Power Consumption**
- > **3 year Warranty**



**ViewSonic®**  
See the difference® 

# VT2405LED

24" (23.6" VIEWABLE) HDTV/PC WITH RS232/IR CONTROL AND HOSPITALITY FEATURES



<b>LCD</b>	Type	24" (23.6" viewable) Wide Color TFT Active Matrix LCD
	Display Area	20.5" horizontal x 11.5" vertical; 23.847" diagonal
	Optimum Resolution	1920x1080
	Contrast Ratio	1000:1 static (typ)
	Viewing Angles	176° horizontal, 160° vertical
	Response Time	5ms
	Light Source	Long life, 30,000 hrs. (typ)
	Brightness	300 cd/m <sup>2</sup> (typ)
	Aspect Ratio	16:9
	Glass Surface	Anti-glare, anti-reflective coat
<b>INPUT</b>	PC	RGB analog (75 ohms, 0.7 Vp-p)
	TV	TV/cable, composite (RCA), component YPbPr/YCbCr, USB, S-Video
	Audio	3.5mm mini stereo audio in, earphone out and RCA (left/right) audio in
	Frequency	F <sub>H</sub> : 30~64kHz, F <sub>V</sub> : 60~75Hz
<b>AUDIO OUTPUT</b>	Speakers	2x2.5-watt
	Remote Control	Type: RCU infrared Range: Up to 23ft (7m)
<b>COMPATIBILITY</b>	PC	1920x1080 @ 60Hz (preferred)
	Mac®*	G3/G4/G5 up to 1920x1080
<b>INPUT SIGNAL</b>	TV/Video Comp.	480i, 480p, 720p, 1080i, 1080p
<b>CONNECTOR</b>	Analog	15-pin mini D-sub (VGA)
	Digital	HDMIx2, USB (Side) (JPEG)
	Power	3-pin AC plug
<b>POWER</b>	Voltage	AC 100~240V (universal), +/-10% Wide Range
	Consumption	28W (Normal) 38W (max)
<b>CONTROLS</b>	Basic	Vol +/-, menu, channel down/up, source, power
	Picture	Contrast, brightness, sharpness, tint, color, color mode, zoom mode, noise reduction, DCR
	TV	TV/CATV, Auto scan, favorites, sleep mode
	Set Up	OSD timeout, OSD language
	Audio	Treble, bass, balance, SPDIF, surround sound, MTS
	Hospitality	Enable/disable inputs and menus, define channel range, defaults volume level control
	Temperature	32~104°F (0~40°C)
	Humidity	20~80% (non-condensing)
	Physical with stand	22.1" x 16.2" x 8.5" (563mm x 411mm x 215mm)
	Physical without stand	22.1" x 14" x 1.53" (563mm x 355mm x 39mm)
<b>WEIGHT</b>	Net with stand	10.3lbs. (4.7 kg)
	Gross with stand	14.3 lbs. (6.5 kg)
<b>VESA® MOUNT</b>		200mm x 100mm
<b>REGULATIONS</b>		FCC, cUL (UL), RoHS, BETS-7, CEC, ENERGY STAR® 4.1, NRCAN, Dolby, SRS, Reach (SVHC)
<b>PACKAGE CONTENTS</b>		LCD TV display, power cable(s), remote control with batteries, Quick Start Guide, User Guide
<b>WARRANTY</b>		3-year limited warranty on parts and backlight



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

\*Adapter may be required. Analog adapter available from ViewSonic. Specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. HDMI, the HDMI logo and High Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing in the U.S. and/or other countries. SRS TruSurround HD is a trademark of SRS Labs, Inc. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2011 ViewSonic Corporation. All rights reserved. [15791-00B-08/11] VT2405LED-1

**ViewSonic®**  
See the difference® 

For more product information, visit us on the web at ViewSonic.com