

19" (18.5" viewable) LED Premium HDTV Display

Hospitality Performance in a Small Package

VT1901LED



The ViewSonic[®] VT1901LED is a professional 19" (18.5" viewable) monitor with HDTV functionality. The VT1901LED features "edge white" LED technology delivering brilliant image clarity, high contrast with saturated colors while consuming very low power. Versatile connectivity is provided through HDMI in addition to PC and traditional YPbPr component video and USB. Internal programming is offered for users wanting to set up specific product calibration. Extreme audio includes internal equalizer with SPDIF digital output.

Experience Widescreen HDTV

Enjoy a widescreen theater experience and high-definition picture quality with this display's "edge white" LED technology, 16:9 widescreen aspect ratio, true HDTV capability, and wide viewing angles.

Advanced ClearPicture[™] – Clearer, Crisper, Sharper Images

Advanced ClearPicture[™] image processing eliminates noise, increases contrast and detail and optimizes color for rich, vibrant images. High-definition images look amazing and even standard television images are unbelievably smooth and sharp.

Perfect for Hospitality Applications

This monitor is great for small screen installations, hospitality displays or applications requiring automated control. Also ideal for hotels, restaurants, sports bars or retail displays. USB multimedia, hospitality menu and cloning feature.





19" (18.5" viewable) LED Premium HDTV Display

VT1901LED



Expand Your Options with Plug-and-Play Connectivity

This HDTV provides the ultimate viewing experience with integrated HDTV tuner and plug-and-play, high-end connectivity for HD set-top boxes, DVDs, game consoles and camcorders.

OptiSync[®] Technology Now Features HDMI

Add versatility to your LCD TV with support for HDMI with high-definition content protection (HDCP) and analog (VGA) signals, plus component, composite, and TV/cable input.

Vivid Graphics, Clear Text, Stunning TV

Ultra-high brightness of 250 nits (typ), contrast ratio of 1000:1, and 1366x768 optimum PC resolution provide vibrant video and crisp data images on the desktop or in the living room.



Specifications					
LCD Panel	Type 19" (18.5" viewable) Wide Color TFT Active Matrix LCD Display Area 16.1" horizontal x 9.1" vertical; 18.5" diagonal Optimum Resolution 1366x768 Brightness 250 cd/m² (typ.) Contrast Ratio 1000:1 (typ.) Viewing Angles 170° horizontal, 160° vertical Response Time 5ms (typ.) Backlight White-light LED Backlight 30,000 hours (typ.) Aspect Ratio 16:9	CONTROLS CONT. Audio Channel Parental 		Sound mode, treble, bass, balance, surround, AVL, digital audio output, equalizer, rock, pop, jazz Channel list, favorite list, channel settings, air/cable, auto (DTV/ATV) channel search Lock parental control, V-chip, change password, keypad lock, source lock	
				Close caption, menu language, clock Blue black, no signal/operation off, all reset, audio only	
			ERGONOMICS	Tilt	0°–20°
	Panel Surface	Anti-glare, hard-coating (3H)	OPERATING CONDITIONS	Temperature Humidity	32–104°F (0–40°C) 20–80% (non-condensing)
INPUT	PC RGB analog (75 ohms, 0.7 Vp-p) TV/video TV/cable, composite (RCA), component YPbPr Audio 3.5mm mini stereo audio in, earphone out and RCA (left/right) audio in Frequency Fh: 30-64kHz, Fv: 60-85Hz Sync H/V separated (TTL) Digital HDMI with HDCP and audio support	DIMENSIONS (W x H x D)	Physical with stand Physical without stand Packaging	17.9 x 11.9 x 7.7 in. / 455.48 x 301.57 x 195 mm 17.9 x 13.6 x 2.1 in. / 455.48 x 346.18 x 53.2 mm 19.7 x 15.7 x 6.1 in. / 500 x 400 x 155 mm	
		WEIGHT	Net with stand Net without stand Gross	5.4 lb. / 2.46 kg 4.8 lb. / 2.18 kg 9.0 lb. / 4.1 kg	
	Tuner		WALL MOUNT		VESA® 100 x 100 mm
AUDIO OUTPUT	Speakers	JPEG 2.5-watt (x2)	REGULATIONS		FCC, cUL (UL), RoHS, BETS-7, Dolby, SRS, ENERGY STAR [®] , NOM
COMPATIBILITY	PC Mac®	Up to 1360x768 @ 60Hz (preferred) Up to 1360x768	RECYCLE/DISPOSAL		Please dispose of in accordance with local, state or federal laws.
INPUT SIGNAL	TV/Video Comp.	480i, 480p, 720p, 1080i, 1080p	WARRANTY		One-year limited warranty on parts, labor and backlight
CONNECTOR	Analog Digital Power	15-pin mini D-sub (VGA), composite, component HDMI, SPDIF Adapter DC 12V	What's in the box?		
POWER	Voltage Consumption	AC 100–240V (universal), +/-10% Wide Range 24W (typ) / 32W (max.)	VT1901LED LCD HDTV, power cable, remote control with batteries, User Guide, Quick Start Guide		
CONTROLS	Side Panel Controls Picture	Vol -/+, channel down/up, menu, source, power Picture mode, contrast, brightness, sharpness, tint, color, screen size, wide, cinema, zoom, normal, auto adjust, clock, phase, H/V position, color temperature, dynamic contrast, film mode, noise reduction			TU HORD "Managede"



Specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details.Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2012 ViewSonic Corporation. All rights reserved. [16055-00B-03/12] VT1901LED