

2012 VIERA®

C5 Series LED LCD



Available Model:
TC-L32C5

Screen image simulated.

720P LCD

Enjoy 720p HD resolution for vivid, lifelike images.

USB PLAYER

View your saved photos and music from the convenient USB port.

-
- 24p Playback
 - Eco Mode
 - Game Mode
 - 2 HDMI / 1 USB / 1 PC



2012 VIERA®

C5 Series LED LCD

		TC-L32C5
DISPLAY		
Screen Size Diagonal (inches)		31.5
Aspect Ratio		16:9
Number of Pixels		1,049,088 (1,366 x 768)
Panel		LCD
HDTV Display Capability (1080p, 1080i, 720p)		Y
Aspect Control		480i/p: FULL, JUST, 4:3, ZOOM 1080i/p: FULL, H-FULL, JUST, 4:3, ZOOM
PICTURE		
Viewing Angle		176 degrees
Filter		—
Panel Drive		60 Backlight Scanning
24p Playback (3:2) / 24p Smooth Film		Y / —
24p Cinematic Playback		—
ISFccc		—
Intelligent Scene Controller		Y
Pro Setting		—
Smart VIERA Engine Pro (Dual core processor)		—
	Pure Image Creation	—
	Vivid Color Creation	—
	Facial Retouch	—
	Web Contents Smoother	—
	1080p Pure Direct	—
FULL HD 3D		
3D Panel		—
3D 24p Cinema Smoother		—
2D-3D Conversion		—
Dedicated 3D Eyewear		—
AUDIO		
3D Real Sound		—
Number of Speakers		2
Audio Output		10 W
Surround Sound		AV Surround
JACKS		
Integrated ATSC Tuner		Y
HDMI Input	Support Feature	2
SD Card		—
USB 2.0		1
Analog Audio Input (for HDMI / DVI)		Y (Mini jack)
Composite Video Input shared with Component		RCA x 1
Audio Input (for Composite Video)		RCA x 1
PC Input		D-sub 15-pin x 1
Component Video Input (Y, P _r , P _b) shared with Composite		RCA x 1
Audio Input (for Component Video)		RCA x 1
Ethernet		—
Digital Audio Output		1
FEATURES		
VIERA Connect™ (IPTV)		—
Online Movies		—
Web Browser		—
Skype™ While Watching TV		—
Multitasking		—
Social Networking TV (Facebook / Twitter)		—
VIERA Remote App Support		—
VIERA Touch Pad Controller		—
Wireless LAN Adaptor		—
DLNA		—
Media Player	Support Format	Y (USB) JPEG / MP3
VIERA Link		—
VIERA Tools		—
Eco Mode		Y
Game Mode		Y
Trilingual Menu (English / Spanish / French)		Y
Built-In Closed Caption Decoder		Y
Off-Timers		Y
E-Help		—
GENERAL		
Power Supply		AC 110-127 V, 60 Hz
On Mode Average Power Consumption		—
Receiving System		ATSC / QAM / NTSC
Dimensions with Stand	Height (inches (mm)) Width (inches (mm)) Depth (inches (mm))	
Dimensions without Stand	Height (inches (mm)) Width (inches (mm)) Depth (inches (mm))	
Weight with Stand (lbs (kg))		
Weight without Stand (lbs (kg))		
Carton Dimensions	Height (inches (mm)) Width (inches (mm)) Depth (inches (mm))	
Gross Weight (lbs (kg))		
Operating Temperature		32°F-95°F (0°C-35°C)
Safety Standard		US: UL60065/FCC Part15, CANADA: CSA C22.2/IC BE15-7
Swivel Angle		—
VESA Compatible		Y
Optional Wall-mounting Bracket Model Numbers		TY-WK3L2RW
Glass & Metal Design		—

*with Special Adapter Cable (dedicated)

03/12 Specifications subject to change without notice.

Panasonic
ideas for life

VIERA

Official Worldwide
Olympic Partner

