



Seiki Digital Inc.

Update Date: 6/May/13

Version: A

Model Number: SE32FY22	32 inch LED Full-HDTV	Features	
UPC Code	819456010286	Built in 3D PAL/NTSC Comb Filter	
Display Features		Built in 3D Video Noise Reduction	
Diagonal Panel Size	31.5 inch	Built in BTSC/SAP	
Active Area	698.40mm (H) X 392.85mm (V)	Over-The-Air ATSC/NTSC RF Input Support	
Aspect Ratio	16:9	Digital/Analog Channel auto tuning	
Panel Resolution	1920 X 1080	Support V-CHIP/CCD/Favorite Channel Edition	
Panel Refresh Rate	60Hz	Component & HDMI support :480I,576I,480P,576P,720P,1080I ,1080P	
Brightness	200cd/m ² (Typical)	USB Support File Format: only for updating software	
Dynamic Contrast ratio	2000:1 (Typical)	OSD Language: English/French/Spanish	
Viewing Angle	±178°	Accessories Included	
Dot Pitch	0.36mm (H) X 0.36mm (V)	Remote Control / Battery Included	
Maximum Color	16.7 (10-Bit)	User Manual / Quick Start Guide	
Response time Gray-Gray	6.5ms	Power Requirements	
Electronics		Power Source	AC100-240V 50/60Hz
Scaler Solution	MSD3393	Power ON consumption	<65W
DNR	3D	Standby consumption	<0.5W
Digital Comb Filter / Type	3D	Operating Temperature	5°C -35°C
TV System & Video Standards Supported		Operating Humidity	20%-80%
TV System	ATSC/NTSC M	Dimension (WxHxD) inch	
Channel CATV - UHF/VHF (ATV)	AIR: 2-69;Cable: 1-135	VESA Dimension (WxH)	100mm x 100mm
Composite / S-Video input	PAL/NTSC	Unit w/ Stand	29.09"x19.37"x6.30"
Video Connections		Unit w/o Stand	29.09"x17.44"x3.35"
Analog&Digital TV Tuner	x1	Carton	32.28"x22.44"x6.46"
Composite Video Input	1(Y terminal will be the same)	Weight (lbs)	
S-Video Input (4pin DIN)	NO	Net Weight w/Stand	12.57 Lbs
Component Input (Y,Cb,Cr/Y,Pb,Pr)	x1	Net Weight w/o Stand	10.91 Lbs
VGA Input (15 pin D-Sub)	x1	Gross Weight	16.53 Lbs
DVI-D / DVI-I Input	NO	Warranty & Support	
HDMI Input	x3	One Year Manufacture Warranty	
USB	x1 (only for upgrade)	Toll Free Customer Support	
Audio		On-Line Manual / Firmware Access	
Maximum Audio Output	2x8W	Logistic	
Number of speakers	x2	Standard Pallet Unit Load	
Audio Surround	Yes	20' GP Container Unit Load w/o Pallet	392
Audio Connections		40' GP Container Unit Load w/o Pallet	800
Stereo Mini Phono Jack Input (3.5mm)	x1(VGA Audio)	40' HQ Container Unit Load w/o Pallet	800
RCA Input	x1(R/L)		
Headphone: Stereo Mini (3.5mm)	x1		
RCA Output	NO		
Coax Digital Output	x1		
VGA Resolutions Supported			
640x480			
800x600			
1024x768			
1360x768			
1920x1080			

This spec may change from time to time, we are not liable for any misrepresentation if we post the wrong specs on the sheet