



VENUS T5c mini

5-Bay SATA RAID Enclosure

- EZ-RAID setup DIP switch
- Support Hot Swap and Hot Spare on RAID
- Supports JBOD, Clone, RAID 0, 1, 3, 5 and 10
- SATA II Port Multiplier backplane
- Combo interface: eSATA + USB 3.0
- JMB393 Hardware-accelerated RAID Engine
(No drivers or BIOS required for RAID and compatible to x86/x64 platforms)



EZ-RAID setup switch does not required any drivers or BIOS for RAID operation.

T5c mini takes up less space on your desk plus easy to carry around for your business travel. Now available in a combo version to support (eSATA + USB 3.0). Once configured in non-RAID or RAID, data can be accessed from either interface. USB 3.0 is also backward compatible to USB 2.0 speed.



Software Management Console (GUI)

- Event logging
- Remote monitoring
- Email notification (Hardware Failure)
- JBOD, Clone, RAID 0, 1, 3, 5 and 10
- Support on-line Auto-Rebuild (200GB/hour)
- Support Hot Swap and Hot Spare on RAID



Hardware RAID JMB393 Chipset



POWER ADAPTER
20w (100-240Vac) 50/60Hz



(EZ-RAID Switch)
eSATA + USB 3.0

MODEL: (DS-2250C)

- Capacity:*** up to 3.7TB (Terabyte)
- Port Multiplier Host Interface:** eSATA (3.0Gbit/s) and USB 3.0 (5.0Gbit/s)
- Disk Interface:** SATA connector
- Disk Drive Tested:**** 160GB to 750GB HDD (9.5mm)
- Interface Transfer Rate:***** 1.5Gbit/s & 3.0Gbit/s
- Software:** Management Console (GUI)
- Supported RAID levels:** JBOD, RAID 0, 1, 3, 5 and 10
- Supported OS (32-bit/64-bit):** Windows 2000/2003/XP/Vista/Win7 Ultimate / Mac OS 10.5 or later
- I/O Control:** Power and Mult- Colored HDD LED
- Cooling:** 5x5cm Fan (ball-bearing)
- Operating Temperature:** 5° to 35° C, Humidity 20 to 80% No Condensation
- Power Supply:** 20w, AC (100-240Vac) 50/60Hz Power Adapter
- Material/Color:** Brush Aluminum Anodized Black
- Dimensions (LxWxH):** 5.5" x 3.1" x 4.9"
- Weight:** 1.35 lbs (net wt.)
- Warranty:** 1 year

* 1GB (gigabyte) = 1 billion bytes. 1TB (terabyte) = 1000GB. Actual capacity varies depending on operating environment. (typically 5-10% less).
 ** Tested with SATA I/II (Seagate, Hitachi, Western Digital and Toshiba). Note: Samsung 750GB does not fit since it is based on 12.5mm design)
 *** Specifications vary depending upon the selected RAID configuration (storage policy). Maximum capacities and sustained transfer rates were rated in (RAID 0) (Windows XP will not recognize single volumes greater than 2TB). A GPT partition is required in Windows Vista / Windows 7 to go beyond 2TB.
 VENUS DS2, DS3, DS5, DS3R, DS3RPRO, T4, T4U, T4S, T5, T5J and T5C are trademarks of American Media Systems, Inc.
 ©2010 American Media Systems, Inc. (AMSElectronics). Other names or brands herein maybe be trademarks or registered trademarks of their respective owners.

