

Solutions	Products and Services	Support	Your Business	Company
You are here: Home > Products	> Power Distribution > Rack-mount T	ransfer Switches		
Product Category Rack Power Distribution (6) Row Power Distribution (6) Room Power Distribution (1) Transfer Switches > Wall-mount Transfer Switches > Rack-mount Transfer Switches	Rack-mount Transfer Rack ATS, 100-120V, 15A, 8	5-15P In, (10) 5-15R C APC Rack-moi Connections: N ), Output: 100\ Includes: Rac Standard Lear	Dut unt Transfer Switches, Input: 100V, 120\ NEMA 5-15P, Cord Length:8 feet ( 2.44 r /, 120V, Output Connections: NEMA 5-1 k Mounting brackets, User Manual d Time: Usually in Stock	neters
Return to Power Distribution	More Images		Software & Firmware Options	
	Technical Specifications Proc	duct Overview Docume	entation Software & Firmware Options	
	Nominal Output Voltage Maximum Total Current Dra Phase	100V, 120V aw per 15A	/	
	Output Connections	(10) NEMA	5-15R	
	Input Nominal Input Voltage	100V, 120V	,	
	Input Frequency	50/60 Hz		
	Regulatory Derated Input C (North America)			
	Input Connections	NEMA 5-15	5P	
	Cord Length	2.44 meters	3	
	Number of Power Cords	2		
	Acceptable Input Voltage	100-125 VA	٨C	
	Maximum Input Current per	phase 15A		
	Load Capacity	1440 VA		
	Physical			
	Net Weight	4.70 KG		
	Maximum Height	44.00 mm		
	Maximum Width	432.00 mm		
	Maximum Depth	236.00 mm		
	Shipping Weight	6.48 KG		

114.00 mm

600.00 mm

356.00 mm

Shipping Height

Shipping Width

Shipping Depth

Calar	Diask
Color	Black
Environmental	
Operating Environment	-5 - 45 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters
Conformance	
Regulatory Approvals	FCC Part 15 Class A, ICES-003, TUV-C, TUV-NURTL, VCCI Class A
Standard Warranty	2 years repair or replace
Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs
Battery Directive	Compliant
Battery Notes	Contains Lithium Battery

©APC by Schneider Electric