

VS92A VS94A VS98A

2/4/8-Port Video Splitter

Send High Quality 1920 x 1440 Video to Multiple Destinations at 350MHz



- One video input to 2/4/8 video outputs
- Supports VGA, SVGA, XGA, SXGA, UXGA, QXGA, WUXGA and multisync monitors
- DDC, DDC2, DDC2B Compatible (Port 1 only)
- Long distance transmission – up to 65 m
- All metal casing

Advantages

- Supports up to 350 MHz bandwidth (VS92A/VS94A), 300MHz bandwidth (VS98A) for high performance video
- Expandable – provides up to 8/64/512 video displays
- Superior video quality – up to 1920 x 1440 @ 60Hz

VS82 VS84 VS88

2/4/8-Port Video Splitter

Compact Design with Convenient Topside Connections




- One video input to 2/4/8 video outputs
- Supports VGA, SVGA, XGA, SXGA, UXGA, QXGA, WUXGA and multisync monitors
- DDC, DDC2, DDC2B Compatible (Port 1 only)
- Long distance transmission – up to 65 m
- Compact design with convenient topside connection, lays flat on a desktop or mounts on the wall

Advantages

- Supports up to 250 MHz bandwidth for high performance video
- Expandable – provides up to 8/64/512 video displays
- Superior video quality – up to 1920 x 1440 @ 60Hz (VS82/VS84); 1600 x 1200 @ 60Hz (VS88)

Setup ►►► VS94A



Accessories

1. VGA Cable: 1.8 m x 1 (optional) (VS82/VS84/VS88)
2. Power Adapter:
 - DC5V x 1 (VS132A/VS134A/VS138A);
 - DC5.3V x 1 (VS132);
 - DC9V x 1 (VS92A/VS94A/VS98A, VS82/VS84/VS88)