

# Antec HCP-1300 Platinum (0-761345-06260-2)

HCP-1300 Platinum EC, 1300W, 110 - 240V AC, 50Hz - 60Hz, 7A - 15A



## Price details:

Price excl. VAT: 284.15 €

Eco fees: 0.04 €

VAT 21 %: 59.68 €

## Product details:

Product code: 0-761345-06260-2

EAN: 0761345062602

Manufacturer: Antec

PDF generated on: 17 January, 2016



# 343.87 €

\* VAT included

Antec's High Current Pro Platinum series is the pinnacle of power supplies. High Current Pro Platinum is fully modular with a revolutionary 20+8-pin MBU socket for the needs of tomorrow. By using a PSU that is 80 PLUS® PLATINUM & ErP Lot 6: 2013 certified, operating up to 94% efficient, you can reduce your electricity bill by up to 25% when compared to many other power supplies. HCP Platinum's innovative 16-pin sockets create a new level of flexibility by doubling the modular connectivity, supporting two different 8-pins connectors and even future connectors of 10, 12, 14 or 16-pins.

## Main specifications:

### Power

Nominal power:	1300 W
AC input voltage:	110 - 240 V
Voltage tolerance:	10 %
AC input frequency:	50 - 60 Hz
Input current:	7 - 15 A
Maximum input current (@110V):	+12V1,+12V2,+12V3,+12V4,+3.3V,+5V,+5Vsb,-12V A
Power Factor Correction (PFC) type:	Active
Combined power (+3.3V):	130 W
Combined power (+5V):	130 W
Combined power (-12V):	6 W
Combined power (+5Vsb):	15 W
Max output current (+3.3V):	25 A
Max output current (+12V1):	50 A
Max output current (+12V2):	50 A
Max output current (+12V3):	50 A
Max output current (+12V4):	50 A
Max output current (+5V):	25 A
Max output current (-12V):	0.5 A
Max output current (+5Vsb):	3 A
Efficiency:	94 %
Power protection features:	Over current,Over power,Over voltage,Overheating,Short circuit,Under voltage

### Cooling

Fan diameter:	135 mm
Number of fans:	1
Fan location:	Top
Cooling type:	Active

### Ports & interfaces

Motherboard power connector:	24-pin ATX
Number of SATA power connectors:	9
Peripheral (Molex) power connectors (4-pin):	6

EPS power connector (8-pin):	Y
PCI Express power connectors (6+2 pin):	10
CPU power connector (4+4 pin):	Y
Floppy drive power connector:	1
CPU power connectors (8-pin):	1
PCI Express connector:	Y
Floppy disk drive connector:	Y
Cabling type:	Modular
<b>Performance</b>	
Purpose:	PC
ATX version:	2.32
EPS version:	2.92
Parallel processing technology support:	2-Way CrossFireX,2-Way SLI
<b>Design</b>	
Colour of product:	Black
<b>Operational conditions</b>	
Operating temperature (T-T):	0 - 50 °C
<b>Weight &amp; dimensions</b>	
Width:	150 mm
Depth:	190 mm
Height:	86 mm
Weight:	2200 g
<b>Certificates</b>	
80 PLUS certification:	80 PLUS Platinum
Safety:	UL, cUL, CB, CE, FCC, TUV, BSMI, CCC, C-Tick, GOST-R

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.